

# PRIME

engineering handbook engineering  
handbook engineering handbook  
book engineering handbook engin  
engineering handbook engineering  
book engineering handbook engin  
engineering handbook engineering  
ok engineering handbook engine  
engineering handbook engineering  
book **engineering handbook** engin  
handbook engineering handbook  
engineering handbook engineering

PRIME ENGINEERING HANDBOOK

for

PRIME P400, P500; PRIMOS IV, V

June, 1978

PE-T-500 REV 0

PRIME ENGINEERING HANDBOOK

This revision corresponds to PRIMOS REV 15.

This is the initial release of the Prime Engineering Handbook, a document produced and maintained by Prime Computer Research and Development. Comments and requests to be added to the distribution list for handbook updates should be addressed to Maggie Chianese, Documentation Administrator, Prime Computer Research and Development, 3 Newton Executive Park, Newton, MA 02162 (617-964-1730, x215).

Published by Prime Computer, Incorporated  
145 Pennsylvania Ave., Framingham, MA 01701

June 21, 1978

All Rights Reserved.

The information contained in this handbook is subject to change without notice. Prime Computer Incorporated assumes no responsibility for errors that may appear in this document. This handbook is intended for the use of Prime employees only.

Copyright 1978 by Prime Computer, Inc.

PE-T-500 REV 0

Table of Contents

1	<u>INTRODUCTION</u> .....	1	7	<u>PERIPHERAL I/O</u> .....	101
	OVERVIEW.....	1		ADDRESSES.....	101
	SYNTAX.....	1		AMLC.....	102
2	<u>CENTRAL PROCESSING UNIT</u> .....	3		ASR.....	102
	ARGUMENT POINTER (AP).....	3		DISK CONTROLLERS.....	103
	CHECKS.....	3		DMX CONTROL WORDS.....	107
	CONCEALED STACK/QUEUE.....	4		MAGTAPE.....	108
	DIAGNOSTIC STATUS WORD (DSW).....	4		PROGRAMMED I/O (PIO).....	109
	DMQ.....	5	8	<u>PRIMOS IV</u> .....	111
	DESCRIPTOR TABLE ADDRESS REGISTER (DTAR).....	5		ABORT FLAGS.....	111
	ENTRY CONTROL BLOCK (ECB).....	6		COMMONS.....	111
	FAULTS.....	6		ERRVEC.....	111
	INDIRECT POINTER (IP).....	6		FIGCOM.....	112
	KEYS, MODALS.....	7		INTERNAL CALLING SEQUENCES.....	112
	MODALS.....	7		LOCKS, LCKCOM.....	116
	PAGE MAPS (HMAP, LMAP).....	8		MMAP (MEMORY MAP).....	116
	PANEL.....	8		PTUSEG.....	116
	PROCESS CONTROL BLOCK (PCB).....	9		PUDCOM.....	117
	READY LIST.....	10		SEGMENT USAGE BY PRIMOS.....	118
	REGISTERS.....	11		SEMAPHORES (SEMCOM).....	119
	RSAV FORMAT.....	13		SVC INTERLUDE.....	119
	SECTOR 0 (P300 only).....	14		USRCOM.....	119
	SEGMENT DESCRIPTOR WORD (SDW).....	14		VQUTM.....	120
	SEMAPHORES.....	15	9	<u>SVC INFORMATION</u> .....	121
	STACK FRAME, STACK ROOT.....	15		SVC CALLING SEQUENCES.....	121
	WAIT LIST.....	15		SVC NUMBERS.....	138
3	<u>COMMANDS</u> .....	17		ERROR MESSAGES AND CODES (SYSCOM>ERRD.F).....	139
4	<u>FILE SYSTEM INTERNALS</u> .....	65	10	<u>APPENDICES</u> .....	141
	DSKRAT FORMATS.....	65		ASCII CHARACTER SET.....	141
	RECORD HEADER FORMATS.....	65		CONVERSION TABLES.....	143
	UPD HEADER AND ENTRY FORMATS.....	67		POWERS OF TWO.....	146
	SEGMENT DIRECTORY FORMATS.....	69	11	<u>GLOSSARY</u> .....	149
5	<u>INSTRUCTION SET</u> .....	71	12	<u>INDEX</u> .....	155
6	<u>OPERATIONAL PROCEDURES</u> .....	93			
	BOOT PROCEDURES.....	93			
	BOOT TERMINAL SPEED SELECTION.....	94			
	TYPICAL SWITCH SETTINGS FOR DISK BOOTS.....	94			
	COLD START (PRIMOS IV,V).....	95			
	HALTS.....	96			
	MEMORY PARITY ERRORS.....	97			
	MEMORY/REGISTER DISPLAY.....	97			
	MEMORY SCAN.....	98			
	TAPE DUMP.....	98			
	WARM START.....	99			

1 INTRODUCTIONOVERVIEW

This handbook provides a summary of information needed for the development and maintenance of Prime P400 and P500 hardware and software systems. While this book contains information useful to a general user community, the information is presented in very condensed form. It is assumed that the reader has had prior contact with this material and, therefore, that detailed descriptions are unnecessary.

Some of the information contained herein pertains only to the latest revision of PRIMOS. This information will be updated on a regular basis as new revisions are released. (Refer to the inside of the cover for the revision currently reflected in this version of the handbook.) Readers are strongly urged to report errors, discrepancies, and omissions as soon as they are noticed.

SYNTAX

The descriptions of commands and external programs use the following syntax:

Abbreviations

Uppercase letters represent minimal abbreviations for commands and options. (When actually typing the command or option, either uppercase or lowercase can usually be used. Exceptions are noted.) For example:

COMOutput

specifies the COMOUTPUT command. COMO, COMOU, COMOUTP, etc., also specify this command.

Command Line Variables

Greater-than (>) and lesser-than (<) signs surrounding a string indicate a variable for which specific information is to be substituted; for example:

<filename>

should be replaced with a valid filename. Notice, however, that the use of greater-than and lesser-than signs in treenames is literal.

Optional Parameters

Brackets enclose optional parameters for a command; for example:

SHutdn [ ALL ]

Alternative Operand Specification, Defaults

When an operand has more than one possible specification, choices are stacked. A default option, if any, is underscored; for example:

OPRpri [ 1 ]  
[ 0 ]

The OPRPRI command accepts a single parameter of 1 or 0. If none is specified, the default parameter is 0.

Repeated Operands

Ellipsis indicate an operand that may be repeated one or more times; for example:

Close <funit> ...

The CLOSE command accepts one or more file unit specifications (separated by blanks or commas).

2 CENTRAL PROCESSING UNITARGUMENT POINTER (AP)

```

1          16 1          16
|B|BBB|I-Z|ZLS|---|---|P|PPP|PPW|WWW|WWW|WWW|

```

BBBB Bit Number  
I Indirect  
ZZ Base Register: 00 - PB  
                  01 - SB  
                  10 - LB  
                  11 - XB  
L Last AP in arglist  
S Store  
P..W Page/Word Disp from Base Reg

Typical values, first word:

100	PB Rel.	4100	PB Rel. Indirect
300	PB Rel. Last	4300	PB Rel. Indirect Last
500	SB Rel.	4500	SB Rel. Indirect
700	SB Rel. Last	4700	SB Rel. Indirect Last
1100	LB Rel.	5100	LB Rel. Indirect
1300	LB Rel. Last	5300	LB Rel. Indirect Last
1500	XB Rel.	5500	XB Rel. Indirect
1700	XB Rel. Last	5700	XB Rel. Indirect Last

CHECKS

CHECK HEADER (4 WORDS): PBH,PBL,KEYS,MODALS

4/200 Power Fail  
4/270 Memory Parity  
4/300 Machine Check  
4/310 Missing Memory Module

On entry to fault handler, mode=64V, MCM=0 for all but ECC, for which MCM=MCM-at-check - 1.

MCMOD interrupts any other check in progress.

MCHK and ECCU interrupt ECCU in progress if MCM=2 (QUIET).

CONCEALED STACK/QUEUE

(Valid only between time of fault and subsequent CALF instruction.)

PCB+'74 --> FIRST	+0	PBH
PCB+'75 --> NEXT	+1	PBL
PCB+'76 --> LAST	+2	KEYS
	+3	FCODE
	+4	FADDRH
	+5	FADDRL

(PB, KEYS are those of procedure causing the fault.)

DIAGNOSTIC STATUS WORD (DSW)

DSWRMA: R34 DSWSTAT: R35 DSWPB: R36

DSWSTATH:

1	100000	CI - Check Immediate
2	040000	MC - Machine Check
3	020000	MP - Memory Parity (ECC)
4	010000	MM - Missing Memory
5-7	007000	Machine Check Code (Valid if bit 8=1):
	xx0xxx	Peripheral Data (BPD) Output
	xx1xxx	Peripheral Addr (BPA) Input
	xx2xxx	Memory Data (BMD) Output
	xx3xxx	Cache Data (RCD)
	xx4xxx	Peripheral Addr (BPA) Output
	xx5xxx	RDX-BPD Input
	xx6xxx	Memory Address (BMA)
	xx7xxx	Register File (RF)
8	000400	Not RCM Parity (P500, XCS)
9	000200	ECCU -- ECC Uncorrectable Error
10	000100	ECCC -- ECC Correctable Error
11	000040	BPUP Invalid -- RP Backup Count Invalid
12-14	000034	RP Backup Count -- Sub from DSWPB
15	000002	Check During DMX
16	000001	IO Bus -- DMX, PIO, u-code check

DSWSTATL:

```

1-5 174000 ECCB Syndrome*:
    000xxx MB 100xxx MB
    004xxx MB 104xxx 7
    010xxx MB 110xxx MB
    014xxx 15 114xxx 3
    020xxx MB 120xxx MB
    024xxx 14 124xxx 2
    030xxx 13 130xxx 1
    034xxx 9 134xxx C2
    040xxx MB 140xxx 8
    044xxx MB 144xxx 6
    050xxx MB 150xxx 5
    054xxx 12 154xxx C5
    060xxx 16 160xxx 4
    064xxx 11 164xxx C4
    070xxx 10 170xxx C3
    074xxx RP,C1 174xxx NE
6 002000 OP -- Overall Parity
7 001000 Unused
8 000400 Mod # (L.O. addr bit of module in err)
9 000200 RMA Invalid
10 000100 Unused
11-16 000077 U-Verify Test Number
    
```

\*\*\* U-Verify Test Number \*\*\*  
to be supplied at next update

\* MB=Multibit, RP,LP=Right/Left Parity,  
Cn=Check Bit n, NE=No Errors

See Micro Code Handbook for additional information.

DMQ

See DMX under Peripheral I/O.

DESCRIPTOR TABLE ADDRESS REGISTER (DTAR)

```

1 16 1 16
|S|SSS|SSS|SSS|AAA|AAA|A*|A*AA|AAA|AAA|AAA|AAA|
    
```

S...S 1024 - # SDWs in Table.  
A...A High Order 21 bits of Physical Addr of Table.  
(Bit 22 taken as zero.)

\*: bits 1 and 2 of the second word must be equal.

ENTRY CONTROL BLOCK (ECB)

0	PROCEDURE	
1	BASE	
2	STACK FRAME SIZE	
3	SN OF STACK ROOT	(0 => USE CURRENT)
4	DISP OF ARGLIST IN S.F.	
5	NUMBER OF ARGUMENTS	
6	LINK	
7	BASE	
10	KEYS	

Locations '11 through '17 are set to 0.

FAULTS

FCODEH: CRS 26H FADDR: CRS 27

FAULT	#	OFFSET	VECT	FCODEH	FADDR	RING	SAVED	PB
RXM	0	0	62	---	addr	curr	backed	
PROCESS	1	4	63	ABFLAGS	---	0	curr	
PAGE	2	10	64	---	addr	0	backed	
SVC	3	14	65	---	---	curr	backed	
UII	4	20	66	cur PBL	addr	curr	backed	
ILL	10	40	72	cur PBL	addr	curr	backed	
ACCESS	11	44	73	code	addr	0	backed	
ARITH	12	50	74	code	addr	curr	curr	
STACK	13	54	75	code	addr	0	backed	
SEGMENT	14	60	76	code	addr	0	backed	
POINTER	15	64	77	code	ptr addr	curr	backed	

INSTRUCTION SET

See Section 5.

INDIRECT POINTER (IP)

```

1 16 1 16
|F|RRR|SSS|SSS|SSS|SSS|P|PPP|PPW|WWW|WWW|WWW|
    
```

F 1 => Missing Pointer  
RR Ring Number (00-11)  
E 1 => Word 3 = bit number: BBBB-----  
S..S Segment Number  
P..W Page Number/Word Number

(As effective address in a base reg, F,E ignored.)

KEYS, MODALS

(CRS 24 RFILE 124,164 CRASH 50,150)

KEYSH (Keys):

1 100000 C Bit  
 2 040000 Double Precision  
 3 020000 Link Bit (L)  
 4-6 016000 Addressing Mode:  
     x00xxx 16S  
     x02xxx 32S  
     x04xxx 64R  
     x06xxx 32R  
     x10xxx 32I  
     x14xxx 64V  
 7 001000 FLEX (0 => Allow Fault)  
 8 000400 IEX (Integer Exception)  
 9 000200 CCLT (condition code)  
 10 000100 CCEQ (condition code)  
 11-14 000074 Unused  
 15 000002 ID (In Dispatcher)  
 16 000001 SD (Save Done)

KEYSL (Modals):

1 100000 ENB (1 => Enable Interrupts)  
 2 040000 VIM (1 => Vectored Int. Mode)  
 3-8 037400 Unused  
 9-11 000340 CRS: xxx00x => Reg File 2  
     xxx04x => Reg File 3  
 12 000020 MIO (1 => Mapped I/O)  
 13 000010 PXM (1 => Process Exchange Mode)  
 14 000004 SEG (1 => Segmentation Mode)  
 15-16 000003 MCM (Machine Check Mode):  
     xxxxx0 None  
     xxxxx1 Memory Parity  
     xxxxx2 Quiet  
     xxxxx3 Record

MODALS

See KEYS (KEYSL).

PAGE MAPS (HMAP, LMAP)

Starts at 4/4000. HMAP, LMAP interleaved in 64-word chunks, thus 128 words/segment in system.

HMAP (Hardware Map):

1 100000 1 => Page Resident.  
 2 040000 1 => Page Referenced.  
 3 020000 0 => Page Modified.  
 4 010000 1 => Shared Page (inhibits cache).  
 5-16 007777 H.O. 12 bits of physical page addr.  
     (Bits 13-22 taken as zero.)

If non-resident, bits 3,5 software defined:

3,5 024000 Page status:  
     000000 Not resident, copy on disk  
     020000 Not resident, no copy on disk  
     004000 In transition, coming in  
     024000 In transition, going out

LMAP (Software Map -- HMAP+'100):

1-2 140000 Lock ctr 0 = unlock, not 0 = locked  
 3 020000 First Time (just paged in)  
 4 010000 Use alternate paging device  
 5-16 007777 Record index (1 val/8 pages)

SEGMENT PAGE MAP LOCATION

0	4000
1	4200
4	4400
5	4600
6	5000
7	5200
10	5400
11	5600
12	6000
6000	6200

PANEL

See MEMORY/REGISTER DISPLAY under OPERATIONAL PROCEDURES.

PROCESS CONTROL BLOCK (PCB)

(See also PCBs under PRIMOS IV.)

0	LEVEL (IN READY LIST)	40	GR7
1	LINK (NEXT PCB IN LIST)	41	"
2	WAIT LIST SN (0=>READY)	42	FP0
3	WAIT LIST WORD NUMBER	43	"
4	ABORT FLAGS	44	"
5	RESERVED	45	"
6	RESERVED	46	FP1
7	RESERVED	47	"
10	ELAPSED TIMER (LOW)	50	"
11	ELAPSED TIMER (HIGH)	51	"
12	DTAR2H	52	PBH
13	DTAR2L	53	PBL
14	DTAR3H	54	SBH
15	DTAR3L	55	SBL
16	INTERVAL TIMER	56	LBH
17	RESERVED	57	LBL
20	SAVE MASK	60	XBH
21	KEYS	61	XBL
22	GR0	62	FAULT VECTOR, RING 0
23	"	63	"
24	GR1	64	FAULT VECTOR, RING 1
25	"	65	"
26	GR2	66	RESERVED
27	"	67	"
30	GR3	70	FAULT VECTOR, RING 3
31	"	71	"
32	GR4	72	PAGE FAULT VECTOR
33	"	73	"
34	GR5	74	CONCEALED STACK FIRST
35	"	75	CONCEALED STACK NEXT
36	GR6	76	CONCEALED STACK LAST
37	"	77	RESERVED

READY LIST

PPA current level/current PCB  
 PPB next level/next PCB  
 LEVELn --> FIRST PCB ON LEVELn  
 LEVELn+1 --> LAST PCB ON LEVELn  
 PCB+0 --> LEVEL THIS PCB IS ON  
 PCB+1 --> NEXT PCB, 0 IF LAST

Ready list in Segment 4, starting at 4/600:

<u>LEVEL</u>	<u>PCBS ON LEVEL</u>
600	CLOCK PROCESS
602	SMLC PROCESS
604	AMLC PROCESS
606	MPC, MP2 PROCESSES
610	VERSATEC PROCESS
612	IPC PROCESS
614	RINGNET PROCESS
616	SPARE1, SPARE2 PROCESSES
620	SUPERVISOR PROCESS (USER 1)
622	PRIORITY 3 USER PROCESSES
624	PRIORITY 2 USER PROCESSES
626	PRIORITY 1 USER PROCESSES (NORMAL LEVEL)
630	PRIORITY 0 USER PROCESSES
632	BACKSTOP PROCESS



RSAB FORMAT

Registers as saved/restored by the RSAB/RRST instructions.

0	SAVE MASK	SAVE MASK (1=>REG SAVED):
1	FRN1	
3	FR1	1-4 170000 Unused
5	FRN0	5 004000 FRN1
7	FR0	6 002000 FR1
11	GR7	7 001000 FRN0
13	GR6	8 000400 FR0
15	GR5	9 000200 GR7
17	GR4	10 000100 GR6
21	GR3	11 000040 GR5
23	GR2	12 000020 GR4
25	GR1	13 000010 GR3
27	GR0	14 000004 GR2
31	X-BASE	15 000002 GR1
		16 000001 GR0

(XB always saved.)

SECTOR 0 (P300 only)

0	X Register (Index Register)
1	A Register (Arithmetic, Shifts, I/O)
2	B Register (Ext Arithmetic, Shifts)
3	Stack Pointer
4	FLPH (Floating Point High)
5	FLPL (Floating Point Low)
6	VSC (Visible Shift Counter)
7	P Register (Program Counter)
10	PMAR (Page Map Address Register)
11	Microcode Scratch Location
12	EAS (Effective Addr Save - ILL, UII, Ints)
13	Microcode Scratch Location
14	Y Register Save (Control Panel, DMA)
15	M Register Save (Control Panel, DMA)
16	Microcode Scratch Location
17	Microcode Scratch Location
20-37	DMA Range/Start Address Pairs
40-47	Reserved for DMC Channel Pairs
60	PFI (Power Fail Int, Watchdog Timer)
61	RTCI (Real Time Clock Increment)
62	REVI (Restricted Execution Violation Int.)
63	Standard Interrupt (Compatible Mode)
64	Page Fault Interrupt
65	SVC Interrupt
66	UII (Unimplemented Instruction Interrupt)
67	Memory Data Parity Error
70	Machine Check
71	Missing Memory Module
72	Illegal Instruction Interrupt
73	Page Write Violation
74	FLEX (Floating Point Exception)
75	Procedure Stack Underflow (300 Only)
76-100	Debugging Scratch Area
101-177	Interrupt Vectors (Vectored Interrupt Mode)
200-777	General Cross Sector Links

SEGMENT DESCRIPTOR WORD (SDW)

1	16	1	16
P PPP PPP PPP 000 000 F AAA BBB CCC PPP PPP			
7	22	1	6

P...0 Page number/Word number of pagemap  
 F Fault, 1 => No segment or missing pagemap  
 AAA Access controls for Ring 1: 000 No access  
 BBB Access controls for Ring 2 001 Gate  
 CCC Access controls for Ring 3 010 Read  
 011 Read/Write  
 100 Reserved  
 101 Reserved  
 110 Read/XEQ  
 111 R/W/XEQ

## REGISTERS

RFIL ADDR = Address in Register File  
 CRASH ADDR = Disp in hardware register save area.

RFIL	CRASH	RFIL	CRASH		
ADDR HIGH	LOW	ADDR HIGH	LOW		
0	TR0	-	300	40	200
1	TR1	-	302	41	202
2	TR2	-	304	42	204
3	TR3	-	306	43	206
4	TR4	-	310	44	210
5	TR5	-	312	45	212
6	TR6	-	314	46	214
7	TR7 (PB)	-	316	47	216
10	GRMX1	-	320	50	220
11	GRMX2	-	322	51	222
12		RATMPL	324	52	224
13	RSGT1	-	326	53	226
14	RSGT2	-	330	54	230
15	RECC1	-	332	55	232
16	RECC2	-	334	56	234
17		REOIV	336	57	236
20	ZERO	ONE	340	60 (20)	(21) 240
21	PBSAVE	-	342	61	242
22	GRMX3	-	344	62 (22)	(23) 244
23	GRMX4	-	346	63	246
24	C377	-	350	64 (24)	(25) 250
25		-	352	65	252
26		-	354	66 (26)	(27) 254
27		-	356	67	256
30	PSWPB	-	360	70 (30)	(31) 260
31	PSWKEYS	-	362	71	262
32	PLA:PPA	PCBA	364	72 (32)	(33) 264
33	PLB:PPB	PCBB	366	73	266
34	DSWRMA	-	370	74 (34)	(35) 270
35	DSWSTAT	-	372	75	272
36	DSWPB	-	374	76 (36)	(37) 274
37	RSVAPTR	-	376	77	276

() indicate P300 address mapping

TR7 PB at machine halt  
 PSWPB PB at last interrupt  
 PSWKEYS Keys at last interrupt  
 PPA Current level/current PCB  
 PPB Next level/next PCB  
 RSVAPTR Reg save area ptr. 0 => regs saved.

See Micro Code Handbook for additional information.

CRS	RF2	CRASH	RF3	CRASH	
ADDR HIGH	LOW	ADDR	ADDR2	ADDR	ADDR3
0	GR0:OLTL	-	100	0	140 100
1	GR1:PTS	-	101	2	141 102
2	GR2 (1,A,LH)	-(2,B,LL)	102	4	142 104
3	GR3 (EH)	-(EL)	103	6	143 106
4	GR4	-	104	10	144 110
5	GR5 (3,S,Y)	-	105	12	145 112
6	GR6	-	106	14	146 114
7	GR7 (0,X)	-	107	16	147 116
10	FAR1 (13)	-	110	20	150 120
11	FLR1	-	111	22	151 122
12	FAR2 (4)	-(5)	112	24	152 124
13	FLR2 (6)	-	113	26	153 126
14	PB	-(0=>CRS)*	114	30	154 130
15	SB (14)	-(15)	115	32	155 132
16	LB (16)	-(17)	116	34	156 134
17	XB	-	117	36	157 136
20	DTAR3 (10)	-	120	40	160 140
21	DTAR2	-	121	42	161 142
22	DTAR1	-	122	44	162 144
23	DTAR0	-	123	46	163 146
24	KEYS	MODALS	124	50	164 150
25	OWNER	-	125	52	165 152
26	FCODE (11)	-	126	54	166 154
27	FADDR	-(12)	127	56	167 156
30	TIMER	-	130	60	170 160
31		-	131	62	171 162
32		-	132	64	172 164
33		-	133	66	173 166
34		-	134	70	174 170
35		-	135	72	175 172
36		-	136	74	176 174
37		-	137	76	177 176

\* Current PBL at halt in TR7L -- R7.

SEMAPHORES

+0 # WAITS - # NOTIFIES, e.g., <0 => notifies outstanding, >0 => processes waiting, =0 => wait list empty.

+1 Pointer to first waiting PCB on queue.

STACK FRAME, STACK ROOT

0	0=>PCL 1=>CALF	
1	SN of STK ROOT	
2	PB FOR	
3	RETURN	
4	CALLER'S SB	
5		
6	CALLER'S LB	
7		
10	CALLER'S KEYS	
11	PECL	
12	FCODE if CALF	<--- START OF AUTOMATIC
13	FADDR if CALF	STORAGE IF PCL (*)
14		

\*: First Argument Ptr pointed to by ECB+4.

STACK ROOT HEADER (WORD 0 OF SEGMENT)

0,1 - FREE POINTER (SN/WN)  
2,3 - FIRST EXTENSION (SN/WN)

STACK EXTENSION HEADER (WORD 0 OF SEGMENT)

0,1 - 0/0  
2,3 - NEXT EXTENSION (SN/WN)

WAIT LIST

SEMAPHORE+0 = COUNT OF WAITING PCBS  
SEMAPHORE+1 --> FIRST PCB

PCB+1(LINK) --> NEXT PCB ON WAIT LIST  
LAST PCB+1 --> 0

PCB+2,3 --> SEMAPHORE PROCESS IS WAITING ON

Note: wait list ordered by increasing ready list level, i.e., highest priority processes first in list.

3 COMMANDSADDISK -- ADD DISKS TO SYSTEM

ADdisk <dvno> ...

System user only.  
Internal command.

AMLC -- SET AMLC LINE CHARACTERISTICS

AMlc [ Tty ] <line> [<config>] [<lword>]  
[ TRan ]  
[TTYHs ]  
[TRANHS]  
[TTYNop]

If 2<USER<TRMUSR, <line>=USER-2.

<config>:  
2033 - 100 BAUD  
2213 - 300 BAUD  
2313 - 1200 BAUD  
2413 - 9600 BAUD

<lword>:

bit	Meaning when on
1 100000	Half duplex
2 040000	No LF after CR
3 020000	XOFF/XON Recognition
4 010000	XOFF Received
5-8 007400	Reserved
9-16 000377	User number

System user only.  
Internal command.

ASRCWD -- SET VIRTUAL ASR CONTROL WORD

ASRc wd [ 0 ] Terminal (Port 1)  
[ 2 ] Centronics Printer #2 (Port 3)  
[ 4 ] Centronics Printer #1 (Port 2)

Internal command.

ASSIGN -- ASSIGN PERIPHERAL DEVICE

ASsign AMLC [<protocol>] <line> [<config>] [<lword>]  
Cenpr [-WAIT]  
CE2pr [-WAIT]  
CARdr [-WAIT]  
Ptr [-WAIT]  
PUncH [-WAIT]  
PRn [-WAIT] (where n=0,1)  
CR1 [-WAIT]  
MTn [-WAIT] (where n=0,7)  
SMLCnn [-WAIT] (where nn=00,03)  
PLOT [-WAIT]  
Disk <dvno> [-WAIT]  
SMLC [-WAIT] <line>

<config> and <lword> described under AMLC on previous page.

<protocol>:  
Tty  
TTYHs  
TRan  
TRANHS  
TTYNop

Internal command.

ATTACH -- ATTACH TO UFD

Attach [<ufdname>] [<passwd>] [<dvno>] [<option>]  
[100000] [ 2 ]  
[177777] [ 1 ]  
[ 177777 ]

<dvno>:  
100000 => search all started devices,  
177777 => search MFD of current device

<option>:  
2 => set home UFD after attach to subUFD  
1 => dont set home UFD after attach to subUFD  
177777 => attach to UFD and dont set home

Internal command.

AVAIL -- TYPE DISK USAGE STATISTICS

```
AVAIL [<packname>]
      [<currdisk>]
      [ * ] (All Started Disks)
      [ ONE ] (Logical disk #1)
      ...
      [SEVENTEEN ]
```

External command.

BASIC

```
BASIC [<filename>]
```

See BASIC Interpretive Language User Guide, MAN1813.

External command.

BASICV -- VIRTUAL MEMORY BASIC

```
BASICV [<filename>]
```

See the BASIC/VM Guide.

External command.

BASINP -- READ PAPER TAPE

```
BASINP <filename>
```

External command.

BINARY -- OPEN FILE UNIT 3 FOR BINARY OUTPUT

```
Binary <filename>
```

Internal command.

CHAP -- CHANGE USER PRIORITY

```
Chap -<usrno> [<level>] [<timeslice>]
      ALL [ 1 ] [ 3 ]
```

<timeslice> is in tenths-of-a-second. Defaults taken only for ALL option, else unchanged.

System user only.  
Internal command.

CLOSE -- CLOSE FILE UNIT(S)

```
Close <funit>...
      <filename>
      ALL
```

Unit '21 (COMOUTPUT) must be closed explicitly.

Internal command.

CMPF -- COMPARE ASCII FILES

```
CMPF <treel> <tree2> [... <tree5>] [<option>...]
```

Options can be:

```
-MINL [<n>] (default = 3)
-BRIEF
-REPORT <report-file-name>
```

External command.

CMPRES -- COMPRESS SOURCE FILE

```
CMPRES <intreename> [<outtreename>]
      [ <intreename>]
```

External command.

CNAME -- CHANGE NAME OF FILE

```
CName <oldfilename> <newfilename>
```

Internal command.

CNVIMA -- CONVERT LOAD MAP FOR PMA

```
CNVIMA <in-file> <out-file>
```

Converts load map into format usable by PSD 'LS' command.

External command.

COBOL

COBOL <treename> [<option>...]

or

COBOL [<option>...] -I <treename> [...<option>]

Options can be:

- Binary  
Define binary file/device.
- B <treename>  
Create binary file with specified treename.
- B NO  
Do not create a binary file.
- B YES  
Create binary file in current UFD.
- EXPLIST  
Generate an expanded listing file.
- Input  
Define input file/device.
- I <treename>  
<treename> is source program.
- Listing  
Define listing file.
- L <treename>  
<treename> is listing file.
- L NO  
Do not create a listing file.
- L YES  
Create listing file in current UFD.
- L TTY  
Print listing at terminal.
- L SPOOL  
Spool listing file to line printer.
- NOEXPLIST  
Do not generate expanded listing file.
- 64R  
Generate relative-addressed code.
- 64V  
Generate segmented-addressed code.

External command.

COMINP -- START COMMAND INPUT FILE

```
Cominp <filename> [<ufdname>] [<funit>]
        [-]PAUSE          [ 6 ]
        [-]CONTIN
        [-]TTY
        -Start
        -End
```

'-S' = 'S' + 'CO CONTIN'. '-E' = 'TTY'.

Internal command.

COMOUTPUT -- CONTROL ROUTING OF TERMINAL OUTPUT

```
COMOutput [<filenamel>] <option>...
```

Options can be:

```
-Ntty      -Contin
-Tty       -Pause
-End
```

Internal command.

X.CONCAT -- CONCATENATE FILES

```
CONCAT [<outtreename>]
```

No name => unit 2 assumed open.

Follow with list of files to be concatenated together. '=' starts line to be used as header. Null line terminates list (unit 2 left open if open on entry).

External command.

COPY -- COPY DISK

COPY

Prompts:

FROM PHYSICAL DISK= (Enter DVNO—see Disk Addresses.)  
 1.5M WORD PACK? (Enter Yes or No.)  
 TO PHYSICAL DISK= (Enter DVNO)  
 1.5M WORD PACK? (Answer as to FROM...)  
 FROM,TO,RECORDS= <from-dvno> <to-dvno> <rec-in-dec>  
 PARAMETERS OK? (Yes or No. No => reenter all.)

External command.

CPMPC -- PUNCH FILE ON CARD PUNCH

CPMPC &lt;treename&gt; [&lt;option&gt;...]

Options can be:

-PRINT  
 -CRØ  
 -CR1

External command.

CREATE -- CREATE SUBUFD IN CURRENT UFD

CReate &lt;ufdname&gt;

Internal command.

CRMPC -- READ CARDS

CRMPC &lt;treename&gt; [&lt;option&gt;...]

Options can be:

-PRINT  
 -CRØ  
 -CR1

External command.

CRSER -- READ FROM SERIAL CARD READER

CRSER &lt;treename&gt;

External command.

CX -- SEQUENTIAL JOB MONITOR

CX [&lt;filename&gt;] [&lt;option&gt;...]

Options can be:

-A list entire audit file.  
 -Dxx drop job numbered xx.  
 -ON <dvno> submit CX job on <dvno> specified.  
 -P list personal jobs in queue and audit file.  
 -Q list queue.  
 -Sxx list status of job numbered xx.

External command.

DATE -- PRINT DATE AND TIME

DATE

External command.

DELAY -- SET TERMINAL DELAY CHARACTERISTICS

DELAY [<min>] [<max>] [<width>]  
 [ 6 ] [ 12 ] [ 72 ]

Can issue prior to login.

Internal command.

DELETE -- DELETE FILE

DELETE &lt;filename&gt;

Internal command.

DELSEG -- DELETE SEGMENT(S)

DELSeg <segno>  
 ALL

segno &gt; '2000 and not '6000

Internal command.

DISKS -- SPECIFY ASSIGNABLE DISKS

Disks [NOT] <dvno> ...

System user only.  
Internal command.

ED -- EDITOR

ED [<filename>] (no <filename> => new file)

(<str> - text string)  
(/ = unique delimiter not in string)

SUBCOMMANDS

.CR. = INPUT TTY

Append <str>

Append to current line.

Bottom

Go to bottom of file.

Brief

Don't display changes.

Change/<str1>/<str2>[/] [<n>] [G]

Change <str1> to <str2> for first occurrence on line, for all occurrences if G present, for <n> lines if <n> present.

Delete [<n>]

Delete <n> (1) lines.

Delete TO <str>

Delete to line containing <str>.

DUnload <fname> [<n>]

Unload/delete <n> (1) lines.

DUload <fname> TO <str>

Unload/delete up to (not incl) line containing <str> to <fname>.

Erase <char>

Make <char> the erase character (" ").

FILE [<fname>]

Write updated file to <fname>.

Find <str>

Find line starting with <str>.

Gmodify <subcmds>

Modify line w/subcommands:

A/<str>/ - Append

B<n> - Back <n> chars

C<c> - Copy up to (not inc) char <c>

D<c> - Delete up to char <c>

E<n> - Delete next <n> chars

F - Copy to end of line

I/<str>/ - Insert <str> at curr pos.

M<n> - Copy <n> chars

Nxx - Negate criteria of cmd xx

O/<str>/ - Overlay at current position

R/<str>/ - Retype at current position

S - Reset to start of line

Insert <str>

Insert line (.NULL. => input mode).

INPUT [ASR] [PTR] [TTY]

Input text from specified device.

Kill <char>

Make <char> new kill character.

LINESz <n>

Set max line size to <n> chars.

LOAD <fname>

Insert contents of <fname>.

Locate <str>

Locate line containing <str>.

MODE <arg>

Set editor mode. <arg> can be:

PRUPPER, PRALL, PRLower,

PROMPT, NPROMPT,

COUNT, NCOUNT,

NUMBER, NNUMBER,

COLUMN, NCOLUMN.

Modify /<str1>/<str2>[/] [G] [<n>]

Copy <str2> on top of <str1> starting with first char.

MOVE <buf1> <buf2>

Move contents of <buf2> to <buf1>.

MOVE <buf1> <str>

Move contents of <str> to <buf1>. Buffers are EDLIN (command line), INLIN (current line to be edited), STR.1, ..., STR.10.

Next [<n>]

Advance <n> (1) lines.

NFind <str>

Find line not starting with <str>.

OUTPUT [DISPLAY] [TTY]

Send verification output to specified device.

Overlay <str>

Overlay line with <str>. Blank leaves current char, WILD becomes blank.

PAuse

Back to PRIMOS, restart w/'S'.

POint <n>

Go to line <n>.

Print [<n>]

Print <n> (1) lines

PSymbol

Print symbols.

PUnch [<n>] [ASR] [PTP]

Punch n lines on indicated device.



Quit  
Exit without filing.

Retype <str>  
Replace line with <str>.

Symbol <name> <char>  
Define <name> symbol. <name>: BLANK (#),  
CPROMPT (\$), COUNTER (@), DPROMPT (&), ERASE  
("), ESCAPE (^), KILL (?), SEMICO (;), TAB (\),  
WILD (!).

Tabset <tabl>...  
Set tab positions.

Top  
Go to top of file.

Unload <fname> [<n>]  
Unload <n> line into <fname>.

Unload <fname> TO <str>  
Unload lines up to (but not incl) <str> to  
<fname>.

Verify  
Display all changed lines.

Where  
Print current line number.

Xeg <buff>  
Execute contents of buffer.

\*[<n>]  
Repeat <n> (until bottom or forever) times.

External command.

EDB -- BINARY EDITOR

EDB <intreename> [<outtreename>]  
PTR PTR

SUBCOMMANDS

BRIEF  
No names printed.

Copy <name>  
Copies up to (but not incl) <name>.

Copy ALL  
Copies to end of file.

Find <name>  
Position to <name>.

Find ALL  
Position to end of file.

Insert <treename>  
Insert <treename>.

Newinf <name>  
Open new input file.

OPEN <name>  
Open output file.

Replac  
Replace <fname> with <treename>.

RFL  
Reset Force Load flag.

SFL  
Set Force Load flag.

TERSE  
Print 1st name in blocks.

Top  
Top of input file.

VERIFY  
Print all names.

To replace <name>:

EDB <oldlib> <newlib>  
R <name> <treename>  
C ALL  
ET  
QUIT

External command.

ELIGTS -- SET ELIGIBILITY TIMESLICE

ELIGTS <tenths>  
           3

Internal command.

EXPAND -- EXPAND (COMPRESSED) SOURCE FILE

EXPAND <intreeame> <outtreeame>

External command.

FILMEM -- ZERO MEMORY

FILMEM [ALL]

No 'ALL' => '100 - '7777 excluding DOS zeroed.

External command.

FILVER -- COMPARE BINARY FILES

FILVER [<treenamel>] [<treename2>]

Prompts if no names entered.

External command.

FIXRAT -- FIX RECORD AVAILABILITY TABLE

FIXRAT [<option>...]

Prompts:

FIX DISK? (Enter Yes or No.)  
 PHYSICAL DISK DRIVE= (Enter DVNO-see Disk Addresses.)  
 If 'OPTIONS' specified:  
     TYPE DIRECTORIES TO LEVEL (Enter level.)  
     TYPE FILENAMES (Enter Yes or No.)  
     TYPE FILE CHAINS (Enter Yes for disk addr.)

External command.

FTN -- FORTRAN

FTN [-Input] <itree> [-B <btree>] [-L <ltree>]  
   [-B B<-<itree>] [-L L<-<itree>]  
           [<options>] [<a-reg>] [<b-reg>]  
   [ 1/1707] [ 2/0 ]

Option      Function

- 64v      Generate 64V mode object code
- 64R      Generate 64R mode object code
- 32r      Generate 32R mode object code
- Big      Dummy arrays may cross segment boundaries
- NOBig
- Dclvar   Flag undeclared variables
- NODclvar
- Debase   Conserve loader base areas
- DYnm     allocate local storage in stack frame
- ERRlist   Generate errors-only listing
- ERRtty   Print errors on terminal
- NOErrtty
- Explist   Generate expanded listing
- Fp       Generate floating-pt skip instr
- NOFp
- Intl      INTEGER\*4 default
- INTS      INTEGER\*2 default
- SAVE      Allocate local storage in linkage frame
- Spo       System programmer option
- Trace     Generate code for trace output
- Notrace
- XREFL     Generate cross reference listing
- Xrefs     Generate abbreviated cross ref listing
- NOXref

A-REG	ON-OPTION	OFF-OPTION	
1	100000	Spo	---
2	040000	Explist	ERlist
3	020000	ERlist	Explist
4	010000	Trace	Notrace
5	004000	64r	32R,64V,DYnm,Big
6	002000	Debase	---
7	001000	ERRtty	NOErrtty
8-10	000700	Input device (see below)	
11-13	000070	Explist,Erlist,Xrefs,XREFL (listing)	
14-16	000007	Binary device	

B-REG

1	100000	(Debug triad dump)	---
2	040000	Unused	---
3	020000	SAve,DYnm	---
4-7	017000	Unused	---
8	000400	64V,DYnm,Big	64r,32r,Debase
9	000200	Big	NOBig
10	000100	Intl	INTS
11	000040	Unused	---
12	000020	Xrefs	XREFL,NOXref
13	000010	Xrefs,XREFL	NOXref
14	000004	Unused	---
15	000002	NOFp	Fp
16	000001	Spo,DClvar	NODclvar

Device codes for Input, Listing, Binary:

0 - None	4 - Line Printer
1 - ASR	5 - Magtape
2 - PTR/PTP	6 - Cassette
3 - Card reader	7 - <u>Disk</u>

External command.

FUTIL -- FILE SYSTEM UTILITY

FUTIL

N.B.: command names must be in upper case.

```

Attach <treename>      ('*' => home ufd)
CLEAN <prefix> [<level>]
Copy <file> [<newname>] [,<file>[<newname>]] ...
COPYSam <file> [<newname>] [,<file>[<newname>]] ...
COPYDam <file> [<newname>] [,<file>[<newname>]] ...
CReate <ufdname> [<owner>] [<non-owner>]]
DELETE <file> [,<file>] ...
FOrce ON or OFF
From <treename>      ('*' => home ufd)
Listf [<level>] [First] [LISTFIL] [PROtect] [Size]
      [Type] [Date] [Rwlock] [PASSw]
LISTSav <filename> [<options as for Listf>]
Protect <file> [<owner>] [<non-owner>]
Quit
Scan <file> [<options as for Listf>]
SRwloc <file> <lockno>
To <treename>
TRECPy <ufd> [<newname>] [,<ufdname>[<newname>]]...
TREDEL <ufdname> [,<ufdname>] ...
TREPro <ufdname> [<owner>] [<non-owner>]]
TRESrw <ufdname> <lockno>
Ufdcpy
UFDDEL
UFDPro [<owner>] [<non-owner>]]
UFDsrw <lockno> <level>

<lockno>:
0   use system read/write lock (SYS)
1   n readers or 1 writer (W/NR)
2   n readers and 1 writer (LWNR)
3   n readers and n writer (NWNr)
    
```

External command.

HPSD -- HIGH PSD

HPSD

```

SA, EA = 147760, 156552.
Start of initial P counter = 150000.
For internal commands, see PSD.
    
```

External command.

INPUT -- OPEN FILE UNIT 1 FOR INPUT

Input &lt;filename&gt;

Internal command

LISTF -- LIST FILES IN CURRENT UFD

Listf

(Note: LISTING command with no name =&gt; LISTF.)

Internal command.

LISTING -- OPEN FILE UNIT 2 FOR LISTING OUTPUT

Listing &lt;filename&gt;

(Note: &lt;filename&gt; omitted =&gt; LISTF.)

Internal command.

LOAD

LOAD

ATtach [<ufd>] [<password>] [<ldisk>] [<key>]  
     <key>=0=>don't set home, 1=>set home.  
 AUTomatic [<n>]     Linkareas of length <n> around  
     module. <n>=0 turns feature off.  
 CHECK [<symbol>] [<par1 ... par9>]  
 COMmon <address>     Set COMMON TOP - 1  
 DC [END]  
 ENTire <treename>  
 ERror [<num>]; <num> = 0, 1, or 2  
 EXecute [<a>] [<b>] [<x>]     Uses START entry  
 FORceload <treename> [<addr>] [<linkstart>]  
     [<linkrange>]  
 F/     Force prefix for FO, LO, LI commands.  
 HARdware <definition>  
     177700 Must be zero  
     000040 1=>Prime 400 instruction set  
     000020 Unused  
     000010 1=>Double prec. fl. pt.  
     000004 1=>Single prec. fl. pt.  
     000002 1=>Prime 300 instruction set  
     000001 1=>High speed arithmetic  
 INitialize <treename> [<addr>] [<linkstart>]  
     [<linklen>]  
     Resets everything and loads <treename>.  
 LIBrary [<treename>] [<addr>]  
     [LIB>FTNLIB]  
 LOad <treename> [<bareal>]...[<barea8>]  
     <treename> [<bareal>]...[<barea9>]  
     <treename> <symbol> [<bareal>]...[<barea9>]

MAP [<treename>] [<option>]  
     [ \$F ] <option> = 0=>full map, 1=>load state,  
     2=>load state and link info, 3=>unresolved  
     references, 4=>same as 0, 5=>system  
     programmer map, 6=>sorted unresolved  
     references, 7=>sorted full map, 10=>symbol  
     map for PSD.  
 MOde [D32R] [D64R] [D16S] [D32S] [D64V] [D32I]  
 P/ Page boundary prefix for FO, LO, LI commands.  
 PAuse  
 PBrk [<symbol>] [<par1 ... par9>]  
     \*     <par1> [<par2 ... par9>]  
 QUIt     Back to PRIMOS  
 SAve <fname> [<a>] [<b>] [<x>] [<keys>]  
 SEtbase [<linkstart>] [<linklen>]  
     \*     [<end of sector>] (\*=>current sector)  
 SS <symbol>  
 SYmbol <symbol> <oldsym> [<par1 ... par6>]  
     <symbol> <addr> [<par2 ... par6>]  
     <symbol> \*     [<par1 ... par3>]  
     parameters can contain + and - signs  
 SZ [NO] or SZ YES  
 VIRTUALbase <linkstart> <tosector>  
 XPunge [<y>] [<z>]     <y>: 0=>all but undefined  
     symbols, 1=>all but undefined and COMMON.  
     <z>: 0=>all defined base areas, 1=>all but  
     sector 0, 2=>return all.

External command.

LOGIN -- LOGIN TO UFD

LOGIN &lt;ufdname&gt; &lt;passwd&gt; [&lt;dvno&gt;] [-ON &lt;nodename&gt;]

Internal command.

LOGOUT -- LOGOUT USER

LOGout [-<usrno>]  
     ALL     (System user only)

&lt;usrno&gt; must have same login name as user unless issued by System user.

Internal command.

LOGPRT -- PRINT LOGREC

```
LOGPRT [<outfile>] [<option>...]
      [ LOGLST ] [ -Help ]
      [ Tty ] [ -From <mmddy> ]
      [ -Type Cold
        Warm
        Timdat
        CHecks
        Disk
        DSKnam
        Overfl
        Shutdn
        CHK300
        Par300
        Mod300
        TYPE10-TYPE15 ]
      [ -Spool ]
      [ -Delete ]
      [ -PURGE ]
```

Prompts for input treename, default (just .CR.) is  
CMDNCO>LOGREC.

External command.

LOOK -- MAP SEGMENT TO USER 1

```
LOOK [-<usrno>] [<segno>] [<access>] [<mapseg>]
      [- 1 ] [ 6000 ] [ 200 ] [ 4001 ]
```

System user only.  
OPRPRI 1.  
Internal command.

X.LS -- LIST FILE CHARACTERISTICS

```
LS [<filename>] [<option>]...
```

Filename can be a wild card name containing  
% and + signs:

- % matches any number of characters (including none) in the filename;
- + matches any one character in the filename.

Options can be:

```
-DIM      -TYPE
-PR       -RWLK
```

External command.

MACHK -- TURNS ON MACHINE CHECK MODE

```
MACHK
```

External command.

MAGNET -- TRANSFER DATA TO AND FROM TAPE

## MAGNET

PROMPTS  
OPTION:RESPONSES  
POSITION or  
READ or  
WRITE or  
COPY

Depending on the option,  
MAGNET may prompt any  
of the following --

MTU # = #/7 or #/9; 0<#<7

ABSOLUTE OR RELATIVE? A or R

FILE # = if # if A mode, #>1;  
if R mode, # can be either  
positive or negative

RECORD # = if A mode, #>1;  
if R mode, #>0

MT FILE # = #>0

LOGICAL RECORD SIZE = < 10K bytes for PRIMOS II  
(DOS), IV, V or  
< 2K bytes for PRIMOS III

BLOCKING FACTOR = # of line images in one  
tape record

ASCII, BCD, BINARY  
or EBCDIC? ASCII or  
EBCDIC or  
BCD or  
BINARY

FULL OR PARTIAL RECORD  
TRANSLATION? FULL or  
PARTIAL

OUTPUT FILE NAME: <filename>

INPUT FILE NAME: <filename>

STARTING FILE # =

# FILES TO COPY =

External command.

MAGRST -- MAGTAPE RESTOREMAGRST [-7TRK]  
-9TRKPROMPTS  
TAPE UNIT:RESPONSES  
0 - 7

ENTER LOGICAL  
TAPE NUMBER: 0 -- tape already positioned  
1 -- first logical tape  
2 -- second logical tape  
etc.

READY TO RESTORE: Yes (yes)  
No (no)  
PA (partial)  
\$I [<filename>] [<level>]  
(turn on indexing)  
NW [<level>] (index only)

TREE NAME: <treename> (often partial) or  
list of treenames, 1 per  
line, end with null line

External command.

MAGSAV -- MAGTAPE SAVE

MAGSAV [&lt;option&gt;...]

Options can be:

- LONG  
1024 word records (default is 512).
- 7TRK  
use 7 track tape format (default is 9 track).
- INC  
incremental save (only save files that  
have been modified since last save).
- UPDT  
set dumped bit in the UFD entry (default  
is not to set the dumped bit).

<u>PROMPTS</u>	<u>RESPONSES</u>
TAPE UNIT:	0 -7
ENTER LOGICAL TAPE NUMBER:	0 -- tape already positioned 1 -- first logical tape 2 -- second logical tape etc.
TAPE NAME:	<6-character name>
DATE:	MM DD YY or .CR. for today's date (under PRIMOS III and IV)
REV NO:	<an arbitrary integer>
NAME:	<filename> \$A [<UFDname>] (attach) \$Q (terminate tape and return to PRIMOS) \$R (terminate tape, rewind, and return to PRIMOS) \$I [<filename>] [<level>] (print index to indicated level) MFD (save entire disk) * (save current directory)

External command.

X.MAIL

MAIL [&lt;ufdname&gt;]

If no <ufdname> is specified, the mail command  
checks mail for the user issuing the command.When sending mail to another user, end message with  
'\$'.

External command.

MAKE -- FORMAT DISKMAKE [OLD]  
[NEW]

<u>PROMPT</u>	<u>RESPONSES</u>
PHYSICAL DISK	physical disk number
1.5 WORD PACK?	yes or no
SPLIT DISK?	yes or no
PAGING RECORDS (DECIMAL)	number of records to be used for paging (see paging records tables, below)
<DISK NUMBER> <FILE RECORDS> <PAGING RECORDS> OK?	yes or no
BADSPOTS ON DISK?	yes or no
TRACK=	track of badspot or 0 to terminate
HEAD=	head of badspot or 9 to terminate
prints list of badspot HEAD and TRACK numbers: PARAMETERS OK?	yes or no
VIRGIN DISK?	yes or no
VERIFY DISK?	yes or no

PAGING RECORDS TABLE

Disk	Decimal Records
Diskette	460
1.5 million word disk	3248
3.0 million word pack	6496
30 million word disk	64960
128 K word fixed head disk (32 trk)	256
256 K word fixed head disk (64 trk)	524
512 K word fixed head disk (128 tk)	1024
1025 K word fixed head disk (256 tk)	4096

RECORDS PARAMETERS FOR 30-MILLION WORD DISK

Partition	Dev Addr 23 Disk Number	Dev Addr 21 Disk Number	Records
2 hd (deflt)	XX025X	XX005X	6496
2 hd (explicit)	XX065X	XX045X	6496
4 hd	XX125X	XX105X	12992
6 hd	XX165X	XX145X	19488
8 hd	XX225X	XX205X	25984
10 hd	XX265X	XX245X	32480
12 hd	XX325X	XX305X	38976
14 hd	XX365X	XX345X	45472
16 hd	XX425X	XX405X	51968
18 hd	XX465X	XX445X	58464
20 hd	XX525X	XX505X	64960

External command.

! MAXSCH -- SET SCHEDULING CONSTANT

MAXSch <n>  
    3

System user only.  
Internal command.

! MAXUSR -- LIMIT NUMBER LOGGED-IN USERS

MAXusr [<number>]  
    [ 64 ]

System user only.  
Internal command.

MDL -- MEMORY DUMP/LOAD

MDL

MDL command requests parameters. Respond with the following data separated by spaces or commas and terminate with a CR or LF:

<u>PARAMETER</u>	<u>DEFINITION</u>
SA	first location to be punched, must be $\geq$ '34.
EA	last location to be punched, must be $\leq$ '17777.
P	auto-start address or 0.
K	keys (default is 16S mode). bit 14: 0 punch end of tape (EOT). 1 omit EOT. bit 15: 0 punch begin of tape (BOT). 1 omit BOT. bit 16: 0 high speed punch. 1 ASR punch
L	loader address (default is sector in which MDL resides); if ASR, avoid following loader address: '10400 thru '11600 '110400 thru '111600

Internal command.

MESSAGE -- SEND MESSAGE TO USER(S) OR SYSTEM

Message -<usrno> [NOW]  
    [-1]  
    ALL  
    NET  
    <nodename>

End command with .CR., enter message on next line, end message with .CR.

System user for all but 'M' (user to operator).  
Internal command.



MRGF -- MERGE ASCII FILES

MRGF <treel> <tree2> [...<tree5>] outtree [<opts>]

Options can be:

- MINL [<n>] (default = 3)
- Brief
- FORCE
- REPORT <report-file-name>

External command.

NUMBER -- (RE)NUMBER BASIC FILE

NUMBER

External command.

OPEN -- OPEN FILE ON SPECIFIED UNIT

Open [<filename>] <unit> <key>

<key>: 1-Read, 2-Write, 3-R/W, 4-Close, 5-Delete, 6-Exist, 7-Rewind, 10-Truncate + 0000-New SAM, 2000-New DAM, 4000-New SAM segment, 6000-New DAM segment, 10000-New UFD. <filename> optional only for Rewind and Truncate.

Internal command.

OPRPRI -- SET OPERATOR PRIORITY

OPRpri [ 1 ]  
[ 0 ]

System user only.  
Internal command.

PASSWD -- SET PASSWORDS ON CURRENT UFD

PASSWD [<owner-password>] [<non-owner-password>]  
[ blanks ] [ blanks ]

Internal command.

PHANTOM -- START PHANTOM USER

PHantom <filename> [<funit>]  
[ 6 ]

Phantom file should end with 'CO TTY' command.

Internal command.

PM -- PRINT USER REGISTER VECTOR

Pm

Internal command.

PMA -- PRIME MACRO ASSEMBLER

PMA [-Input] <itree> [-B <btree>] [-L <ltree>]  
[-B B<-<itree>] [-L L<-<itree>]  
[<options>] [<a-reg>] [<b-reg>] [<x-reg>]  
[ 1/777 ] [ 2/0 ] [ 3/0 ]

External command.

Options:

Errlist Errors-only listing  
EXplist Expanded listing

A-REG	ON-OPTION	OFF-OPTION
1	100000	Unused
2	040000	Errlist
3	020000	EXplist
4-7	017000	Unused
8-10	000700	Input device (see below)
11-13	000070	Errlist,EXplist (normal listing)
14-17	000007	Binary device

Device codes (Input, Listing Binary):

0 - None	4 - Line Printer
1 - ASR	5 - Magtape
2 - PTR/PTP	6 - Cassette
3 - Card Reader	7 - Disk

B-REG (PRIMOS IV BUILD):

11-13	000020	64-user version
	000000	16-user version
16	000001	Large 16-user version

PMA ERROR CODES:

C: INST IMPROPERLY TERMINATED.  
 F: BAD MACRO EXPR TERMINATOR, ILLEGAL OP ON STACK PUSH/POP, FAIL PSEUDO-OP.  
 G: GOTO ERROR WITHIN MACRO, END/ENDM IN 'GOTO' SKIP AREA.  
 I: GENERIC, I/O, OR SHIFT HAS TAG, TAG ON 32I FIELD INSTR, SHORT INSTR SPEC (#) IMPOSSIBLE, 64V LDX CLASS BAD TAG, 64V TAG ON BRANCH ILLEGAL, SEG EXT REF BAD INDIRECT OR INDEX, AP/IP, INDEX SPECIFIER INVALID, TAG ON 32I BRANCH.  
 L: BAD LABEL, EXTERNAL VARIABLE IN LITERAL, BAD ARG IN EQU. SET, OR XSET,  
 M: MULTIPLY DEFINED LABEL.  
 N: 'END' WITHIN MACRO OR IF.  
 O: BAD OPCODE, 64V MEMORY REFERENCE WHEN NOT IN 64V MODE, S/R MODE MEMORY REFERENCE NOT IN S/R MODE.  
 P: MISMATCHED PARENTHESIS.  
 Q: AP, NOT IN 64V/32I MODE, IP, NOT IN 64V/32I MODE, ENDM PSEUDO-OP NOT IN MACRO.  
 R: STACK OVERFLOW, MULT DEF MACRO OR NAME EMPTY.  
 S: 'LOAD' MODE, INSTR NEEDS DSECT, INDIRECT DAC IN C64R MODE.  
 T: 32I MODE TAG MOD SYNTAX ERROR.  
 U: UNDEF VAR IN ADR FIELD/EXP, UNDEFINED VARIABLE IN ORG/SETB.  
 V: BIT FIELD OUT OF RANGE, UNRECOGNIZED OPERATOR IN EXPRESSION, FIELD ADR INST, OUT OF RANGE, I/O INSTR FIELD OUT OF RANGE, INSTR, SHIFT COUNT OUT OF RANGE, NO COMMA FOLLOWING FAR SPEC, 32I NO COMMA AFTER REGISTER #, 32I NO COMMA AFTER BIT #, 32I BAD DELIMITER, 32I SHIFT INSTR, BAD DELIM, BAD COUNT IN 32I SHIFT INSTR, BAD TAG MODIFIER IN 32I SHIFT, BAD DELIM AFTER REG # 32I PIO, OPEN PAREN MISSING ON DFTB ARG, CLOSE PAREN MISSING ON DFTB ARG, NO LAB IFTF, IFTT, IFVT, IFVF, NO NAME IFTF, IFTT, IFVT, IFVF, ABS/REL ILLEGAL IN SEG MODE, SEG/SEGR AFTER CODE GENED, PROC/LINK OUTSIDE OF SEG MODE, FIELD OUT OF RANGE ON DDM, BAD ARGUMENT FOLLOWING 'EXT', 'END' WITHIN MACRO, SYNTAX ERR IN 'DYNM' PSEUDO-OP, BAD ARG ON SUBR STATEMENT, VFD PSEUDO-OP, 16 BITS NOT DEFINED, UNTERMINATED CHARACTER STRING, EXPRESSION OVERFLOW ON FL PT NORMALIZE, EXPRESSION OVERFLOW ON FL PT RE-NORMALIZE, SCALED BINARY LOSS OF SIG, FL POINT NUMBER OUT OF RANGE, BCI REPEAT COUNT ERROR, BCI COUNT VARIABLE TYPE ERROR, MUNG IN ADDR FIELD OF CALL, BAD ADDR FIELD ON COMN, REPEAT COUNT ERROR, DEC/OCT PSEUDO OP HAS BAD OP, RLIT FOUND AFTER CODE GENED, NO LABEL ON DFTB.  
 X: 32I MODE GPR SPEC ERROR.  
 Y: PHASE ERROR.  
 Z: ILLEGAL ABS REF IN SEG MODE, SEG MODE ABS REF NOT 0-7, AP/IP, ABSOLUTE REF INVALID, TOO MANY EXT NAMES IN EXPR, BAD EXPR MODE FOR INSTR, EXPRESSION MODE ERROR, >1 NON-ABS/REL OPERATOR, RIGHT-HAND OP NOT ABS/REL, EXTERNAL NAME NOT PERMITTED.

PRERR -- PRINT ERRVEC AND LAST ERROR MESSAGE

PRerr

Internal command.

PRMPC -- PRINT FILE ON LINE PRINTER

PRMPC &lt;treename&gt;

External command.

PROTECT -- SET PROTECTION ON FILE

```
PROtec [<owner-rights>] [<non-owner-rights>]
      [ 0 ] [ 0 ]
```

0-No access, 1-Read, 2-Write, 3-R/W,  
 4-Delete/Truncate, 5-D/T/R, 6-D/T/W, 7-All.  
 Default on file creation equals 7 0.

Internal command.

PRSER -- PRINT FILE ON SERIAL LINE PRINTER

PRSER &lt;treename&gt;

External command.

PRVER -- PRINT FILE ON VERSATEC

PRVER &lt;treename&gt;

External command.

PSD -- PRIME SYMBOLIC DEBUGGER

PSD [&lt;token&gt;...]

(NOTE: VPSD has: segment, base register operations,  
does not have: symbols, trace.)

TERMINATORS for 'A'MODES

.CR. *+1	:A	ASCII
, *+1	:B	BINARY
^ *-1 (uparrow)	:H	HEXIDECIMAL
.n *+n	:O	OCTAL
.-n *-n	:S	SYMBOLIC
@ Effective address	:D	DECIMAL
\ Back to last @	:P	AP
( To contents of *	:L	LONG OCTAL INTEGER

) Back to last defined (  
 = EA + contents, no update of \*  
 / Return, do not close \*  
 ? return, do not close \*  
 ! Return, close \*

Expressions: Locations can be expressions including:

\* (current location)  
 [+]number-in-current-mode  
 >number-relative to relocation constant

#### SUBCOMMANDS

Access <loc>  
 Access location.  
 Breakpoint <loc>  
 Set breakpoint (up to 10).  
 BR  
 Print base registers.  
 Copy <from> <to> <new-addr>  
 Copy block of memory to new location.  
 Define <sym> <val>  
 Define symbol.  
 Dump <from> <to> [<ncol>] [<mode>]  
 Dump contents of memory.  
 Effective <from> <to> <match> [<mask>]  
 Search for effective address.  
 Execute <addr> [<a>] [<b>] [<x>]  
 Search for effective address.  
 EXecute  
 Execute segmented program.  
 FAddress <fld-addr-reg-no>  
 Access field address register.  
 FLength <fld-len-reg-no>  
 Access field address register.  
 Fill <from> <to> <val>  
 Fill memory block with <val>.  
 GO [<count>] [<a>] [<b>] [<x>] [<k>]  
 Continue at breakpoint.  
 Jumptrace [<start>] [<a>] [<b>]  
 Execute obj prog and produce diagnostic listing.  
 Keys <value>  
 Set keys to value.  
 List <loc>  
 list location.  
 LB <sn> <wn>  
 Set link base.  
 LS  
 Load symbols (unit 1).

MAP  
 Print load map symbols.  
 MO [D16S] [D32R] [D64R] [D64V] [D32S] [D32I]  
 Set address mode.  
 Monitor [<start>] [<a>] [<b>] <addr>  
 Trace obj prog for mem ref instr.  
 Not-equal <from> <to> <nmatch> [<mask>]  
 Negative search.  
 Open <fname> <unit> <key>  
 Open unit.  
 PATCH <loc1> <loc2>  
 Patch instr in <loc2> into <loc1>.  
 Print  
 Print brkpt, contents, a, b, x,  
 keys, relocation.  
 PROceed [<newbrk>] [<a>] [<b>] [<x>] [<k>]  
 Set new brkpt and resume execution.  
 Quit  
 Quit.  
 RElocate <reloc-val>  
 Set relocation constant.  
 Run [<loc>] [<a>] [<b>] [<x>] [<keys>]  
 Run program.  
 SB <sn> <wn>  
 Set stack base.  
 Search <from> <to> <match> [<mask>]  
 Search memory block.  
 SN <sn>  
 Set segment number.  
 SY 0  
 Symbol mode off.  
 SY 1  
 Symbol mode on.  
 Trace [<addr>] [<a>] [<b>] [<val>] [-1 <interval>]  
 Trace program.  
 Update <loc> <val>  
 Update location.  
 Verify <from> <to> <copy-addr>  
 Verify block of memory.  
 VErision  
 Print version, restart address.  
 Where  
 Display brkpts and proceed counts.  
 X <reloc-val>  
 Set relocation constant.  
 XB <sn> <wn>  
 Set X base.  
 XR <val>  
 Set X register.  
 YR <val>  
 Set Y register.  
 Zero [<brk-loc>]  
 Remove brkpt (current)

External command.

PTBOOT -- PAPER TAPE BOOT

PTBOOT

External command.

PTCPY -- PAPER TAPE COPY

PTCPY

External command.

PUSS -- COMPARE SOURCE FILES

PUSS

PROMPTS

DIFF FILE, OMISSIONS?

OLD-FILE TREE-NAME:

NEW-FILE TREE-NAME:

Obsolete -- use CMPF.

External command.

RESPONSESname of difference file  
followed by a space plus  
YES, NO, or carriage return

&lt;treename&gt;

&lt;treename&gt;

RESTORE -- RESTORE EXTERNAL PROGRAMRESTore <filename> [<sa>] [<ea>] [<p>] [<a>]  
[<b>] [<x>] [<k>]

Internal command.

RESUME -- RUN EXTERNAL PROGRAMRESume <filename> [<token>...] [<sa>] [<ea>] [<p>]  
[<a>] [<b>] [<x>] [<k>]

Internal command.

RPG -- REPORT PROGRAM GENERATOR

RPG &lt;filename&gt; [&lt;option&gt;...]

Options can be:

-SEQCHK, -NOSEQCHK  
-BANNER, -NOBANNER  
-OBDATA, -NOOBDATA  
-STATUS, -NOSTATUS  
-ERRTTY, -NOERRTTY  
-LISTING  
-BINARYError Message Format:

\*\*\*ERROR, LINE (xxxx) COL yy-zz [contents]-message.

\*\*WARNING, LINE (xxxx) COL yy-zz [contents]-message.

xxxx = Line number of statement in error  
yy-zz = Beginning and ending column number of  
the field in error. If yy is the same  
as zz, the zz portion is omitted  
[contents] = contents of columns yy-zz  
message = comments about the field in error

External command.

RUNOFF -- TEXT FORMATTER

RUNOFF [<filename>]

Notes:

- 1) When imbedded in text, all runoff command lines begin with a period; when issued at command level, runoff commands do not begin with a period.
- 2) In the table below, some runoff command actions are followed by brk, ejt, and/or deflt to indicate the command causes a break, ejects a page, and/or is the default. Also, if the runoff command has a default value, that value is specified.

(<str> = text string)

SUBCOMMANDS

.NULL.  
Start processing (from command mode).

\* <str>  
Comment line.

+ <str>  
Enter verbatim string.

/-/-/-/  
/Left/Center/Right/ strings.

> <str>  
Center string.

Adjust  
Enter adjust/fill modes (brk, deflt).

BLank <char>  
Define blank substitute character (.NULL.).

BMargin <n>  
Set bottom margin (brk, ejt, 5).

Break  
Break (start new line).

CMargin <n>  
Set column margin (brk, ejt, 5).

Column  
Set number of columns (brk, ejt, 1).

DD <str>  
Down Decimal level.

DDS <str>  
Down decimal level, no decimal number.

Define <sym> <str>  
Define symbol value.

DI <lev> <before> <after>  
Set decimal indents. 0 => all levels

DLevel <n>  
Go to decimal level <n> (1).

DLI <n>  
Set highest decimal level to appear in Table of Contents (all).

DN <str>  
Next heading on current decimal level.

DNS <str>  
Next heading on current decimal level, suppress number.

DR <n>  
Reset number on decimal level <n>.

DS <lev> <before> <after>  
Set decimal heading skip values.  
0 => all; -1 => eject before

DU [<n>]  
Go up <n> decimal levels (1).

EFooter /-/-/-/  
Define even-page footer.

EHeader /-/-/-/  
Define even-page header.

Eject  
Page eject (brk, ejt).

ERase <char>  
Define cmd mode erase char.

ERRgo  
Continue on error.

FILE <fn>  
Specify output file.

Fill  
Enter fill mode.

FLoat <fn>  
Floating insert of <fn>.

FOoter /-/-/-/  
Define footer for all pages.

FRom <n>  
First page number to output.

Header /-/-/-/  
Define header for all pages.

HYphen <char>  
Define phantom hyphen char (.RUBOUT.).

Indent <n>  
Indent left margin (5).

INDEX <str>  
Write <str> and page number to index.

INS <fn> [<parms>]  
Insert <fn>.

INS <unit>  
Insert from <unit>.

IXfile <fn>  
Define index file (16).

Kill <char>  
Define command line kill char (?).

Length  
Specify physical page length (brk, ejt, 66).

NAdjust  
Leave adjust mode (brk).

Need <n>  
Eject if <n> lines (1).

NERrgo  
Stop on error encountered (deflt).

NFill  
     Leave fill and adjust modes (brk).  
 NFILE  
     No output to file.  
 NIXfile  
     Stop output to index file.  
 NParagraph  
     No paragraph indentation (deflt).  
 NPAUse  
     No pause between pages (deflt).  
 NPERforate  
     No perforation marks (deflt).  
 NTty  
     No output to TTY (deflt).  
 OFooter /-/-/-/  
     Define odd-page footer.  
 OHeader /-/-/-/  
     Define odd-page header.  
 PAGen <n>  
     Set page number (1).  
 Paragraph [<n>] [<m>]  
     Start paragraph, skip <n>, indent <m>.  
 PAUse  
     Pause between output pages.  
 PERforate  
     Print perforation marks.  
 PICTURE <n>  
     Leave <n> lines together (1).  
 PURge  
     Force in outstanding floats.  
 Quit  
     Exit RUNOFF (brk, ejt).  
 RBar [ON]  
     Start revision bars.  
 RBar [OFF]  
     Stop revision bars.  
 RReturn <n>  
     Return to prev input file (0).  
 Rindent <n>  
     Indent right margin (5).  
 RUndent <n>  
     Undent right margin (0).  
 Skip <n>  
     Skip <n> lines (brk, 1).  
 SM <n>  
     Specify side margins (brk, ejt, 7).  
 SO <n>  
     Print <n>th source line # (1).  
 Space <n>  
     Specify single/double, etc. spacing (1).  
 STop  
     Conditional .QUIT/.RETURN.  
 SYchar <char>  
     Define symbol delimiter (%).

Tab <char> <nl> ...  
     Set tab character and stops.  
 TMargin <n>  
     Specify top margin (brk, ejt, 7).  
 TO <n>  
     Specify last page to print (32767).  
 TOFc <fn> <lim>  
     Specify table of contents file.  
 TOFc [<opt>]  
     Close, stop, start table of contents for  
     <opt>=omitted, 0, 1.  
 TIOFc <str>  
     Enter string in table of contents.  
 TTy  
     Output to TTY.  
 UNDEfine <sym>  
     Undefine symbol.  
 Undent <n>  
     Undent left margin.  
 WIDow <n>  
     Specify allowable widow size (0).  
 Width <n>  
     Specify paper width (brk, ejt, 85).

External command.

#### SAVE -- SAVE MEMORY IMAGE

SAve <filename> [<sa>] [<ea>] [<p>] [<a>] [<b>]  
 [<x>] [<k>]

Do not use SAve with 64V segmented files.

Internal command.

#### X.SAVER -- COMPARE RUNFILES

SAVER [<treenamel>] [<treename2>]

Prompts if no names entered.

External command.

SEG -- SEGMENTED LOADER

SEG [<filename>]

SUBCOMMANDS

DELETE [<filename>]  
deletes runfile.

HELP  
print list of SEG commands.

LOAD [<treename>]  
define runfile and invoke loader for creation.

LOAD \* [<treename>]  
define runfile and invoke loader for appending.

ATTach [<UFDname>] [<password>] [<ldisk>] [<key>]  
attach to UFD.

A/Symbol <sname> [<segtype>] <segno> <size>  
define a symbol in memory and reserve space  
for it using absolute segment numbers.

COMmon [ABS] <segno>  
relocate COMMON using absolute segment  
numbers.

COMmon REL <segno>  
relocate COMMON using relative segment  
assignment.

D/IL (D = Ditto = use parms of previous cmd.)

D/LCAD

D/Library

D/Forceload

D/PL or D/RL  
load using previous parameters. D/ and F/ may  
be combined.

EXecute  
save load to disk and execute program.

F/xx [<filename>] [<addr psegno lsegno>]  
forceload all routines in object file.

IL [<addr psegno lsegno>]  
load impure FORTRAN library.

INITialize [<treename>]  
initialize and restart loader.

LIBrary [<treename>] [<addr psegno lsegno>]  
load library file.

LO [<treename>] [<addr psegno lsegno>]  
load object file.

MAP [<filename>] <option>  
generate load map.

MIXup [ON] or MIXup OFF  
mixes procedure and static data.

MV  
moves portion of loaded file. Will prompt for  
info.

Operator  
relax/impose high-level restrictions

PL [<addr psegno lsegno>]  
load pure FORTRAN library.

P/xx [<filename>] [<option>] [<psegno  
lsegno>]  
load on a page boundary.

QUIT  
return to PRIMOS command level.

RETURN  
return to SEG command level.

RL <treename> [<addr psegno lsegno>]  
reload a routine.

R/Symbol <sname> [<segtype>] <segno> <size>  
define symbol in memory and reserve space for  
relative segment assignment.

SAve [a] [b] [x]  
save load to disk.

SE <segno> <len>  
create base area for desectorization.

SPLIT <segno><addr>  
<addr>  
<addr><ssegno><saddr> <esegno>  
break data into data and procedure portions

SS <sname>  
save symbol.

STACK <size>  
change stack size.

SYMBOL [<sname>] <segno> <addr>  
define a symbol at specific location in  
memory.

S/xx [<filename>] <addr> <psegno> <lsegno>  
load a specific absolute segment.

XP <dsymbol> <dbase>  
expunge symbols from symbol table and delete  
base information.

MAP <filename1> [<filename2>] <option>  
ascending addr, ll=sym

```

:  MODify [<filename>] or SA [<filename>]
    invoke modification subprocessor.
    NEw <filename>
        write new copy of runfile to disk.
    PAtch
        modify save range of existing segment.
    REturn
        return to SEG command level.
    SK <ssize> or SK <segno> <addr>
        alter stack size and/or location.
    STart <segno> <addr>
        change program execution start address.
    WRite
        write all segments to disk.
    PArms [<filename>]
        display parameters of runfile.
    PSd
        invoke VPSD debugging utility.
    Quit
        return to PRIMOS command level.
    REStore [<treename>]
        bring runfile into user memory.
    RESUme [<treename>]
        restore runfile and begin execution.
    SHare [<treename>]
        create R mode runfiles for segments below '4001.
    SIngle [<treename>] <segno>
        create R mode file image of single segment.
    TIme [<treename>]
        print time and date of last runfile
        modification.
    VERsION
        display SEG version number.

External command.

```

SETIME -- SET DATE AND TIME

```
SEtime -<mmddy> -<hhmm>
```

Must be issued before user logins possible.  
System user only.  
Internal command.

SFRWLK -- SET FILE READ/WRITE LOCK

```
SFRWLK
```

Prompts for filename, RWLOCK setting (0-3): 0 - use system lock, 1 - N readers or one writer, 2 - N readers and one writer, 3 - N readers and N writers.

External command.

SHARE -- SPECIFY SHARED SEGMENT

```
SHAre [<filename>] <segno> [<access>]
                                [ 600 ]
```

Omitted <filename> => change access only. <access>:  
000-no access, 200-read access, 600-read/execute  
access, 700-read, write, execute access.  
segno < '4000.

System user only.  
OPRPRI 1 only.  
Internal command.

SHUTDN -- SHUTDOWN DISK(S) OR SYSTEM

```
SHutdn [<node>] [<dvno> ... ]
        [ ALL ]
```

Do not shutdown logical device 0 --  
contains CMDNC0.

System user only.  
Internal command.

SIZE -- PRINT SIZE OF FILE

```
SIZE <treename>
```

External command.

SLIST -- PRINT FILE TO TERMINAL

```
SLIST [<treename>]
```

External command.

SORT

```
SORT [ option1 ] [ option2 ]
```

Options are: BRief, SPace, and MERge.

Prompts for: input filename, output filename, number of pairs of starting and ending columns, input pairs of starting and ending columns, reverse order, and data type. If merge option: number of files to be merged followed by input files, one per line.

External command.



SPOOL -- PRINT QUEUE MANAGER

```

SPOOL [ <treename> ] [<options>]
  [ %<treename> ] [ -Lnum ] Line Numbers
                  [ -Ftn ]  F'IN Forms Ctl
                  [ -Expand ] Expand
                  [ -Nofmt ] No Format Ctl
                  [ -Plot <nw> ] Plot
                  [ -Defer [<time>]] Defer to time
                  [ -Home ] Local Printer
                  [ -FOrM <name> ] Forms type
                  [ -Open ] Open only
                  [ -FUnit <unit> ] From unit
                  [ -Tunit <unit> ] To unit (2)

  [ -CMD ]
  [ -CANCEL <filename> ]
  [ -LIST [ ALL ] ]
          [ OWN ]
          [ DEFER ]
          [ PLOT ]
          [ PRINT ]
          [ FORM <type> ] (For default, say: ' ')

```

Prompts for defer time (-D), form type (-T) if not entered. '-CMD' ('SYSTEM' only) allows internal commands:

```

USER <usrno-of-spooler>
ABORT (Abort current file and restart later)
DROP (Aborts and deletes)
BACK (Backs up 100 lines and restarts)
RESTART (Restart current file)
FORM <type> (Specify new paper type)
HANG (Stop now)
GO (Restart after HANG, FINISH)
LENGTH <n> (Specify paper length)
QUIT (Exit SPOOL environment)
TIME <secs> (To wait for phantom)
CANCEL <filename>
FINISH (Stop when current file done)
LIST

```

External command.

START -- START EXECUTION

```
Start [<token>... ] [<p>] [<a>] [<b>] [<x>] [<k>]
```

Internal command.

STARTUP -- STARTUP DISK(S)

```
STARTUp [<nodename>] <dvno> ...
```

System user only.  
Internal command.

STATUS -- PRINT USER OR SYSTEM STATUS

```

STATUs [ ALL ]
        [ USers ]
        [ DISks ]
        [ UNits ]
        [ NET ]

```

Internal command.

SVCSW -- SET USER SVC SWITCH (INTERNAL

```

SVcsw [ 1 ]
       [ 0 ]

```

1 => bounce (except class 5), 0 => don't bounce.

Internal command.

TA -- TREE ATTACH

```
TA <treename>
```

WARNING: Wipes out memory.

External command.

TAPXAM -- READ/WRITE MAGTAPE

## TAPXAM

Allows examination of 7 or 9-track tapes at a single tape command level. Can be used to diagnose failing drive or controller. Prompts for drive number, 7 or 9 track indication, maximum record size to read or write. Defaults (just hit .CR.) are drive 0, 9 track, '1000 words. Displays command, status, and NW transferred after each operation. Internal commands:

BF or BT        Backspace one filemark (tapemark).  
 BS or BR        Backspace one record.  
 DS              Display Status.    Interprets last status read in readable form.  
 Eol             Write MAGSAV-style End-Logical-Tape record. Must first read last record on tape (to get sequence number right).  
 FF or FT        Forward space to file mark.  
 FS or FR        Forward space one record.  
 In              Re-initialize (all prompts repeated).  
 Max [<n>]       Set max amt of data to display after reads -- 0-10 words, defaults to 0.  
 Psd             Enter PSD (to examine block just read). Prints addr of buffer, use 'Q' in PSD to return to TAPXAM.  
 Quit            Exit TAPXAM (tape is not rewound).  
 R[C][l] [<nw>] Read [Binary] [l char/word] or [Correct] [l char/word].  
 RW              Rewind to load point.  
 St              Read current status.  
 W[C][l] [<nw>] Write [Binary] [l char/word] or [Correct] [l char/word].  
 WF or WT        Write file mark (tape mark).  
 1600BPI        Set density to 1600 bpi. (only applicable for software settable density)  
 6250BPI        Set density to 6250 bpi. (only applicable for software settable density)

External command.

TERM -- SET TERMINAL CHARACTERISTICS

```
TERM [ DISPLA ]
      [ ERASE <char> ]
      [ KILL <char> ]
      [ BREAK ON ]
      [ OFF ]
      [ HALF [NOLF] [XOFF] ]
      [ FULL [XOFF] ]
```

External command.

TIME -- PRINT TIME STATISTICS

Time

HH'MM logged in, MM'SS CPU time, MM'SS I/O time.

Internal command.

TRAMLC -- AMLC I/O

```
TRAMLC TRANSMIT <filename> <line> [T]
TRAMLC RECEIVE <filename> <line> [T]
```

External command.

UNASSIGN -- RELEASE PERIPHERAL DEVICE

Unassign <parameters-identical-to-ASSIGN-command>

Internal command.

UPCASE -- TRANSLATE FILE TO UPPER CASE

```
UPCASE <intreename> [<outtreename>]
                        [<file-open-on-unit 2>]
```

External command.

USERS -- PRINT CURRENT NUMBER OF USERS

USERS

Internal command.

USRASR -- CONNECT SYSTEM ASR TO USER

USRasr <usrno>

Must type full USRASR if not logged in.

System user only.  
Internal command.

VPSD -- VIRTUAL MODE PSD

VPSD

Supports V-mode. For internal commands, see PSD.

External command.

VRTSSW -- SET VIRTUAL SENSE SWITCHES

Vrtssw [<sense-switch-setting>]  
[ 0 ]

Internal command.

4 FILE SYSTEM INTERNALS

The following describes the internal formats of all disk records for both the old and new file system partitions. All numbers are decimal unless preceded by a ':'. Where possible, field names are the same as those used by the internal file system routines.

DSKRAT FORMATSDSKRAT Format -- Old Partitions

0	5	NUMBER OF WORDS IN DSKRAT HEADER = 5
1	RECSIZ	DISK RECORD SIZE (448 or 1040)
2	NMRECS	NUMBER RECORDS IN PARTITION
3	UNUSED	UNUSED
4	NHEADS	NUMBER HEADS IN PARTITION
5	DATA	START OF DSKRAT DATA (ONE BIT/RECORD)
	....	

DSKRAT Format -- New Partitions

0	8	NUMBER WORDS IN HEADER = 8
1	RECSIZ	RECORD SIZE
2	NMRECS	NUMBER RECORDS IN PARTITION (TWO WORDS)
4	NHEADS	NUMBER HEADS IN PARTITION
5	RESERVED	RESERVED
6	RESERVED	RESERVED
7	RESERVED	RESERVED
8	DATA	START OF DSKRAT DATA (ONE BIT/RECORD)
	....	

RECORD HEADER FORMATS

NOTE: record header formats are the same for new and old partitions. The format of a record header is a function of the physical record size.

Record Header Format -- 448-Word Records

0	REKCRA	RECORD ADDRESS (OF THIS RECORD)
1	REKBRA	RA OF DIRECTORY ENTRY OR FIRST RECORD
2	REKFPT	RA OF NEXT SEQUENTIAL RECORD
3	REKBPT	RA OF PREVIOUS RECORD
4	REKCNT	NUMBER DATA WORDS IN THIS RECORD
5	REKTYP	TYPE OF THIS FILE
6	REKLVL	INDEX LEVEL FOR NEW PART DAM FILES
7	RESERVED	RESERVED

Record Header Format -- 1040-Word Records

0	REKCRA	RECORD ADDR OF THIS RECORD (TWO WORDS)
2	REKBRA	BEGINNING RECORD ADDRESS (TWO WORDS) (BRA OF DIRECTORY IF FIRST RECORD)
4	REKCNT	NUMBER DATA WORDS IN THIS RECORD
5	REKTYP	TYPE OF THIS FILE
6	REKFPT	RA NEXT SEQUENTIAL RECORD (TWO WORDS) (0 IF LAST)
8	REKBPT	RA OF PREVIOUS RECORD (TWO WORDS) (0 IF FIRST)
10	REKLVL	INDEX LEVEL FOR NEW PART DAM FILES
11		
	RESERVED	RESERVED (FIVE WORDS)
15		

Notes

- 1) All disks except Storage Module have 448-word records. Storage Modules have 1040-word records.
- 2) The BRA of the first record in a file points to the beginning record address of the directory in which the file entry appears. In all other records, the BRA points to the first record of the file.
- 3) REKFPT contains the address of the next sequential record in the file or 0 if it is the last record in the file.
- 4) REKBPT contains the address of the previous record in sequence or 0 if it is the first record in the file.
- 5) REKTYP is valid only in the first record of a file. Legal values are:
 

0	SAM File
1	DAM File
2	SAM Segment Directory
3	DAM Segment Directory
4	User File Directory (UFD)
- 6) If the file is the record zero bootstrap (BOOT) or the disk record availability table (DSKRAT or volume name) and the disk has a 1040 record size (Storage Module), bit 1 (:100000) of FILTYP will be set.
- 7) DAM files on new partitions are organized somewhat differently from the above -- see PE-T-276.

UFD HEADER AND ENTRY FORMATSOld UFD Header Format

0	8	SIZE OF HEADER -- 8 WORDS
1	OPASSW	OWNER PASSWORD (THREE WORDS)
4	NPASSW	NON-OWNER PASSWORD (THREE WORDS)
7	RESERVED	RESERVED

New UFD Header Format

0	ECW	ECW (SEE NOTE 1 ON NEXT PAGE)
1	OPASSW	OWNER PASSWORD (THREE WORDS)
4	NPASSW	NON-OWNER PASSWORD (THREE WORDS)
7	RESERVED	RESERVED (SIXTEEN WORDS)
23		

Old UFD Entry Format

0	BRA	BEGINNING RECORD ADDRESS
1	FILE	FILENAME (THREE WORDS)
	NAME	
4	SPACES	2 BLANKS FOR NAME EXPANSION (RESERVED)
5	PROTEC	PROTECTION (OWNER/NON-OWNER)

Notes

In an old UFD, the high-order eight bits of PROTEC are the owner rights stored in complemented form ( $\emptyset$ =>owner has right). The low-order eight bits are non-owner protection, stored in true form ( $\emptyset$ =>no right). On creation, PROTEC= $\emptyset$ . After a 'PROT 7  $\emptyset$ ', PROTEC=:174000.

New UFD Entry Format

0	ECW	ENTRY CONTROL WORD (TYPE/LENGTH)
1	BRA	BEGINNING RECORD ADDRESS (TWO WORDS)
3	RESERVED	RESERVED (THREE WORDS)
6	PROTEC	PROTECTION (OWNER/NON-OWNER)
7	RESERVED	RESERVED FOR FUTURE USE
8	DATMOD	DATE LAST MODIFIED (YYYYYYMMMMDDDD)
9	TIMMOD	TIME LAST MODIFIED (SECS-SINCE-MID./4)
10	FILTYF	FILETYPE
11	SCW	SUBENTRY CONTROL WORD FOR FILENAME
12	F	
	I	
	L	
	E	
	...	FILENAME (1-16 WORDS, BLANK PADDED)
	N	
	A	
	M	
N	E	

Notes

- 1) The Entry Control Word (ECW) consists of two eight-bit subfields. The top eight bits indicate the type of the following entry as follows:

0	Old UFD Header
1	New UFD Header
2	Vacant Entry
3	New UFD File Entry

- The low-order eight bits give the size of the entry including the ECW itself.
- 2) The bits in PROTEC are stored in true form ( $\emptyset$ => no right) for both owner and non-owner fields.
- 3) The file type field is as before (see Old Record Header Format) with following additional bits:

BIT	MEANING WHEN BIT IS ON
1	File has 16-word hdr (DSKRAT, BOOT only).
4	Special file (BOOT, DSKRAT, MFD, BADSPT).

- 4) The Subentry Control Word (SCW) consists of two eight-bit subfields. The top 8 bits are  $\emptyset$ , indicating subentry type  $\emptyset$ . The low-order 8 bits give the size of the subentry including the SCW itself.
- 5) N.B.: UFD entries are reused by the new file system. This means that a new entry will not necessarily appear at the end of the UFD.

SEGMENT DIRECTORY FORMATSOld Segment Directory Format

0	BRA0	BRA OF FIRST ENTRY IN DIRECTORY
1	BRA1	BRA OF SECOND FILE
2	0000	NULL ENTRY
	...	
N	BRAn	BRA OF LAST FILE IN DIRECTORY

New Segment Directory Format

0	BRA0	BRA OF FIRST FILE IN DIR (2 WORDS)
2	BRA1	BRA OF SECOND FILE IN DIR (2 WORDS)
	0000	NULL ENTRY (2 WORDS)
	0000	
	...	
2N	BRAn	BRA OF LAST FILE IN DIR (2 WORDS)

Notes

The only difference between old and new directories is that each entry in a new directory is two words. A null entry in a new directory is a 32-bit 0.

5 INSTRUCTION SET

The following description applies only to P400 memory reference. The first number in the "opcode" column is the octal representation of instruction bits 3-6. The second number is the octal representation of bits 13-14 (bits 13-14 are inspected only if bits 6-11 are 11000, i.e., S=1 and  $-256 \leq D < -224$ ).

The 'type' column indicates the format and/or function of the operation as follows.

AP: Three-word operation, the last two words of which are an AP address pointer.  
 BR: Two-word operation, the second word of which is a word number within the current procedure segment to which to branch.  
 CON: Single-word control operation.  
 DA: Decimal arithmetic operation.  
 FE: Field and edit operation.  
 FLD: Single-word field operation.  
 FOP: Single-word floating-point operation.  
 FSK: Single-word floating-point skip operation.  
 IG: Single-word integrity operation.  
 IO: Single-word input/output operation.  
 LOG: Single-word logicize operation.  
 MOD: Single-word mode operation.  
 MR: Memory-reference operation.  
 OPR: Single-word miscellaneous operation.  
 PIO: Programmed input/output operation.  
 SH: Single-word shift operation.  
 SKP: Single-word skip operation.  
 VM: Virtual memory operation.

The 'C' column indicates the effect of the operation on the C-bit and the L-bit as follows.

-: C and L are unchanged by the operation.  
 1: C is unchanged, L is carry.  
 2: C is overflow, L is carry.  
 3: C is overflow, L is indeterminant.  
 4: C is shift extension, L is indeterminant.  
 5: C is a result of op, L is indeterminant.  
 6: C and L are indeterminant.  
 7: C and L are loaded by the operation.  
 8: C is cleared, L is indeterminant.

The 'cc' column indicates the effect of the operation on the condition codes as follows.

-: Cond. codes are unchanged.  
 1,4: Cond. codes result of arith op or compare.  
 5: Cond. codes indeterminant.  
 6: Cond. codes loaded by operation.  
 7: Cond. codes indicate result of operation.

The 'avail' column indicates in which addressing modes the operation is available as follows.

S: Available in 16S and 32S modes.  
 R: Available in 32R and 64R modes.  
 V: Available in 64V mode.  
 I: Available in 32I mode.  
 \*: Restricted to Ring 0 execution.

PRIME 400 MEMORY-REFERENCE INSTRUCTIONS  
 (WHEN IN 64V MODE).

INSTRUCTION BITS 13-14 (if S=1 and $-256 \leq D < -224$ )					
INSTRUCTION BITS 3-6	00	01	10	11	
0001	JMP	EAL	XEC	-	
0010	LDA	FLD	DFLD	LDL	
0011	ANA	STLR	ORA	ANL	
0100	STA	FST	DFST	STL	
0101	ERA	LDLR	-	ERL	
0110	ADD	FAD	DFAD	ADL	
0111	SUB	FSB	DFSB	SBL	
1000	JST	-	PCL	-	
1001	CAS	FCS	DFCS	CLS	
1010	IRS	MIA	EAXB	-	
1011	IMA	MIB	EALB	-	
1100	JSY	EIO	JSXB	-	
1101*	STX	FLX	DFLX	-	
1101**	LDX	LDY	STY	JSX	
1110	MPY	FMP	DFMP	MPL	
1111	DIV	FDV	DFDV	DVL	

Use column 00 if S (bit 7) is 0 or if D (bits 8-16) is not in the range  $-256 \leq D < -224$ .

\*: Use this row if bit 2 of instr. word is a 0. These instructions cannot be indexed.

\*\* : Use this row if bit 2 of the instruction word is a 1. These instructions cannot be indexed.

MNEM	OPCODE	TYP	C	AVAIL	DESCRIPTION
A			I		ADD WORD.
A1A	141206	OPR	2 1	SRV	ADD 1 TO A REG. A+1=>A.
A2A	140304	OPR	2 1	SRV	ADD 2 TO A REGISTER. A+2=>A.
ABQ	50134	OPR	- 7	I	ADD TO BOTTOM OF QUEUE.
ABQ	141716	AP	- 6	SRV	ADD TO BOT OF Q. CCEQ => FULL.
ACA	141216	OPR	2 1	SRV	ADD CBIT TO A REG. CBIT+A=>A.
ADD	06	MR	2 1	SRV	ADD. (A) + [EA]16 => A.
ADL	06 03	MR	2 1	V	(A,B)+[EA]32=>A,B. (NO HOLE).
ADLL	141000	OPR	2 1	SRV	ADD LINK TO L REGISTER.
ADLR	50014	OPR	- 7	I	ADD LINK TO GR.
AH	12	MR	2 1	I	ADD HALFWD. RH+[EA]16=>RH.
ALFA	001301	FLD	6 5	SRV	ADD L TO FIELD ADDR REG. ZERO.
ALFA	001311	FLD	6 5	SRV	ADD L TO FIELD ADDR REG. ONE.
ALL	0414XX	SH	4 5	SRV	A LEFT LOGICAL.
ALR	0416XX	SH	4 5	SRV	A LEFT ROTATE.
ALS	0415XX	SH	4 5	SRV	A LEFT SHIFT (SHORT INT ARITH).
ANA	03	MR	- -	SRV	AND. (A) .AND. [EA]16 => A.
ANL	03 03	MR	- -	V	(A,B) .AND. [EA]32 => A,B.
ARFA	50161	FLD	- 7	I	ADD GR TO FIELD ADDR REG.
ARGT	000605	CON	- -	SRV	ARG TRANSFER (USED WITH PCL).
ARL	0404XX	SH	4 5	SRV	A RIGHT LOGICAL.
ARR	0406XX	SH	4 5	SRV	A RIGHT ROTATE.
ARS	0405XX	SH	4 5	SRV	A RIGHT SHIFT (SHORT ARITH).
ATQ	50135	OPR	- 7	I	ADD TO TOP OF QUEUE.
ATQ	141717	AP	- 6	SRV	ADD TO TOP OF Q. CCEQ => FULL.
BCEQ	141602	BR	- -	SRV	BRANCH ON CONDITION CODE .EQ. 0.
BCGE	141605	BR	- -	SRV	BRANCH ON CONDITION CODE .GE. 0.
BCGT	141601	BR	- -	SRV	BRANCH ON CONDITION CODE .GT. 0.
BCLE	141600	BR	- -	SRV	BRANCH ON CONDITION CODE .LE. 0.
BCLT	141704	BR	- -	SRV	BRANCH ON CONDITION CODE .LT. 0.
BCNE	141603	BR	- -	SRV	BRANCH ON CONDITION CODE .NE. 0.
BCR	141705	BR	- -	SRV	BRANCH ON CBIT RESET.
BCS	141604	BR	- -	SRV	BRANCH ON CBIT SET.
BDX	140734	BR	- -	SRV	BRANCH ON DECREMENTED X.
BDY	140724	BR	- -	SRV	BRANCH ON DECREMENTED Y.
BEQ	140612	BR	- 4	SRV	BRANCH ON A REGISTER .EQ. 0.
BFEQ	50122	BR	- 4	I	BRANCH ON FLTG REG EQ.
BFEQ	141612	BR	- 4	SRV	BRANCH ON FAC .EQ. 0.
BFGE	50125	BR	- 4	I	BRANCH ON FLTG REG NE.
BFGE	141615	BR	- 4	SRV	BRANCH ON FAC .GE. 0.
BFGT	50121	BR	- 4	I	BRANCH ON FLTG REG LE.
BFGT	141611	BR	- 4	SRV	BRANCH ON FAC .GT. 0.
BFLE	50120	BR	- 4	I	BRANCH ON FLTG REG LT.
BFLE	141610	BR	- 4	SRV	BRANCH ON FAC .LE. 0.
BFLT	50124	BR	- 4	I	BRANCH ON FLTG REG GT.
BFLT	141614	BR	- 4	SRV	BRANCH ON FAC .LT. 0.
BFNE	50123	BR	- 4	I	BRANCH ON FLTG REG GE.
BFNE	141613	BR	- 4	SRV	BRANCH ON FAC .NE. 0.
BGE	140615	BR	- 4	SRV	BRANCH ON A REGISTER .GE. 0.
BGT	140611	BR	- 4	SRV	BRANCH ON A REGISTER .GT. 0.
BHD1	50144	BR	- -	I	BRANCH ON HALF REG DEC BY 1.
BHD2	50145	BR	- -	I	BRANCH ON HALF REG DEC BY 2.

BHD4	50146	BR	- -	I	BRANCH ON HALF REG DEC BY 4.
BHEQ	50112	BR	- 4	I	BRANCH ON HALF REG EQ.
BHGT	50111	BR	- 4	I	BRANCH ON HALF REG LE.
BHI1	50140	BR	- -	I	BRANCH ON HALF REG INCR BY 1.
BHI2	50141	BR	- -	I	BRANCH ON HALF REG INCR BY 2.
BHI4	50142	BR	- -	I	BRANCH ON HALF REG INCR BY 4.
BHLE	50110	BR	- 4	I	BRANCH ON HALF REG LT.
BHLT	50104	BR	- 4	I	BRANCH ON HALF REG GT.
BHNE	50113	BR	- 4	I	BRANCH ON HALF REG GE.
BHNE	50105	BR	- 4	I	BRANCH ON HALF REG NE.
BIX	141334	BR	- -	SRV	BRANCH ON INCREMENTED X.
BIY	141324	BR	- -	SRV	BRANCH ON INCREMENTED Y.
BLE	140610	BR	- 4	SRV	BRANCH ON A REGISTER .LE. 0.
BLEQ	140702	BR	- 4	SRV	BRANCH ON L REGISTER .EQ. 0.
BLGE	140615	BR	- 4	SRV	BRANCH ON L REGISTER .GE. 0.
BLGT	140701	BR	- 4	SRV	BRANCH ON L REGISTER .GT. 0.
BLLE	140700	BR	- 4	SRV	BRANCH ON L REGISTER .LE. 0.
BLLT	140614	BR	- 4	SRV	BRANCH ON L REGISTER .LT. 0.
BLNE	140703	BR	- 4	SRV	BRANCH ON L REGISTER .NE. 0.
BLR	141707	BR	- -	SRV	BRANCH ON LINK RESET.
BLS	141706	BR	- -	SRV	BRANCH ON LINK SET.
BLT	140614	BR	- 4	SRV	BRANCH ON A REGISTER .LT. 0.
BMEQ	141602	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .EQ.
BMGE	141706	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .GE.
BMGT	141710	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .GT.
BMLE	141711	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .LE.
BMLT	141707	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .LT.
BMNE	141603	BR	- -	SRV	BRANCH ON MAG.-COND. L,CC .NE.
BNE	140613	BR	- 4	SRV	BRANCH ON A REGISTER .NE. 0.
BRBR	50040	BR	- -	I	BRANCH ON REG BIT RESET.
BRBS	50000	BR	- -	I	BRANCH ON REG BIT SET.
BGR1	50134	BR	- -	I	BRANCH ON REG DEC BY 1.
BGR2	50135	BR	- -	I	BRANCH ON REG DEC BY 2.
BGR4	50136	BR	- -	I	BRANCH ON REG DEC BY 4.
BREQ	50102	BR	- 4	I	BRANCH ON REG EQ.
BRGE	50105	BR	- 4	I	BRANCH ON REG NE.
BRGT	50101	BR	- 4	I	BRANCH ON REG LE.
BRI1	50130	BR	- -	I	BRANCH ON REG INCR BY 1.
BRI2	50131	BR	- -	I	BRANCH ON REG INCR BY 2.
BRI4	50132	BR	- -	I	BRANCH ON REG INCR BY 4.
BRLE	50100	BR	- 4	I	BRANCH ON REGISTER LT.
BRLT	50104	BR	- 4	I	BRANCH ON REGISTER GT.
BRNE	50103	BR	- 4	I	BRANCH ON REGISTER GE.
C	61	MR	1 1	I	COMPARE R WITH [EA]32].
CAI	000411	IO	- -	SRVI	*CLEAR ACTIVE INTERRUPT.
CAL	141050	OPR	- -	SRV	CLEAR A REG. LEFT BYTE.
CALF	000705	AP	7 6	SRV	PROC CALL FROM FAULTING PROC.
CAR	141044	OPR	- -	SRV	CLEAR A REG. RIGHT BYTE.
CAS	11	MR	1 1	SRV	SKIP 0,1,2 IF (A) >,< [EA]16.
CAZ	140214	OPR	1 1	SRV	SKIP 0,1,2 INST. IF A >,< 0.
CEA	000111	OPR	- -	SRV	A AS EA=>A. (USELESS IN 64V).
CGT	50026	OPR	- 7	I	COMPUTED GOTO.
CGT	001314	-	6 5	SRV	COMPUTED GO TO.
CH	71	MR	1 1	I	COMPARE RH WITH [EA]16].
CHS	50040	OPR	- -	I	CHANGE SIGN -(1)=>GR(1).
CHS	140024	OPR	- -	SRV	CHANGE SIGN OF A REGISTER.
CLS	11 03	MR	1 1	V	SKIP 0,1,2 IF (A,B) >,< [EA]32].



CMA 140401 OPR -- SRV ONE'S COMPLEMENT A REGISTER.  
 CMH 50045 OPR -- I COMP HALF REG. GRH=>GRH.  
 CMR 50044 OPR -- I COMP REG. GR=>GR.  
 CR 50056 OPR -- I CLEAR REG. 0 => GR.  
 CRA 140040 OPR -- SRV CLEAR A REGISTER. 0=>A.  
 CRB 140015 OPR -- SRV CLEAR B REGISTER. 0=>B.  
 CRBL 50062 OPR -- I LEFT BYTE 0=>GRH(1-8).  
 CRBR 50063 OPR -- I RIGHT BYTE 0=>GRH(9-16).  
 CRE 141404 OPR -- SRV CLEAR E. 0=>E.  
 CREP 10 02 MR -- R (P) => [(S)+1]16, EA=>P.  
 CRL 140010 OPR -- SRV CLEAR L REGISTER. 0=>L.  
 CRLE 141410 OPR -- SRV CLEAR L AND E. 0=>L, 0=>E.  
 CSA 140320 OPR 5 -- SRV CPY SIGN OF A. A1=>CBIT,0=>A1.  
 CSR 50041 OPR -- I COPY & SAVE SIGN. 1=>C,0=>GR1.  
 CXCS 001714 IG -- V CONTROL EXTENDED CONTROL STORE.  
 D 62 MR 3 1 I DIV. (R,R+1)/[EA32=>R RMR=>R+1.  
 DAD 06 (DP) MR 2 1 SR (A,B)+[EA]32 => A,B. (W/HOLE).  
 DBL 000007 MOD -- SRV ENTER DOUBLE-PREC MODE.  
 DBLE 50106 FOP -- I CONV SINGLE TO DOUBLE FLTG PT.  
 DECH 70 MR - 1 I DECR HALFW. [EA16]-1=>[EA16].  
 DFA 15 17 MR 3 1 I DBLE FLTG ADD. DFR+[EA64]=>DFR.  
 DFAD 06 02 MR 3 5 RV (DFAC) + [EA]64 => DFAC.  
 DFC 05 07 MR - 1 I DBLE FLTG COMP DRF TO [EA64].  
 DFCM 50144 FOP 3 1 I DBL PRC FLTG COMP. -DFGR=>DFGR.  
 DFCM 140574 FOP 3 5 SRV -DFAC=>DFAC.  
 DFCS 11 02 MR 6 5 RV SKP 0,1,2 IF (DFAC)>,.<[EA]64.  
 DFD 31,33 MR 3 1 I DOUBLE FLTG DIVIDE.  
 DFDV 17 02 MR 3 5 RV (DFAC) / [EA]64 => DFAC.  
 DFL 01 03 MR -- I DBLE FLTG LOAD. [EA643]=>DFR.  
 DFLD 02 02 MR -- RV [EA]64 => DFAC.  
 DFLX 15 02 MR -- V LD DFLT INDEX. 4\*[EA]16 => X.  
 DFM 25 27 MR 3 1 I DBL FLTG MULT. DFR/[EA64]=>DFR.  
 DFMP 16 02 MR 3 5 RV (DFAC) \* [EA]64 => DFAC.  
 DFS 21 23 MR 3 1 I DBLE FLTG SUB. DFR-[EA64]=>DFR.  
 DFSB 07 02 MR 3 5 RV (DFAC) - [EA]64 => DFAC.  
 DFST 11,13 MR 1 1 I DBLE FLTG STORE. DFR=>[EA64].  
 DFST 04 02 MR -- RV (DFAC) => [EA]64.  
 DH 72 MR 3 1 I DIV HW. R/[EA16]=>RH RM=>RL(2).  
 DH1 50130 OPR 2 1 I DECR HALF REG BY 1. GRH-1=>GRH.  
 DH2 50131 OPR 2 1 I DECR HALF REG BY 2. GRH-2=>GRH.  
 DIV 17 MR 3 5 V (A,B)/[EA]16=>A,REM=>B. (NOHOLE)  
 DIV 17 MR 3 5 SR (A,B)/[EA]16=>A;REM=>B. (W/HOLE)  
 DLD 02 (DP) MR -- SR DOUBLE LOAD. [EA]32 => A,B.  
 DM 60 MR - 1 I DECR. [EA32]-1=>[EA32].  
 DMH 70 MR - 1 I DECR HALDWD. [EA16]-1=>[EA16].  
 DR1 50124 OPR 2 1 I DECR REG BY 1. GR-1=>GR.  
 DR2 50125 OPR 2 1 I DECR REG BY 2. GR-2=>GR.  
 DRX 140210 OPR -- SRV DECREMENT X AND SKIP IF 0.  
 DSB 07 (DP) MR 2 1 SR (A,B)-[EA]32 => A,B (W/HOLE).  
 DST 04 (DP) MR -- SR DOUBLE STORE. (A,B) => [EA]32.  
 DVL 17 03 MR 3 5 V (A,B,E)/[EA]32=>A,B REM=>EH,EL.  
 E16S 000011 MOD -- SRV ENTER P300 16K SECTORED MODE.  
 E32I 001010 MOD -- SRV ENTER P500 32L MODE.  
 E32R 001013 MOD -- SRVI ENTER P300 32K RELATIVE MODE.  
 E32S 000013 MOD -- SRVI ENTER P300 32K SECTORED MODE.  
 E64R 001011 MOD -- SRVI ENTER P300 64K RELATIVE MODE.  
 E64V 000010 MOD -- SRVI ENTER P400 MODE.

EAA 01 01 MR -- R EFF. ADDR TO A-REG. EA => A.  
 EAFA 001300 AP -- SRVI EFF. ADDR TO FIELD REG 0.  
 EAFA 001310 AP -- SRVI EFF. ADDR TO FIELD REG 1.  
 EAL 01 01 MR -- V LOAD EFFECTIVE ADDR. EA => L.  
 EALB 42 MR -- I EFF ADDR to LB. EA=>LB.  
 EALB 13 02 MR -- V EFF. ADDR TO LB. EA => LB.  
 EAR 63 MR -- I EFF ADDR (EA32)TO R.  
 EAXB 52 MR -- I EFF ADDR TO XB. EA=>XB.  
 EAXB 12 02 MR -- V EFF. ADDR TO XB. EA => XB.  
 EIO 34 MR - 2 I EXECUTE ADDR TO BASE REG.  
 EIO 14 01 MR - 7 V\* EXEC EA AS I/O INSTR.CCEQ=>SKP.  
 EMCM 000503 IG -- SRVI\*ENTER MACH CHK MODE.  
 ENB 000401 IO -- SRVI\*ENABLE INTERRUPTS.  
 ENTR 01 03 MR -- R (S)=>[(S)-EA]16, (S)-EA=>S.  
 EPMJ 000217 VM -- SR ENT PAGE MODE AND JUMP (P300).  
 EPMX 000237 VM -- SR ENT PAG MOD & JMP TO MICROCODE.  
 ERA 05 MR -- SRV (A) .XOR. [EA]16 => A.  
 ERL 05 03 MR -- V (A,B) .XOR. [EA]32 => A,B.  
 ERMJ 000701 VM -- SR ENTER RESTR MODE & JUMP (P300).  
 ERMX 000721 VM -- SR RESTR MOD & JUMP TO MICROCODE.  
 ESIM 000415 MOD -- SRVI\*ENTER STANDAGR INTERRUPT MODE.  
 EVIM 000417 MOD -- SRVI\*ENTER VECTORED INTERRUPT MODE.  
 EVMJ 000703 VM -- SR ENT VIRT MODE AND JUMP (P300).  
 EVMX 000723 VM -- SR VIRT MOD & JUMP TO MICROCODE.  
 FA 14,16 MR 3 1 I FLTG ADD. FR+[EA32]=>FR.  
 FAD 06 01 MR 3 5 RV (FAC) + [EA]32 => FAC.  
 FC 04,06 MR - 1 I FLTG COMPARE FR TO [EA32]  
 FCM 50100 FOP 3 1 I FLTG COMP. -FGR=>FGR.  
 FCM 140530 FOP 3 5 SRV FLOATING COMP. -FAC=>FAC.  
 FCS 11 01 MR 6 5 RV SKIP 0,1,2 IF (FAC)>,.<[EA]32.  
 FD 30,32 MR 3 1 I FLTG DIV. -FR/[EA32]=>FR.  
 FDBL 140016 FOP -- SRV FAC=>DFAC.  
 FDV 17 01 MR 3 5 RV (FAC) / [EA]32 => FAC.  
 FLD 02 01 MR -- RV FLOATING LOAD. [EA]32 => FAC.  
 FLOT 140550 FOP 6 5 SRV FLOT(A,B)=>FAC. (A,B) W/HOLE  
 FLT 50105 FOP -- I CONV INT TO FLTG PT FLOAT.  
 FLTA 140532 FOP 3 5 SRV FLOT(A)=>FAC.  
 FLTH 50102 FOP -- I CNV HALF WD INT TO FLTG PT.  
 FLTL 140535 FOP 8 5 SRV FLOT(L)=>FAC. (L W/NO HOLE)  
 FLX 15 01 MR -- RV 2\*[EA]16 => X.  
 FM 24,26 MR 3 1 I FLTG MULT. FR\*[EA32]=>FR.  
 FMP 16 01 MR 3 5 RV (FAC) \* [EA]32 => FAC.  
 FRN 50107 FOP 3 1 I FLOATING ROUND UP.  
 FRN 140534 FOP 3 5 SRV FLOATING ROUND UP.  
 FS 20,22 MR 3 1 I FLTG SUB. FR-[EA32]=>FR.  
 FSB 07 01 MR 3 5 RV (FAC) - [EA]32 => FAC.  
 FSGT 140515 FSK - 4 SRV FLOATING SKIP IF .GT. 0.  
 FSLE 140514 FSK - 4 SRV FLOATING SKIP IF .LE. 0.  
 FSMI 140512 FSK - 4 SRV FLOATING SKIP IF .LT. 0.  
 FSNZ 140511 FSK - 4 SRV FLOATING SKIP IF .NE. 0.  
 FSPL 140513 FSK - 4 SRV FLOATING SKIP IF .GE. 0.  
 FST 10,12 MR -- I FLTG STORE. FR=>[EA32].  
 FST 04 01 MR 6 6 RV (FAC) => [EA]32.  
 FSZE 140510 FSK - 4 SRV FLOATING SKIP IF .EQ. 0.  
 HLT 000000 CON -- SRVI\*HALT COMPUTER OPERATION.  
 I 41 MR -- I INTERCHANGE R WITH [EA32].  
 IAB 000201 OPR -- SRV EXCHANGE A AND B A=>B & B=>A.

ICA 141340 OPR - - SRV INTERCHANGE BYTES OF A REG.  
 ICBL 50065 OPR - - I GRH(1-8)=>GRH(9-16), 0=>R.  
 ICBR 50066 OPR - - I GRH(9-16)=>GRH(1-8), 0=>  
 ICHL 50060 OPR - - I GRH=>GRL, 0=>GRH.  
 ICHR 50061 OPR - - I GRL=>GRH, 0=>GRL.  
 ICL 141140 OPR - - SRV EXCHANGE BYTES OF A, CLR LEFT.  
 ICR 141240 OPR - - SRV EXCHANGE BYTES OF A, CLR RIGHT.  
 IH 51 MR - - I INTERCHANGE RH WITH [EA16].  
 IH1 50126 OPR 2 1 I GRH+1=>GRH.  
 IH2 50127 OPR 2 1 I GRH+2=>GRH.  
 ILE 141414 OPR - - SRV EXCHANGE L AND E. L=>E & E=>L.  
 IM 40 I - 1 I INCR. [EA31]+1=>[EA32].  
 IMA 13 MR - - SRV EXCHANGE MEMORY AND A-REGISTER.  
 IMH 0 MR - 1 I INCR HALF WD. [EA16]+1=>[EA16].  
 INA 54 PIO - - SR\* INPUT TO A-REGISTER.  
 INBC 001217 AP 6 5 SRVI\*NTFY IN INT, LIFO, DO CAI.  
 INBN 001215 AP 6 5 SRVI\*NTFY IN INT, LIFO, NO CAI.  
 INEC 001216 AP 6 5 SRVI\*NTFY IN INT, FIFO Q, DO CAI.  
 INEN 001214 AP 6 5 SRVI\*NTFY IN INT, FIFO Q, NO CAI.  
 INH 001001 IO - - SRVI\*INHIBIT INTERRUPTS.  
 INK 50070 OPR - - I MOVE KEYS TO REG KEYS.  
 INK 000043 OPR - - SRV INPUT P-300 KEYS INTO A REG.  
 INT 50103 FOP - - I INT(FRS)=>GR.  
 INT 140554 FOP 3 5 SRV INT(FAC)=>A,B W/HOLE.  
 INTA 140531 FOP 3 5 SRV INT(FAC)=>A.  
 INTH 50101 FOP - - I INT(FRS)=>GRH.  
 INTL 140533 FOP 3 5 SRV INT(FAC)=>L.  
 IR1 50122 OPR 2 1 I INCR REG BY 1. GR+1=>GR.  
 IR2 50123 OPR 2 1 I INCR REG BY 2. GR+2=>GR.  
 IRB 50062 OPR - - I BYTES GRH(1-8)=>GRH(9-16)  
 IRH 50057 OPR - - I GRH=>GRL, GRL=>GRH.  
 IRS 12 MR - - SRV INC, REPLACE, AND SKIP IF ZERO.  
 IRTC 000603 CON 7 6 SRVI\*INTERRUPT RETURN, DO CAI.  
 IRTN 000601 CON 7 6 SRVI\*INTERRUPT RETURN, NO CAI.  
 IRX 140114 OPR - - SRV INCREMENT X AND SKIP IF 0.  
 ITLB 000615 CON - - SRVI\*INVAL STLB ENTRY, L = VADDR.  
 JDX 15 02 MR - - R JUMP ON DECREMENTED X-R ZERO.  
 JEQ 02 03 MR - - R IF (A) .EQ. 0, EA => P.  
 JGE 07 03 MR - - R IF (A) .GE. 0, EA => P.  
 JGT 05 03 MR - - R IF (A) .GT. 0, EA => P.  
 JIX 15 03 MR - - R JUMP ON INCREMENTED X-REG ZERO.  
 JLE 04 03 MR - - R IF (A) .LE. 0, EA => P.  
 JLT 06 03 MR - - R IF (A) .LT. 0, EA => P.  
 JMP 51 MR - - I JUMP. EA=>RP.  
 JMP 01 MR - - SRV UNCOND JUMP. EA => PB,P.  
 JNE 03 03 MR - - R IF (A) .NE. 0, EA => P.  
 JSR 73 MR - - I RPL=>RH, EA32=>RP  
 JST 10 MR - - SRV (P) => [EA]16, EA+1 => P.  
 JSX 35 03 MR - - RV (P) => X, EA => P.  
 JSXB 61 MR - - I RP=>XB, EA=>RP.  
 JSXB 14 02 MR - - V (PB,P) => XB, EA => PB,P.  
 JSY 14 MR - - V (P) => Y, EA => P.  
 L 01 MR - - I LOAD. [EA32]=>R.  
 LCEQ 50153 LOG - - I IF .EQ., 1=>GRH, ELSE 0=>GRH.  
 LCEQ 141503 LOG - - SRV IF CC.EQ.,1=>A. ELSE 0=>A.  
 LCGE 50154 LOG - - I IF .GE.,1=>GRH, ELSE 0=>GRH.  
 LCGE 141504 LOG - - SRV IF CC.GE.,1=>A. ELSE 0=>A.

LCGT 50155 LOG - - I IF .GT., 1=>GRH, ELSE 0=>GRH.  
 LCGT 141505 LOG - - SRV IF CC.GT.,1=>A. ELSE 0=>A.  
 LCLE 50151 LOG - - I IF .LE., 1=>GRH, ELSE 0=>GRH.  
 LCLE 141501 LOG - - SRV IF CC.LE.,1=>A. ELSE 0=>A.  
 LCLT 50150 LOG - - I IF .LT., 1=>GRH, ELSE 0=>GRH.  
 LCLT 141500 LOG - - SRV IF CC.LT.,1=>A. ELSE 0=>A.  
 LCNE 50152 LOG - - I IF .NE.,1=>GRH, ELSE 0=>GRH.  
 LCNE 141502 LOG - - SRV IF CC.NE.,1=>A. ELSE 0=>A.  
 LDA 02 MR - - SRV LOAD A-REGISTER. [EA]16 => A.  
 LDAR 44 MR - - I LOAD ADDR REGISTER.  
 LDC 50162 FLD - 7 I LOAD CHAR TO GRH.  
 LDC 001312 FLD - 7 SRV LOAD CHAR TO A REG PER FAR 1.  
 LDC 001302 FLD - 7 SRV LOAD CHAR TO A REG VIA FAR 0.  
 LDL 02 03 MR - - V LOAD LONG. [EA]32 => A,B.  
 LDLR 05 01 MR - - V LOAD LONG FROM RFILE LOC EA.  
 LDX 35 MR - - SRV LOAD X-REGISTER. [EA]16 => X.  
 LDY 35 01 MR - - V LOAD Y-REGISTER. [EA]16 => Y.  
 LEQ 50003 LOG - 4 I IF GR=0 TN 1=>GRH,ELSE 0=>GRH.  
 LEQ 140413 LOG - 4 SRV IF A.EQ.0, 1=>A. ELSE 0=>A.  
 LF 50016 LOG - 4 I LOGICIZE .F. 0=>GRH.  
 LF 140416 LOG - 5 SRV LOGICIZE FALSE. 0=>A.  
 LFEQ 50023 LOG - 4 I IF FRS=0 TN 1=>GRH,ELSE 0=>GRH.  
 LFEQ 141113 LOG - 4 SRV IF FAC.EQ.0, 1=>A. ELSE 0=>A.  
 LFGC 50024 LOG - 4 I IF FRS=>0 T 1=>GRH,ELSE 0=>GRH.  
 LFGC 141114 LOG - 4 SRV IF FAC.GE.0, 1=>A. ELSE 0=>A.  
 LFGT 50025 LOG - 4 I IF FRS>0 TN 1=>GRH,ELSE 0=>GRH.  
 LFGT 141115 LOG - 4 SRV IF FAC.GT.0, 1=>A. ELSE 0=>A.  
 LFLE 50021 LOG - 4 I IF FRS<=0 T 1=>GRH,ELSE 0=>GRH.  
 LFLE 141111 LOG - 4 SRV IF FAC.LE.0, 1=>A. ELSE 0=>A.  
 LFLI 001313 - - - SRV LOAD FIELD LEN REG IMM ONE.  
 LFLI 001303 - - - SRV LOAD FIELD LEN REG IMM ZERO.  
 LFLT 50020 LOG - 4 I IF FRS<0 T 1=>GRH,ELSE 0=>GRH.  
 LFLT 141110 LOG - 4 SRV IF FAC.LT.0, 1=>A. ELSE 0=>A.  
 LFNE 50022 LOG - 4 I IF FRS<>0 T 1=>GRH,ELSE 0=>GRH.  
 LFNE 141112 LOG - 4 SRV IF FAC.NE.0, 1=>A. ELSE 0=>A.  
 LGE 50004 LOG - 4 I IF GR>=0 TN 1=>GRH,ELSE 0=>GRH.  
 LGE 140414 LOG - 4 SRV IF A.GE.0, 1=>A. ELSE 0=>A.  
 LGT 50005 LOG - 4 I IF GR>0 TN 1=>GRH, ELSE 0=>GRH.  
 LGT 140415 LOG - 4 SRV IF A.GT.0, 1=>A. ELSE 0=>A.  
 LH 11 MR - - I LOAD HALF WD. [EA16]=>RH.  
 LHEQ 50013 LOG - 4 I IF GRH=0 TN 1=>GRH,ELSE 0=>GRH.  
 LHGE 50004 LOG - 4 I IF GRH>=0 T 1=>GRH,ELSE 0=>GRH.  
 LHGT 50015 LOG - 4 I IF GRH>0 TN 1=>GRH,ELSE 0=>GRH.  
 LHL1 04 MR - - I SHIFTED 1 [EA16] .LS. 1=>GRH.  
 LHL2 14 MR - - I SHIFTED 2 [EA16] .LS. 2=>GRH.  
 LHLE 50011 LOG - 4 I IF GRH<=0 T 1=>GRH,ELSE 0=>GRH.  
 LHLT 50000 LOG - 4 I IF GR<0 TN 1=>GRH,ELSE 0=>GRH.  
 LHNE 50012 LOG - 4 I IF GRH<>0 T 1=>GRH,ELSE 0=>GRH.  
 LLE 50001 LOG - 4 I IF GR<=0 TN 1=>GRH,ELSE 0=>GRH.  
 LLE 140411 LOG - 4 SRV IF A.LE.0, 1=>A. ELSE 0=>A.  
 LLEQ 141513 LOG - 4 SRV IF L.EQ.0, 1=>A. ELSE 0=>A.  
 LLGE 140414 LOG - 4 SRV IF L.GE.0, 1=>A. ELSE 0=>A.  
 LLGT 141515 LOG - 4 SRV IF L.GT.0, 1=>A. ELSE 0=>A.  
 LLL 0410XX SH 4 5 SRV LONG LEFT LOGICAL.  
 LLL 141511 LOG - 4 SRV IF L.LE.0, 1=>A. ELSE 0=>A.  
 LLLT 140410 LOG - 4 SRV IF L.LT.0, 1=>A. ELSE 0=>A.  
 LLNE 141512 LOG - 4 SRV IF L.NE.0, 1=>A. ELSE 0=>A.

```

LLR 0412XX SH 4 5 SRV LONG LEFT ROTATE.
LLS 0411XX SH 4 5 SRV LNG LSFT 64V=>LNG INT,ELSE HOLE
LLT 50000 LOG - 4 I IF GR<0 TN 1=> GRH,ELSE 0=>GRH.
LLT 140410 LOG - 4 SRV IF A.LT.0, 1=>A. ELSE 0=>A.
LMCM 000501 IG - - SRVI*LEAVE MACHINE CHECK MODE.
LNE 50002 LOG - 4 I IF GR<0 TN 1=>GRH,ELSE 0=>GRH.
LNE 140412 LOG - 4 SRV IF A.NE.0, 1=>A. ELSE 0=>A.
LPID 000617 CON - - SRVI*LOAD PROCESS ID FROM A01-A12.
LPMJ 000215 VM - - SR LEAVE PAGE MODE & JUMP (P300).
LPMX 000235 VM - - SR LVE PAG MOD & JMP TO MICROCODE.
LPSW 000711 AP 7 6 SRVI*LOAD PSW (SN,WN,KEYS,MODALS).
LRL 0400XX SH 4 5 SRV LONG RIGHT LOGICAL.
LRR 0402XX SH 4 5 SRV LONG RIGHT ROTATE.
LRS 0401XX SH 4 5 SRV LNG RSFT.64V=LNG INT,ELSE HOLE.
LT 140417 LOG - 5 SRV LOGICIZE TRUE. 1=>A.
LWCS 001710 IG - - V LOAD WRITABLE CONTROL STORE.
M 42 MR 3 1 I MULT. R*[EA32]=>(R,R+1).
MDEI 001304 IG - - SRVI*MEM DIAG ENABLE INTERLEAVE.
MDII 001305 IG - - SRVI*MEM DIAGN INHIBIT INTERLEAVE.
MDIW 0013?? IG - - SRVI*MEM DIAG WRT INTERLV. L=>[E].
MDRS 001306 IG - - SRVI*MEM DIAG READ SYNDROME BITS.
MDWC 001307 IG - - SRV* MEM DIAG LOAD WRITE CTL REG.
MH 52 MR 3 1 I RH*[EA16]=>R.
MIA 64 MR - - I MICROCODE EXECUTE A.
MIA 12 01 MR - - V MICROCODE ENTRANCE.
MIB 74 MR - - I MICROCODE EXECUTE B.
MIB 13 01 MR - - V MICROCODE ENTRANCE.
MPL 16 03 MR - 1 V (A,B) * [EA]16 => A,B. (NOHOLE)
MPY 16 MR - 1 V (A) * [EA]16 => A,B. (NOHOLE).
MPY 16 MR 3 1 SR (A) * [EA]16 => A,B. (HOLE).
N 03 MR - - I R .AND. [EA32]=>R.
NFYB 001211 AP 6 5 SRVI*NOTIFY ON SEM AT AP. LIFO Q.
NFYE 001210 AP 6 5 SRVI*NOTIFY ON SEM AT AP. FIFO Q.
NH 13 MR - - I RH .AND. [EA16]=>RH.
NOP 000001 OPR - - SRV NO OPERATION.
NRM 000101 OPR - - SRV NORMALIZE A,B AS ON P-300.
O 23 MR - - I R .OR. [EA32]=>R.
OCP 14 PIO - - SR* OUTPUT CONTROL PULSE.
OH 33 MR - - I RH .OR. [EA16]=>RH.
ORA 03 02 MR - - V (A) .OR. [EA]16 => A.
OTA 74 PIO - - SR* OUTPUT FROM A-REGISTER.
OTK 50071 OPR 7 S I SET KEYS FROM REGISTER
OTK 000405 OPR 7 6 SRV OUTPUT A TO 300 KEYS, SHFT CTR.
PCL 41 MR - - I PROCEDURE CALL.
PCL 10 02 MR 7 6 V P-400 PROCEDURE CALL.
PID 50052 OPR - - I GR=>GRN, (1)=>GR(2-32).
PID 000211 OPR - - SRV SHORT INT TO DP INT W/HOLE.
PIDA 000115 OPR - - SRV SHORT TO LONG INT CONV. A=>L.
PIDH 50053 OPR - - I GRH=>GRL,GRH(1)=>GRH(2-16).
PIDL 000305 OPR - - SRV CONVERT LONG INT TO 64 BIT INT.
PIM 50050 OPR 2 1 I POS REG AFTER INT MULTIPLY.
PIM 000205 OPR - - SRV DP INT WITH HOLE TO SHORT INT.
PIMA 000015 OPR 3 5 SRV L=>A. IEX ON PREC LOSS.
PIMH 50051 OPR 2 1 I POS HALF REG AFTER INT MULT.
PIML 000301 OPR 3 5 SRV 64BIT INT TO LONG INT. (L,E)=>L.
PRTN 000611 CON 7 6 SRVI PROCEDURE RETURN.
RBQ 50133 OPR - 7 I REMOVE FROM BOTTOM OF QUEUE.

```

```

RBQ 141715 AP - 6 SRV RMV BOT OF Q. EMP=>A=0, CCEQ
RCB 140200 OPR 5 - SRV RESET CBIT. 0=>CBIT.
RMC 000021 IG - - SRVI*RESET MACHINE CHECK FLAG.
RRST 000717 AP - - SRV REST REGS (GEN, FLT, XB).
RSAV 000715 AP - - SRV SAVE REGS (GEN, FLT, XB).
RTN 000105 OPR - - SRV RETURN FROM P-300 RECUR PROC.
RTQ 50132 OPR - 7 I REMOVE FROM TOP OF QUEUE.
RTQ 141714 AP - 6 SRV RMV TOP OF Q. EMP=>A=0, CCEQ.
S 22 MR 2 1 I SUB. R-[EA32]=>R.
S1A 140110 OPR 2 1 SRV SUB 1 FROM A REGISTER. A-1=>A.
S2A 140310 OPR 2 1 SRV SUB 2 FROM A REGISTER. A-2=>A.
SAR 10026X SKP - - SRV SKIP IF A REG. BIT N RESET.
SAS 101260 SKP - - SRV SKIP IF A REG. BIT N SET.
SBL 07 03 MR 2 1 V (A,B) - [EA]32 => A,B. (NOHOLE)
SCA 000041 OPR - - SRV LOAD P-300 SHFT CTR INTO A REG.
SCB 140600 OPR 5 - SRV SET CBIT. 1=>CBIT.
SGL 000005 MOD - - SRV ENTER SINGLE-PRECISION MODE.
SGT 100220 SKP - - SRV SKIP IF A REG. .GT. 0.
SH 32 MR 2 1 I SUB HALF WD. RH-[EA16]=>RH.
SHA 15 MR 4 - I ARITHMETIC SHIFT.
SHL 05 MR 4 - I LOGICAL SHIFT.
SHL1 50076 OPR 4 1 I GRH .LS. 1 => GRH.
SHL2 50077 OPR 4 1 I GRH .LS. 2 => GRH.
SHR1 50120 OPR 4 1 I GRH .RS. 1 => GRH.
SHR2 50121 OPR 4 1 I GRH .RS. 2 => GRH.
SKP 100000 SKP - - SRV SKIP ONE WORD.
SKS 34 PIO - - SR SKIP IF CONDITION SET.
SL1 50072 OPR 4 1 I GR .LS. 1 => GR.
SL2 50073 OPR 4 1 I GR .LS. 2 => GR.
SLE 101220 SKP - - SRV SKIP IF A REG. .LE. 0.
SIN 101100 SKP - - SRV SKIP IF A REG. BIT 16 SET.
SLZ 100100 SKP - - SRV SKIP IF A REG. BIT 16 .EQ. 0.
SMCR 100200 SKP - - SRV SKIP IF MACHINE CHECK RESET.
SMCS 101200 SKP - - SRV SKIP IF MACHINE CHECK SET.
SMI 101400 SKP - - SRV SKIP IF A REG. .LT. 0.
SMK 170020 PIO - - SR* SET INTERRUPT MASKS.
SNR 10024X SKP - - SRV* SKIP IF SENSE SWITCH N RESET.
SNS 101240 SKP - - SRV* SKIP IF SENSE SWITCH N SET.
SNZ 101040 SKP - - SRV SKIP IF A REG. NE. 0.
SPL 100400 SKP - - SRV SKIP IF A REG. .GE. 0.
SR1 50074 OPR 4 1 I GR .RS. 1 => GR.
SR1 100020 SKP - - SRV* SKIP IF SENSE SWITCH 1 RESET.
SR2 50075 OPR 4 1 I GR .RS. 2 => GR.
SR2 100010 SKP - - SRV* SKIP IF SENSE SWITCH 2 RESET.
SR3 100004 SKP - - SRV* SKIP IF SENSE SWITCH 3 RESET.
SR4 100002 SKP - - SRV* SKIP IF SENSE SWITCH 4 RESET.
SRC 100001 SKP - - SRV SKIP IF CBIT RESET.
SS1 101020 SKP - - SRV* SKIP IF SENSE SWITCH 1 SET.
SS2 101010 SKP - - SRV* SKIP IF SENSE SWITCH 2 SET.
SS3 101004 SKP - - SRV* SKIP IF SENSE SWITCH 3 SET.
SS4 101002 SKP - - SRV* SKIP IF SENSE SWITCH 4 SET.
SSC 101001 SKP - - SRV SKIP IF CBIT SET.
SSM 50042 OPR - - I SET SIGN. MINUS 1=>(1).
SSM 140500 OPR - - SRV SET SIGN OF A MINUS. 1=>A1.
SSP 50043 OPR - - I SET SIGN. PLUS 0=>(1).
SSP 140100 OPR - - SRV SET SIGN OF A PLUS. 0=>ABIT1.
SSR 100036 SKP - - SRV* SKIP IF SSWI 1,2,3 AND 4 RESET.

```

SSS 101036 SKP - - SRV\* SKIP IF SSWI 1,2,3 AND 4 SET.  
 ST 21 MR - - I STORE. R=>[EA32].  
 STA 04 MR - - SRV STORE A-REG. (A) => [EA]16.  
 STAC 001200 AP - 7 SRV ST A COND ON B=[EA16].CCEQ= OK.  
 STAR 54 MR - - I STORE ADDRESSED REGISTER.  
 STC 50166 FLD - 7 I STORE CHARACTER FROM GRH.  
 STC 001332 FLD - 7 SRV STORE CHAR FROM A (SEE FAR1).  
 STC 001322 FLD - 7 SRV STORE CHAR FROM A (SEE FAR0).  
 STCD 50137 OPR - 7 I GR+1=[EA16].  
 STCH 50136 OPR - 7 I GRL=[EA16].  
 STEX 50027 OPR - 7 I STACK EXTEND.  
 STEX 001315 OPR 6 5 SRV STK EXTEND. L REG HAS EXTENT.  
 STFA 001330 AP - - SRVI STORE FIELD ADDR REG 1.  
 STFA 001320 AP - - SRVI STORE FIELD ADDR REG 0.  
 STH 31 MR - - I STORE HALF WD. RH=>[EA16].  
 STL 04 03 MR - - V STORE LONG. (A,B) => [EA]32.  
 STLC 001204 AP - 7 SRV ST L COND ON E=[EA32].CCEQ=OK.  
 STLR 03 01 MR - - V STORE LONG INTO RFILE LOC EA.  
 STX 15 MR - - SRV STORE X-REG. (X) => [EA]16.  
 STY 35 02 MR - - V STORE Y-REG. (Y) => [EA]16.  
 SUB 07 MR 2 1 SRV SUBTRACT. (A) - [EA]16 => A.  
 SVC 000505 CON - - SRVI SUPERVISOR CALL.  
 SZE 100040 SKP - - SRV SKIP IF A REG .EQ. 0.  
 TAB 140314 OPR - - SRV TRANSFER A TO B REG. A=>B.  
 TAK 001015 OPR 7 6 SRV TRANSFER A TO KEYS.  
 TAX 140504 OPR - - SRV TRANS A REG TO X REG. A=>X.  
 TAY 140505 OPR - - SRV TRANS A REG TO Y REG. A=>Y.  
 TBA 140604 OPR - - SRV TRANS B REG TO A REG. B=>A.  
 TC 50047 OPR 3 1 I -GR+1=>GR.  
 TCA 140407 OPR 2 1 SRV TWO'S COMPLEMENT A. -A=>A.  
 TCH 50047 OPR 3 1 I -GRH+1=>GRH.  
 TCL 141210 OPR 2 1 SRV TWO'S COMPLEMENT L. -L=>L.  
 TFLL 001333 FLD - - SRV XFER FLD LEN REG TO L REG 1.  
 TFLL 001323 FLD - - SRV XFER FLD LEN REG TO L REG 0.  
 TFLR 50163 FLD - 7 I TRANSFER FLD LENGTH REG TO GR.  
 TKA 001005 OPR - - SRV TRANSFER KEYS TO A.  
 TLF 001321 FLD - - SRV TRANS L TO FLD LEN REG 0.  
 TLF 001331 FLD - - SRV TRANSFER L TO FLD LEN REG 1.  
 TM 44 MR - 1 I REST MEM. [EA32]::0=>CC.  
 TRFL 50165 FLD - 7 I TRANSFER GR TO FLD LENGTH REG.  
 TSTQ 50104 OPR - 7 I TEST QUEUE.  
 TSTQ 141757 AP - 6 SRV TEST Q. A=# ITEMS. CCEQ=> EMP.  
 TXA 141034 OPR - - SRV TRANS X REG TO A REG. X=>A.  
 TYA 141124 OPR - - SRV TRANS Y REG TO A REG. Y=>A.  
 VIRY 000311 IG 5 6 SRV\* EXECUTE VERIFICATION ROUTINE.  
 WAIT 000315 AP - - SRV\* WAIT ON SEMAPHORE AT AP.  
 WCS 0016XX - - - SRV\* WCS ENTRANCES. UII ON NO WCS.  
 X 43 MR - - I EXC OR. R.XOR. [EA32]=>R.  
 XAD 001100 DA X X VI ADD TWO DECIMAL FLDS.  
 XBTD 001145 DA X X VI CONV BI DEC VALUE TO DEC FLD.  
 XCA 140104 OPR - - SRV EXCHG AND CLR A. A=>B, 0=>A.  
 XCB 140204 OPR - - SRV EXCHG AND CLR B. B=>A, 0=>B.  
 XEC 01 02 MR - - RV EXECUTE INSTRUCTION AT EA.  
 XCM 001102 DA X X VI COMP TWO NUMERIC FLDS.  
 XDIB 001146 DA X X VI CONV DEC FLD TO BI REG VALUE.  
 XDZ 001107 DA X X VI DIV DEST FLD BY SOURCE FLD.  
 XEC 01 02 MR - - RV EX EFF ADDR CONT AS THIS INST.

XED 001112 FE X X VI EDIT NUMERIC FIELD.  
 XH 52 MR - - I RH .XOR. [EA16]=>RH.  
 XMP 001104 DA X X VI MULTIPLY TWO DEC FLDS.  
 XMV 001101 DA X X VI MOVE NUM SOURCE FLD TO DST FLD.  
 ZCM 001117 CS X X VI COMP TWO CHAR STR FIELDS.  
 ZED 001111 FE X X VI EDIT CHAR STR FIELD.  
 ZFIL 011116 CS X X VI FILL CHAR STR FLD WITH CHAR.  
 ZM 43 MR - - I ZERO MEM. 0=>[EA32].  
 ZMH 53 MR - - I ZERO MEM. HALF WD. 0=>[EA16].  
 ZMV 001114 CS X X VI CPY FRM SOURCE FLD TO DEST FLD.  
 ZMVD 001115 - X X VI CPY FROM SOURCE FLD TO DEST  
 FLD OF EQUAL LENGTH.  
 ZTRN 001110 CS X X VI TRANS SRCE STR FLD TO DEST FLD.  
 xxx 140014 OPR - - SRV OBSOLETE. CLRS B, LSW OF DFAC.

INSTRUCTION SET GROUPED BY FUNCTIONMiscellaneous Operations

CGT 001314 - 6 5 SRV COMPUTED GO TO.  
 LFLI 001313 - - - SRV LOAD FIELD LEN REG IMM ONE.  
 LFLI 001303 - - - SRV LOAD FIELD LEN REG IMM ZERO.  
 WCS 0016XX - - - SRV\* WCS ENTRANCES. UII ON NO WCS.  
 ZMVD 001115 - X X VI CPY FROM SOURCE FLD TO DEST

Address Pointer Operations

ABQ 141716 AP - 6 SRV ADD TO BOT OF Q. CCEQ => FULL.  
 ATQ 141717 AP - 6 SRV ADD TO TOP OF Q. CCEQ => FULL.  
 CALF 000705 AP 7 6 SRV PROC CALL FROM FAULTING PROC.  
 EAFA 001300 AP - - SRVI EFF. ADDR TO FIELD REG 0.  
 EAFA 001310 AP - - SRVI EFF. ADDR TO FIELD REG 1.  
 INBC 001217 AP 6 5 SRVI\*NTFY IN INT, LIFO, DO CAI.  
 INBN 001215 AP 6 5 SRVI\*NTFY IN INT, LIFO, NO CAI.  
 INEC 001216 AP 6 5 SRVI\*NTFY IN INT, FIFO Q, DO CAI.  
 INEN 001214 AP 6 5 SRVI\*NTFY IN INT, FIFO Q, NO CAI.  
 LPSW 000711 AP 7 6 SRVI\*LOAD PSW (SN,WN,KEYS,MODALS).  
 NFYB 001211 AP 6 5 SRVI\*NOTIFY ON SEM AT AP. LIFO Q.  
 NFYE 001210 AP 6 5 SRVI\*NOTIFY ON SEM AT AP. FIFO Q.  
 RBQ 141715 AP - 6 SRV RMV BOT OF Q. EMP=>A=0, CCEQ  
 RST 000717 AP - - SRV REST REGS (GEN, FLT, XB).  
 RSV 000715 AP - - SRV SAVE REGS (GEN, FLT, XB).  
 RTQ 141714 AP - 6 SRV RMV TOP OF Q. EMP=>A=0, CCEQ.  
 STAC 001200 AP - 7 SRV ST A COND ON B=[EA16].CCEQ= OK.  
 STFA 001330 AP - - SRVI STORE FIELD ADDR REG 1.  
 STFA 001320 AP - - SRVI STORE FIELD ADDR REG 0.  
 STLC 001204 AP - 7 SRV ST L COND ON E=[EA32].CCEQ=OK.  
 TSTQ 141757 AP - 6 SRV TEST Q. A=# ITEMS. CCEQ=> EMP.  
 WAIT 000315 AP - - SRV\* WAIT ON SEMAPHORE AT AP.

Branch Operations

BCEQ 141602 BR - - SRV BRANCH ON CONDITION CODE .EQ.  
 BCGE 141605 BR - - SRV BRANCH ON CONDITION CODE .GE.

BCGT	141601	BR	--	SRV	BRANCH ON CONDITION CODE .GT.
BCLE	141600	BR	--	SRV	BRANCH ON CONDITION CODE .LE.
BCLT	141704	BR	--	SRV	BRANCH ON CONDITION CODE .LT.
BCNE	141603	BR	--	SRV	BRANCH ON CONDITION CODE .NE.
BCR	141705	BR	--	SRV	BRANCH ON CBIT RESET.
BCS	141604	BR	--	SRV	BRANCH ON CBIT SET.
BDX	140734	BR	--	SRV	BRANCH ON DECREMENTED X.
BDY	140724	BR	--	SRV	BRANCH ON DECREMENTED Y.
BEQ	140612	BR	- 4	SRV	BRANCH ON A REGISTER .EQ. 0.
BFEQ	50122	BR	- 4	I	BRANCH ON FLTG REG EQ.
BFEQ	141612	BR	- 4	SRV	BRANCH ON FAC .EQ. 0.
BFGE	50125	BR	- 4	I	BRANCH ON FLTG REG NE.
BFGE	141615	BR	- 4	SRV	BRANCH ON FAC .GE. 0.
BFGT	50121	BR	- 4	I	BRANCH ON FLTG REG LE.
BFGT	141611	BR	- 4	SRV	BRANCH ON FAC .GT. 0.
BFLE	50120	BR	- 4	I	BRANCH ON FLTG REG LT.
BFLE	141610	BR	- 4	SRV	BRANCH ON FAC .LE. 0.
BFLT	50124	BR	- 4	I	BRANCH ON FLTG REG GT.
BFLT	141614	BR	- 4	SRV	BRANCH ON FAC .LT. 0.
BFNE	50123	BR	- 4	I	BRANCH ON FLTG REG GE.
BFNE	141613	BR	- 4	SRV	BRANCH ON FAC .NE. 0.
BGE	140615	BR	- 4	SRV	BRANCH ON A REGISTER .GE. 0.
BGT	140611	BR	- 4	SRV	BRANCH ON A REGISTER .GT. 0.
BHD1	50144	BR	--	I	BRANCH ON HALF REG DEC BY 1.
BHD2	50145	BR	--	I	BRANCH ON HALF REG DEC BY 2.
BHD4	50146	BR	--	I	BRANCH ON HALF REG DEC BY 4.
BHEQ	50112	BR	- 4	I	BRANCH ON HALF REG EQ.
BHGT	50111	BR	- 4	I	BRANCH ON HALF REG LE.
BHI1	50140	BR	--	I	BRANCH ON HALF REG INCR BY 1.
BHI2	50141	BR	--	I	BRANCH ON HALF REG INCR BY 2.
BHI4	50142	BR	--	I	BRANCH ON HALF REG INCR BY 4.
BHLE	50110	BR	- 4	I	BRANCH ON HALF REG LT.
BHLT	50104	BR	- 4	I	BRANCH ON HALF REG GT.
BHNE	50113	BR	- 4	I	BRANCH ON HALF REG GE.
BHNE	50105	BR	- 4	I	BRANCH ON HALF REG NE.
BIX	141334	BR	--	SRV	BRANCH ON INCREMENTED X.
BIY	141324	BR	--	SRV	BRANCH ON INCREMENTED Y.
BLE	140610	BR	- 4	SRV	BRANCH ON A REGISTER .LE. 0.
BLEQ	140702	BR	- 4	SRV	BRANCH ON L REGISTER .EQ. 0.
BLGE	140615	BR	- 4	SRV	BRANCH ON L REGISTER .GE. 0.
BLGT	140701	BR	- 4	SRV	BRANCH ON L REGISTER .GT. 0.
BLLE	140700	BR	- 4	SRV	BRANCH ON L REGISTER .LE. 0.
BLLT	140614	BR	- 4	SRV	BRANCH ON L REGISTER .LT. 0.
BLNE	140703	BR	- 4	SRV	BRANCH ON L REGISTER .NE. 0.
BLR	141707	BR	--	SRV	BRANCH ON LINK RESET.
BLS	141706	BR	--	SRV	BRANCH ON LINK SET.
BLT	140614	BR	- 4	SRV	BRANCH ON A REGISTER .LT. 0.
BMEQ	141602	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .EQ.
BMGE	141706	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .GE.
BMGT	141710	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .GT.
BMLE	141711	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .LE.
BMLT	141707	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .LT.
BMNE	141603	BR	--	SRV	BRANCH ON MAG.-COND. L,CC .NE.
BNE	140613	BR	- 4	SRV	BRANCH ON A REGISTER .NE. 0.
BRBR	50040	BR	--	I	BRANCH ON REG BIT RESET.
BRBS	50000	BR	--	I	BRANCH ON REG BIT SET.
BGR1	50134	BR	--	I	BRANCH ON REG DEC BY 1.

BGR2	50135	BR	--	I	BRANCH ON REG DEC BY 2.
BGR4	50136	BR	--	I	BRANCH ON REG DEC BY 4.
BREQ	50102	BR	- 4	I	BRANCH ON REG EQ.
BRGE	50105	BR	- 4	I	BRANCH ON REG NE.
BRGT	50101	BR	- 4	I	BRANCH ON REG LE.
BRI1	50130	BR	--	I	BRANCH ON REG INCR BY 1.
BRI2	50131	BR	--	I	BRANCH ON REG INCR BY 2.
BRI4	50132	BR	--	I	BRANCH ON REG INCR BY 4.
BRLE	50100	BR	- 4	I	BRANCH ON REGISTER LT.
BRLT	50104	BR	- 4	I	BRANCH ON REGISTER GT.
BRNE	50103	BR	- 4	I	BRANCH ON REGISTER GE.

Control Operations

ARGT	000605	CON	--	SRV	ARG TRANSFER (USED WITH PCL).
HLT	000000	CON	--	SRVI	*HALT COMPUTER OPERATION.
IRTC	000603	CON	7 6	SRVI	*INTERRUPT RETURN, DO CAL.
IRIN	000601	CON	7 6	SRVI	*INTERRUPT RETURN, NO CAL.
ITLB	000615	CON	--	SRVI	*INVAL STLB ENTRY, L = VADDR.
LPID	000617	CON	--	SRVI	*LOAD PROCESS ID FROM A01-A12.
PRTN	000611	CON	7 6	SRVI	PROCEDURE RETURN.
SVC	000505	CON	--	SRVI	SUPERVISOR CALL.

Character String Operations

ZCM	001117	CS	X X	VI	COMP TWO CHAR STR FIELDS.
ZFIL	011116	CS	X X	VI	FILL CHAR STR FLD WITH CHAR.
ZMV	001114	CS	X X	VI	CPY FRM SOURCE FLD TO DEST FLD.
ZTRN	001110	CS	X X	VI	TRANS SRCE STR FLD TO DEST FLD.

Decimal Arithmetic

XAD	001100	DA	X X	VI	ADD TWO DECIMAL FLDS.
XBTD	001145	DA	X X	VI	CONV BI DEC VALUE TO DEC FLD.
XCM	001102	DA	X X	VI	COMP TWO NUMERIC FLDS.
XDTB	001146	DA	X X	VI	CONV DEC FLD TO BI REG VALUE.
XDZ	001107	DA	X X	VI	DIV DEST FLD BY SOURCE FLD.
XMP	001104	DA	X X	VI	MULTIPLY TWO DEC FLDS.
XMV	001101	DA	X X	VI	MOVE NUM SOURCE FLD TO DST FLD.

Field and Edit Operations

XED	001112	FE	X X	VI	EDIT NUMERIC FIELD.
ZED	001111	FE	X X	VI	EDIT CHAR STR FIELD.

Field Operations

ALFA	001301	FLD	6 5	SRV	ADD L TO FIELD ADDR REG. ZERO.
ALFA	001311	FLD	6 5	SRV	ADD L TO FIELD ADDR REG. ONE.
ARFA	50161	FLD	- 7	I	ADD GR TO FIELD ADDR REG.
LDC	50162	FLD	- 7	I	LOAD CHAR TO GRH.
LDC	001312	FLD	- 7	SRV	LOAD CHAR TO A REG PER FAR 1.
LDC	001302	FLD	- 7	SRV	LOAD CHAR TO A REG VIA FAR 0.
STC	50166	FLD	- 7	I	STORE CHARACTER FROM GRH.
STC	001332	FLD	- 7	SRV	STORE CHAR FROM A (SEE FAR1).
STC	001322	FLD	- 7	SRV	STORE CHAR FROM A (SEE FAR0).
TFLL	001333	FLD	--	SRV	XFER FLD LEN REG TO L REG 1.

TFL 001323 FLD -- SRV XFER FLD LEN REG TO L REG 0.  
 TFLR 50163 FLD - 7 I TRANSFER FLD LENGTH REG TO GR.  
 TLFL 001321 FLD -- SRV TRANS L TO FLD LEN REG 0.  
 TLFL 001331 FLD -- SRV TRANSFER L TO FLD LEN REG 1.  
 TRFL 50165 FLD - 7 I TRANSFER GR TO FLD LENGTH REG.

Floating-point Operations

DBLE 50106 FOP -- I CONV SINGLE TO DOUBLE FLTG PT.  
 DFCM 50144 FOP 3 1 I DBL PRC FLTG COMP. -DFGR=>DFGR.  
 DFCM 140574 FOP 3 5 SRV -DFAC=>DFAC.  
 FCM 50100 FOP 3 1 I FLTG COMP. -FGR=>FGR.  
 FCM 140530 FOP 3 5 SRV FLOATING COMP. -FAC=>FAC.  
 FDBL 140016 FOP -- SRV FAC=>DFAC.  
 FLTH 50192 FOP -- I // HALF WD INT TO FLTG PT.  
 FLOT 140550 FOP 6 5 SRV FLOT(A,B)=>FAC. (A,B) W/HOLE  
 FLT 50105 FOP -- I CONV INT TO FLTG PT FLOAT.  
 FLTA 140532 FOP 3 5 SRV FLOT(A)=>FAC.  
 FLTL 140535 FOP 8 5 SRV FLOT(L)=>FAC. (L W/NO HOLE)  
 FRN 50107 FOP 3 1 I FLOATING ROUND UP.  
 FRN 140534 FOP 3 5 SRV FLOATING ROUND UP.  
 INT 50103 FOP -- I INT(FRS)=>GR.  
 INT 140554 FOP 3 5 SRV INT(FAC)=>A,B W/HOLE.  
 INTA 140531 FOP 3 5 SRV INT(FAC)=>A.  
 INTH 50101 FOP -- I INT(FRS)=>GRH.  
 INTL 140533 FOP 3 5 SRV INT(FAC)=>L.

Floating-point Skip Operations

FSGT 140515 FSK - 4 SRV FLOATING SKIP IF .GT. 0.  
 FSLE 140514 FSK - 4 SRV FLOATING SKIP IF .LE. 0.  
 FSMI 140512 FSK - 4 SRV FLOATING SKIP IF .LT. 0.  
 FSNZ 140511 FSK - 4 SRV FLOATING SKIP IF .NE. 0.  
 FSPL 140513 FSK - 4 SRV FLOATING SKIP IF .GE. 0.  
 FSZE 140510 FSK - 4 SRV FLOATING SKIP IF .EQ. 0.

Integrity Operations

CXCS 001714 IG -- V CONTROL EXTENDED CONTROL STORE.  
 EMCM 000503 IG -- SRVI\*ENTER MACH CHK MODE.  
 LMCM 000501 IG -- SRVI\*LEAVE MACHINE CHECK MODE.  
 LWCS 001710 IG -- V LOAD WRITABLE CONTROL STORE.  
 MDEI 001304 IG -- SRVI\*MEM DIAG ENABLE INTERLEAVE.  
 MDII 001305 IG -- SRVI\*MEM DIAGN INHIBIT INTERLEAVE.  
 MDIW 0013?? IG -- SRVI\*MEM DIAG WRT INTERLV. I=>[E].  
 MDRS 001306 IG -- SRVI\*MEM DIAG READ SYNDROME BITS.  
 MDWC 001307 IG -- SRV\* MEM DIAG LOAD WRITE CTL REG.  
 RMC 000021 IG -- SRVI\*RESET MACHINE CHECK FLAG.  
 VIRY 000311 IG 5 6 SRV\* EXECUTE VERIFICATON ROUTINE.

Input/Output Operations

CAI 000411 IO -- SRVI\*CLEAR ACTIVE INTERRUPT.  
 ENB 000401 IO -- SRVI\*ENABLE INTERRUPTS.  
 INH 001001 IO -- SRVI\*INHIBIT INTERRUPTS.

Logicize Operations

LCEQ 50153 LOG -- I IF .EQ., 1=>GRH, ELSE 0=>GRH.  
 LCEQ 141503 LOG -- SRV IF CC.EQ., 1=>A. ELSE 0=>A.  
 LCGE 50154 LOG -- I IF .GE., 1=>GRH, ELSE 0=>GRH.  
 LCGE 141504 LOG -- SRV IF CC.GE., 1=>A. ELSE 0=>A.  
 LCGT 50155 LOG -- I IF .GT., 1=>GRH, ELSE 0=>GRH.  
 LCGT 141505 LOG -- SRV IF CC.GT., 1=>A. ELSE 0=>A.  
 LCLE 50151 LOG -- I IF .LE., 1=>GRH, ELSE 0=>GRH.  
 LCLE 141501 LOG -- SRV IF CC.LE., 1=>A. ELSE 0=>A.  
 LCLT 50150 LOG -- I IF .LT., 1=>GRH, ELSE 0=>GRH.  
 LCLT 141500 LOG -- SRV IF CC.LT., 1=>A. ELSE 0=>A.  
 LCNE 50152 LOG -- I IF .NE., 1=>GRH, ELSE 0=>GRH.  
 LCNE 141502 LOG -- SRV IF CC.NE., 1=>A. ELSE 0=>A.  
 LEQ 50003 LOG - 4 I IF GR=0 TN 1=>GRH, ELSE 0=>GRH.  
 LEQ 140413 LOG - 4 SRV IF A.EQ.0, 1=>A. ELSE 0=>A.  
 LF 50016 LOG - 4 I LOGICIZE .F. 0=>GRH.  
 LF 140416 LOG - 5 SRV LOGICIZE FALSE. 0=>A.  
 LFEC 50023 LOG - 4 I IF FRS=0 TN1=>GRH, ELSE 0=>GRH.  
 LFEC 141113 LOG - 4 SRV IF FAC.EQ.0, 1=>A. ELSE 0=>A.  
 LFGE 50024 LOG - 4 I IF FRS>0 T 1=>GRH, ELSE 0=>GRH.  
 LFGE 141114 LOG - 4 SRV IF FAC.GE.0, 1=>A. ELSE 0=>A.  
 LFGT 50025 LOG - 4 I IF FRS>0 TN 1=>GRH, ELSE 0=>GRH.  
 LFGT 141115 LOG - 4 SRV IF FAC.GT.0, 1=>A. ELSE 0=>A.  
 LFLE 50021 LOG - 4 I IF FRS<0 T 1=>GRH, ELSE 0=>GRH.  
 LFLE 141111 LOG - 4 SRV IF FAC.LE.0, 1=>A. ELSE 0=>A.  
 LFLT 50020 LOG - 4 I IF FRS<0 T 1=>GRH, ELSE 0=>GRH.  
 LFLT 141110 LOG - 4 SRV IF FAC.LT.0, 1=>A. ELSE 0=>A.  
 LFNE 50022 LOG - 4 I IF FRS<0 T 1=>GRH, ELSE 0=>GRH.  
 LFNE 141112 LOG - 4 SRV IF FAC.NE.0, 1=>A. ELSE 0=>A.  
 LGE 50004 LOG - 4 I IF GR>0 TN 1=>GRH, ELSE 0=>GRH.  
 LGE 140414 LOG - 4 SRV IF A.GE.0, 1=>A. ELSE 0=>A.  
 LGT 50005 LOG - 4 I IF GR>0 TN 1=>GRH, ELSE 0=>GRH.  
 LGT 140415 LOG - 4 SRV IF A.GT.0, 1=>A. ELSE 0=>A.  
 LHEQ 50013 LOG - 4 I IF GRH=0 TN 1=>GRH, ELSE 0=>GRH.  
 LHGE 50004 LOG - 4 I IF GRH>0 T 1=>GRH, ELSE 0=>GRH.  
 LHGT 50015 LOG - 4 I IF GRH>0 TN 1=>GRH, ELSE 0=>GRH.  
 LHLE 50011 LOG - 4 I IF GRH<0 T 1=>GRH, ELSE 0=>GRH.  
 LHLT 50000 LOG - 4 I IF GR<0 TN 1=>GRH, ELSE 0=>GRH.  
 LHNE 50012 LOG - 4 I IF GRH<0 T 1=>GRH, ELSE 0=>GRH.  
 LLE 50001 LOG - 4 I IF GR<0 TN 1=>GRH, ELSE 0=>GRH.  
 LLE 140411 LOG - 4 SRV IF A.LE.0, 1=>A. ELSE 0=>A.  
 LLEQ 141513 LOG - 4 SRV IF L.EQ.0, 1=>A. ELSE 0=>A.  
 LLGE 140414 LOG - 4 SRV IF L.GE.0, 1=>A. ELSE 0=>A.  
 LLGT 141515 LOG - 4 SRV IF L.GT.0, 1=>A. ELSE 0=>A.  
 LLL 141511 LOG - 4 SRV IF L.LE.0, 1=>A. ELSE 0=>A.  
 LLLT 140410 LOG - 4 SRV IF L.LT.0, 1=>A. ELSE 0=>A.  
 LLNE 141512 LOG - 4 SRV IF L.NE.0, 1=>A. ELSE 0=>A.  
 LLT 50000 LOG - 4 I IF GR<0 TN 1=> GRH, ELSE 0=>GRH.  
 LLT 140410 LOG - 4 SRV IF A.LT.0, 1=>A. ELSE 0=>A.  
 LNE 50002 LOG - 4 I IF GR<>0 TN 1=>GRH, ELSE 0=>GRH.  
 LNE 140412 LOG - 4 SRV IF A.NE.0, 1=>A. ELSE 0=>A.  
 LT 140417 LOG - 5 SRV LOGICIZE TRUE. 1=>A.

Mode Operations

DBL 000007 MOD -- SRV ENTER DOUBLE-PREC MODE.  
 E16S 000011 MOD -- SRV ENTER P300 16K SECTORED MODE.

E32I 001010 MOD -- SRV ENTER P500 32I MODE.  
 E32R 001013 MOD -- SRVI ENTER P300 32K RELATIVE MODE.  
 E32S 000013 MOD -- SRVI ENTER P300 32K SECTORED MODE.  
 E64R 001011 MOD -- SRVI ENTER P300 64K RELATIVE MODE.  
 E64V 000010 MOD -- SRVI ENTER P400 MODE.  
 ESIM 000415 MOD -- SRVI\*ENTER STANDAGR INTERRUPT MODE.  
 EVIM 000417 MOD -- SRVI\*ENTER VECTORED INTERUPT MODE.  
 SGL 000005 MOD -- SRV ENTER SINGLE-PRECISION MODE.

Memory-reference Operations

ADD 06 MR 2 1 SRV ADD. (A) + [EA]16 => A.  
 ADL 06 03 MR 2 1 V (A,B)+[EA]32=>A,B. (NO HOLE).  
 AH 12 MR 2 1 I ADD HALFWD. RH+[EA]16=>RH.  
 ANA 03 MR -- SRV AND. (A) .AND. [EA]16 => A.  
 ANL 03 03 MR -- V (A,B) .AND. [EA]32 => A,B.  
 C 61 MR 1 1 I COMPARE R WITH [EA32].  
 CAS 11 MR 1 1 SRV SKIP 0,1,2 IF (A) >,< [EA]16.  
 CH 71 MR 1 1 I COMPARE RH WITH [EA]16.  
 CLS 11 03 MR 1 1 V SKIP 0,1,2 IF (A,B) >,< [EA]32.  
 CREP 10 02 MR -- R (P) => [(S)+1]16, EA=>P.  
 D 62 MR 3 1 I DIV. (R,R+1)/[EA]32=>R RMR=>R+1.  
 DAD 06(DP) MR 2 1 SR (A,B)+[EA]32 => A,B. (W/HOLE).  
 DFA 15 17 MR 3 1 I DBLE FLTG ADD. DFR+[EA]64=>DFR.  
 DFAD 06 02 MR 3 5 RV (DFAC) + [EA]64 => DFAC.  
 DFC 05 07 MR - 1 I DBLE FLTG COMP DRF TO [EA]64].  
 DFCS 11 02 MR 6 5 RV SKP 0,1,2 IF (DFAC) >,< [EA]64.  
 DFD 31,33 MR 3 1 I DOUBLE FLTG DIVIDE.  
 DFDV 17 02 MR 3 5 RV (DFAC) / [EA]64 => DFAC.  
 DFL 01 03 MR -- I DBLE FLTG LOAD. [EA]64=>DFR.  
 DFLD 02 02 MR -- RV [EA]64 => DFAC.  
 DFLX 15 02 MR -- V LD DFLT INDEX. 4\*[EA]16 => X.  
 DFM 25 27 MR 3 1 I DBL FLTG MULT. DFR/[EA]64=>DFR.  
 DFMP 16 02 MR 3 5 RV (DFAC) \* [EA]64 => DFAC.  
 DFS 21 23 MR 3 1 I DBLE FLTG SUB. DFR-[EA]64=>DFR.  
 DFBS 07 02 MR 3 5 RV (DFAC) - [EA]64 => DFAC.  
 DFST 11,13 MR 1 1 I DBLE FLTG STORE. DFR=>[EA]64].  
 DFST 04 02 MR -- RV (DFAC) => [EA]64.  
 DH 72 MR 3 1 I DIV HW. R/[EA]16=>RH RM=>RL(2).  
 DIV 17 MR 3 5 V (A,B)/[EA]16=>A,REM=>B. (NOHOLE)  
 DIV 17 MR 3 5 SR (A,B)/[EA]16=>A;REM=>B. (W/HOLE)  
 DLD 02(DP) MR -- SR DOUBLE LOAD. [EA]32 => A,B.  
 DM 60 MR - 1 I DECR. [EA]32]-1=>[EA]32].  
 DMH 70 MR - 1 I DECR HALDWD. [EA]16]-1=>[EA]16].  
 DSB 07(DP) MR 2 1 SR (A,B)-[EA]32 => A,B (W/HOLE).  
 DST 04(DP) MR -- SR DOUBLE STORE. (A,B) => [EA]32.  
 DVL 17 03 MR 3 5 V (A,B,E)/[EA]32=>A,B REM=>EH,EL.  
 EAA 01 01 MR -- R EFF. ADDR TO A-REG. EA => A.  
 EAL 01 01 MR -- V LOAD EFFECTIVE ADDR. EA => L.  
 EALB 42 MR -- I EFF ADDR TO LB. EA=>LB.  
 EALB 13 02 MR -- V EFF. ADDR TO LB. EA => LB.  
 EAR 63 MR -- I EFF ADDR (EA32) TO R.  
 EAXB 52 MR -- I EFF ADDR TO XB. EA=>XB.  
 EAXB 12 02 MR -- V EFF. ADDR TO XB. EA => XB.  
 EIO 34 MR - 2 I EXECUTE ADDR TO BASE REG.  
 EIO 14 01 MR - 7 V\* EXEC EA AS I/O INSTR.CCEQ=>SKP.  
 ENTR 01 03 MR -- R (S) => [(S)-EA]16, (S)-EA=>S.

ERA 05 MR -- SRV (A) .XOR. [EA]16 => A.  
 ERL 05 03 MR -- V (A,B) .XOR. [EA]32 => A,B.  
 FA 14,16 MR 3 1 I FLTG ADD. FR+[EA]32=>FR.  
 FAD 06 01 MR 3 5 RV (FAC) + [EA]32 => FAC.  
 FC 04,06 MR - 1 I FLTG COMPARE FR TO [EA]32].  
 FCS 11 01 MR 6 5 RV SKIP 0,1,2 IF (FAC) >,< [EA]32.  
 FD 30,32 MR 3 1 I FLTG DIV. -FR/[EA]32=>FR.  
 FDV 17 01 MR 3 5 RV (FAC) / [EA]32 => FAC.  
 FLD 02 01 MR -- RV FLOATING LOAD. [EA]32 => FAC.  
 FLX 15 01 MR -- RV 2\*[EA]16 => X.  
 FM 24,26 MR 3 1 I FLTG MULT. FR\*[EA]32=>FR.  
 FMP 16 01 MR 3 5 RV (FAC) \* [EA]32 => FAC.  
 FS 20,22 MR 3 1 I FLTG SUB. FR-[EA]32=>FR.  
 FSB 07 01 MR 3 5 RV (FAC) - [EA]32 => FAC.  
 FST 10,12 MR -- I FLTG STORE. FR=>[EA]32].  
 FST 04 01 MR 6 6 RV (FAC) => [EA]32.  
 I 41 MR -- I INTERCHANGE R WITH [EA]32].  
 IH 51 MR -- I INTERCHANGE RH WITH [EA]16].  
 IM 40 MR - 1 I INCR. [EA]32]+1=>[EA]32].  
 IMA 13 MR -- SRV EXCHANGE MEMORY AND A-REGISTER.  
 IMH 02 MR - 1 I INCR HALD WD> [EA]16]+1=>[EA]16].  
 IRS 10 MR -- SRV INC, REPLACE, AND SKIP IF ZERO.  
 JDX 15 02 MR -- R JUMP ON DECREMENTED X-R ZERO.  
 JEQ 02 03 MR -- R IF (A) .EQ. 0, EA => P.  
 JGE 07 03 MR -- R IF (A) .GE. 0, EA => P.  
 JGT 05 03 MR -- R IF (A) .GT. 0, EA => P.  
 JIX 15 03 MR -- R JUMP ON INCREMENTED X-REG ZERO.  
 JLE 04 03 MR -- R IF (A) .LE. 0, EA => P.  
 JLT 06 03 MR -- R IF (A) .LT. 0, EA => P.  
 JMP 51 MR -- I JUMP. EA=>RP.  
 JMP 01 MR -- SRV UNCOND JUMP. EA => PB,P.  
 JNE 03 03 MR -- R IF (A) .NE. 0, EA => P.  
 JSR 73 MR -- I RPL=>RH, EA32=>RP  
 JST 10 MR -- SRV (P) => [EA]16, EA+1 => P.  
 JSX 35 03 MR -- RV (P) => X, EA => P.  
 JSXB 61 MR -- I RP=>XB, EA=>RP.  
 JSXB 14 02 MR -- V (PB,P) => XB, EA => PB,P.  
 JSY 14 MR -- V (P) => Y, EA => P.  
 L 01 MR -- I LOAD. [EA]32=>R.  
 LDA 02 MR -- SRV LOAD A-REGISTER. [EA]16 => A.  
 LDAR 44 MR -- I LOAD ADDR REGISTER.  
 LDL 02 03 MR -- V LOAD LONG. [EA]32 => A,B.  
 LDLR 05 01 MR -- V LOAD LONG FROM RFILE LOC EA.  
 LDX 35 MR -- SRV LOAD X-REGISTER. [EA]16 => X.  
 LDY 35 01 MR -- V LOAD Y-REGISTER. [EA]16 => Y.  
 LH 11 MR -- I LOAD HALF WD. [EA]16=>RH.  
 LHL1 04 MR -- I SHIFTED 1 [EA]16] .LS. 1=>GRH.  
 LHL2 14 MR -- I SHIFTED 2 [EA]16] .LS. 2=>GRH.  
 M 42 MR 3 1 I MULT. R\*[EA]32=>(R,R+1).  
 MH 52 MR 3 1 I RH\*[EA]16=>R.  
 MIA 64 MR -- I MICROCODE EXECUTE A.  
 MIA 12 01 MR -- V MICROCODE ENTRANCE.  
 MIB 74 MR -- I MICROCODE EXECUTE B.  
 MIB 13 01 MR -- V MICROCODE ENTRANCE.  
 MPL 16 03 MR - 1 V (A,B) \* [EA]16 => A,B. (NOHOLE)  
 MPY 16 MR - 1 V (A) \* [EA]16 => A,B. (NOHOLE).  
 MPY 16 MR 3 1 SR (A) \* [EA]16 => A,B. (HOLE).

N	03	MR	--I	R .AND. [EA32]=>R.
NH	13	MR	--I	RH .AND. [EA16]=>RH.
O	23	MR	--I	R .OR. [EA32]=>R.
OH	33	MR	--I	RH .OR. [EA16]=>RH.
ORA	03 02	MR	--V	(A) .OR. [EA]16 => A.
PCL	41	MR	--I	PROCEDURE CALL.
PCL	10 02	MR	7 6 V	P-400 PROCEDURE CALL.
S	22	MR	2 1 I	SUB. R-[EA32]=>R.
SBL	07 03	MR	2 1 V	(A,B) - [EA]32 => A,B.(NOHOLE)
SH	32	MR	2 1 I	SUB HALF WD. RH-[EA16]=>RH.
SHA	15	MR	4 - I	ARITHMETIC SHIFT.
SHL	05	MR	4 - I	LOGICAL SHIFT.
ST	21	MR	--I	STORE. R=>[EA32].
STA	04	MR	--SRV	STORE A-REG. (A) => [EA]16.
STAR	54	MR	--I	STORE ADDRESSED REGISTER.
STH	31	MR	--I	STORE HALF WD. RH=>[EA16].
STL	04 03	MR	--V	STORE LONG. (A,B) => [EA]32.
STLR	03 01	MR	--V	STORE LONG INTO RFILE LOC EA.
STX	15	MR	--SRV	STORE X-REG. (X) => [EA]16.
STY	35 02	MR	--V	STORE Y-REG. (Y) => [EA]16.
SUB	07	MR	2 1 SRV	SUBTRACT. (A) - [EA]16 => A.
TM	44	MR	- 1 I	REST MEM. [EA32]::0=>CC.
X	43	MR	--I	EXC OR. R .XOR. [EA32]=>R.
XEC	01 02	MR	--RV	EXECUTE INSTRUCTION AT EA.
XEC	01 02	MR	--RV	EX EFF ADDR CONT AS THIS INST.
XH	52	MR	--I	RH .XOR. [EA16]=>RH.
ZM	43	MR	--I	ZERO MEM. 0=>[EA32].
ZMH	53	MR	--I	ZERO MEM. HALF WD. 0=>[EA16].

Miscellaneous Operations

A1A	141206	OPR	2 1 SRV	ADD 1 TO A REG. A+1=>A.
A2A	140304	OPR	2 1 SRV	ADD 2 TO A REGISTER. A+2=>A.
ABQ	50134	OPR	- 7 I	ADD TO BOTTOM OF QUEUE.
ACA	141216	OPR	2 1 SRV	ADD CBIT TO A REG. CBIT+A=>A.
ADDL	141000	OPR	2 1 SRV	ADD LINK TO L REGISTER.
ADLR	50014	OPR	- 7 I	ADD LINK TO GR.
ATQ	50135	OPR	- 7 I	ADD TO TOP OF QUEUE.
CAL	141050	OPR	--SRV	CLEAR A REG. LEFT BYTE.
CAR	141044	OPR	--SRV	CLEAR A REG. RIGHT BYTE.
CAZ	140214	OPR	1 1 SRV	SKIP 0,1,2 INST. IF A >,< 0.
CEA	000111	OPR	--SRV	A AS EA=>A. (USELESS IN 64V ).
CGT	50026	OPR	- 7 I	COMPUTED GOTO.
CHS	50040	OPR	--I	CHANGE SIGN -(1)=>GR(1).
CHS	140024	OPR	--SRV	CHANGE SIGN OF A REGISTER.
CMA	140401	OPR	--SRV	ONE'S COMPLEMENT A REGISTER.
CMH	50045	OPR	--I	COMP HALF REG. GRH=>GRH.
CMR	50044	OPR	--I	COMP REG. GR=>GR.
CR	50056	OPR	--I	CLEAR REG. 0 => GR.
CRA	140040	OPR	--SRV	CLEAR A REGISTER. 0=>A.
CRB	140015	OPR	--SRV	CLEAR B REGISTER. 0=>B.
CRBL	50062	OPR	--I	LEFT BYTE 0=>GRH(1-8).
CRBR	50063	OPR	--I	RIGHT BYTE 0=>GRH(9-16).
CRE	141404	OPR	--SRV	CLEAR E. 0=>E.
CRL	140010	OPR	--SRV	CLEAR L REGISTER. 0=>L.
CRLE	141410	OPR	--SRV	CLEAR L AND E. 0=>L, 0=>E.
CSA	140320	OPR	5 - SRV	CPY SIGN OF A. A1=>CBIT,0=>A1.

CSR	50041	OPR	--I	COPY & SAVE SIGN. 1=>C,0=>GRL.
DH1	50130	OPR	2 1 I	DECR HALF REG BY 1. GRH-1=>GRH.
DH2	50131	OPR	2 1 I	DECR HALF REG BY 2. GRH-2=>GRH.
DR1	50124	OPR	2 1 I	DECR REG BY 1. GR-1=>GR.
DR2	50125	OPR	2 1 I	DECR REG BY 2. GR-2=>GR.
DRX	140210	OPR	--SRV	DECREMENT X AND SKIP IF 0.
IAB	000201	OPR	--SRV	EXCHANGE A AND B A=>B & B=>A.
ICA	141340	OPR	--SRV	INTERCHANGE BYTES OF A REG.
ICBL	50065	OPR	--I	GRH(1-8)=>GRH(9-16), 0=>R.
ICBR	50066	OPR	--I	GRH(9-16)=>GRH(1-8), 0=>
ICHL	50060	OPR	--I	GRH=>GRL, 0=>GRH.
ICHR	50061	OPR	--I	GRL=>GRH, 0=>GRL.
ICL	141140	OPR	--SRV	EXCHANGE BYTES OF A, CLR LEFT.
ICR	141240	OPR	--SRV	EXCHANGE BYTES OF A, CLR RIGHT.
IH1	50126	OPR	2 1 I	GRH+1=>GRH.
IH2	50127	OPR	2 1 I	GRH+2=>GRH.
ILE	141414	OPR	--SRV	EXCHANGE L AND E. L=>E & E=>L.
INK	50070	OPR	--I	MOVE KEYS TO REG KEYS.
INK	000043	OPR	--SRV	INPUT P-300 KEYS INTO A REG.
IR1	50122	OPR	2 1 I	INCR REG BY 1. GR+1=>GR.
IR2	50123	OPR	2 1 I	INCR REG BY 2. GR+2=>GR.
IRB	50062	OPR	--I	BYTES GRH(1-8)=>GRH(9-16)
IRH	50057	OPR	--I	GRH=>GRL, GRL=>GRH.
IRX	140114	OPR	--SRV	INCREMENT X AND SKIP IF 0.
NOP	000001	OPR	--SRV	NO OPERATION.
NRM	000101	OPR	--SRV	NORMALIZE A,B AS ON P-300.
OTK	50071	OPR	7 S I	SET KEYS FROM REGISTER
OTK	000405	OPR	7 6 SRV	OUTPUT A TO 300 KEYS, SHFT CTR.
PID	50052	OPR	--I	GR=>GRN, (1)=>GR(2-32).
PID	000211	OPR	--SRV	SHORT INT TO DP INT W/HOLE.
PIDA	000115	OPR	--SRV	SHORT TO LONG INT CONV. A=>L.
PIDH	50053	OPR	--I	GRH=>GRL,GRH(1)=>GRH(2-16).
PIDL	000305	OPR	--SRV	CONVERT LONG INT TO 64 BIT INT.
PIM	50050	OPR	2 1 I	POS REG AFTER INT MULTIPLY.
PIM	000205	OPR	--SRV	DP INT WITH HOLE TO SHORT INT.
PIMA	000015	OPR	3 5 SRV	L=>A. IEX ON PREC LOSS.
PIMH	50051	OPR	2 1 I	POS HALF REG AFTER INT MULT.
PIML	000301	OPR	3 5 SRV	64BIT INT TO LONG INT.(L,E)=>L.
RBQ	50133	OPR	- 7 I	REMOVE FROM BOTTOM OF QUEUE.
RCB	140200	OPR	5 - SRV	RESET CBIT. 0=>CBIT.
RTN	000105	OPR	--SRV	RETURN FROM P-300 RECUR PROC.
RTQ	50132	OPR	- 7 I	REMOVE FROM TOP OF QUEUE.
S1A	140110	OPR	2 1 SRV	SUB 1 FROM A REGISTER. A-1=>A.
S2A	140310	OPR	2 1 SRV	SUB 2 FROM A REGISTER. A-2=>A.
SCA	000041	OPR	--SRV	LOAD P-300 SHFT CTR INTO A REG.
SCB	140600	OPR	5 - SRV	SET CBIT. 1=>CBIT.
SHL1	50076	OPR	4 1 I	GRH .LS. 1 => GRH.
SHL2	50077	OPR	4 1 I	GRH .LS. 2 => GRH.
SHR1	50120	OPR	4 1 I	GRH .RS. 1 => GRH.
SHR2	50121	OPR	4 1 I	GRH .RS. 2 => GRH.
SL1	50072	OPR	4 1 I	GR .LS. 1 => GR.
SL2	50073	OPR	4 1 I	GR .LS. 2 => GR.
SR1	50074	OPR	4 1 I	GR .RS. 1 => GR.
SR2	50075	OPR	4 1 I	GR .RS. 2 => GR.
SSM	50042	OPR	--I	SET SIGN. MINUS 1=>(1).
SSM	140500	OPR	--SRV	SET SIGN OF A MINUS. 1=>A1.
SSP	50043	OPR	--I	SET SIGN. PLUS 0=>(1).



SSP 140100 OPR - - SRV SET SIGN OF A PLUS. 0=>ABIT1.  
 STCD 50137 OPR - 7 I GR+1=[EA16].  
 STCH 50136 OPR - 7 I GRL=[EA16].  
 STEX 50027 OPR - 7 I STACK EXTEND.  
 STEX 001315 OPR 6 5 SRV STK EXTEND. L REG HAS EXTENT.  
 TAB 140314 OPR - - SRV TRANSFER A TO B REG. A=>B.  
 TAK 001015 OPR 7 6 SRV TRANSFER A TO KEYS.  
 TAX 140504 OPR - - SRV TRANS A REG TO X REG. A=>X.  
 TAY 140505 OPR - - SRV TRANS A REG TO Y REG. A=>Y.  
 TBA 140604 OPR - - SRV TRANS B REG TO A REG. B=>A.  
 TC 50047 OPR 3 1 I -GR+1=>GR.  
 TCA 140407 OPR 2 1 SRV TWO'S COMPLEMENT A. -A=>A.  
 TCH 50047 OPR 3 1 I -GRH+1=>GRH.  
 TCL 141210 OPR 2 1 SRV TWO'S COMPLEMENT L. -L=>L.  
 TKA 001005 OPR - - SRV TRANSFER KEYS TO A.  
 TSTQ 50104 OPR - 7 I TEST QUEUE.  
 TXA 141034 OPR - - SRV TRANS X REG TO A REG. X=>A.  
 TYA 141124 OPR - - SRV TRANS Y REG TO A REG. Y=>A.  
 XCA 140104 OPR - - SRV EXCHG AND CLR A. A=>B, 0=>A.  
 XCB 140204 OPR - - SRV EXCHG AND CLR B. B=>A, 0=>B.  
 xxx 140014 OPR - - SRV OBSOLETE. CLRS B, LSW OF DFAC.

Programmed I/O Operations

INA 54 PIO - - SR\* INPUT TO A-REGISTER.  
 OCP 14 PIO - - SR\* OUTPUT CONTROL PULSE.  
 OTA 74 PIO - - SR\* OUTPUT FROM A-REGISTER.  
 SKS 34 PIO - - SR SKIP IF CONDITION SET.  
 SMK 170020 PIO - - SR\* SET INTERRUPT MASKS.

Shift Operations

ALL 0414XX SH 4 5 SRV A LEFT LOGICAL.  
 ALR 0416XX SH 4 5 SRV A LEFT ROTATE.  
 ALS 0415XX SH 4 5 SRV A LEFT SHIFT (SHORT INT ARITH).  
 ARL 0404XX SH 4 5 SRV A RIGHT LOGICAL.  
 ARR 0406XX SH 4 5 SRV A RIGHT ROTATE.  
 ARS 0405XX SH 4 5 SRV A RIGHT SHIFT (SHORT ARITH).  
 LLL 0410XX SH 4 5 SRV LONG LEFT LOGICAL.  
 LLR 0412XX SH 4 5 SRV LONG LEFT ROTATE.  
 LLS 0411XX SH 4 5 SRV LNG LSFT 64V=>LNG INT,ELSE HOLE  
 LRL 0400XX SH 4 5 SRV LONG RIGHT LOGICAL.  
 LRR 0402XX SH 4 5 SRV LONG RIGHT ROTATE.  
 LRS 0401XX SH 4 5 SRV LNG RSFT.64V=LNG INT,ELSE HOLE.

Skip Operations

SAR 10026X SKP - - SRV SKIP IF A REG. BIT N RESET.  
 SAS 101260 SKP - - SRV SKIP IF A REG. BIT N SET.  
 SGT 100220 SKP - - SRV SKIP IF A REG. .GT. 0.  
 SKP 100000 SKP - - SRV SKIP ONE WORD.  
 SLE 101220 SKP - - SRV SKIP IF A REG. .LE. 0.  
 SLN 101100 SKP - - SRV SKIP IF A REG. BIT 16 SET.  
 SLZ 100100 SKP - - SRV SKIP IF A REG. BIT 16 .EQ. 0.  
 SMCR 100200 SKP - - SRV SKIP IF MACHINE CHECK RESET.  
 SMCS 101200 SKP - - SRV SKIP IF MACHINE CHECK SET.  
 SMI 101400 SKP - - SRV SKIP IF A REG. .LT. 0.

SNR 10024X SKP - - SRV\* SKIP IF SENSE SWITCH N RESET.  
 SNS 101240 SKP - - SRV\* SKIP IF SENSE SWITCH N SET.  
 SNZ 101040 SKP - - SRV SKIP IF A REG. NE. 0.  
 SPL 100400 SKP - - SRV SKIP IF A REG. .GE. 0.  
 SR1 100020 SKP - - SRV\* SKIP IF SENSE SWITCH 1 RESET.  
 SR2 100010 SKP - - SRV\* SKIP IF SENSE SWITCH 2 RESET.  
 SR3 100004 SKP - - SRV\* SKIP IF SENSE SWITCH 3 RESET.  
 SR4 100002 SKP - - SRV\* SKIP IF SENSE SWITCH 4 RESET.  
 SRC 100001 SKP - - SRV SKIP IF CBIT RESET.  
 SS1 101020 SKP - - SRV\* SKIP IF SENSE SWITCH 1 SET.  
 SS2 101010 SKP - - SRV\* SKIP IF SENSE SWITCH 2 SET.  
 SS3 101004 SKP - - SRV\* SKIP IF SENSE SWITCH 3 SET.  
 SS4 101002 SKP - - SRV\* SKIP IF SENSE SWITCH 4 SET.  
 SSC 101001 SKP - - SRV SKIP IF CBIT SET.  
 SSR 100036 SKP - - SRV\* SKIP IF SSWI 1,2,3 AND 4 RESET.  
 SSS 101036 SKP - - SRV\* SKIP IF SSWI 1,2,3 AND 4 SET.  
 SZE 100040 SKP - - SRV SKIP IF A REG .EQ. 0.

Virtual-memory Operations

EPMJ 000217 VM - - SR ENT PAGE MODE AND JUMP (P300).  
 EPMX 000237 VM - - SR ENT PAG MOD & JMP TO MICROCODE.  
 ERMJ 000701 VM - - SR ENTER RESTR MODE & JUMP (P300).  
 ERMX 000721 VM - - SR RESTR MOD & JUMP TO MICROCODE.  
 EVMJ 000703 VM - - SR ENT VIRT MODE AND JUMP (P300).  
 EVMX 000723 VM - - SR VIRT MOD & JUMP TO MICROCODE.  
 LPMJ 000215 VM - - SR LEAVE PAGE MODE & JUMP (P300).  
 LPMX 000235 VM - - SR LVE PAG MOD & JMP TO MICROCODE.

6 OPERATIONAL PROCEDURES

BOOT TERMINAL SPEED SELECTION

BOOT PROCEDURES

Master clear, select LOAD, raise data switches 1-16 as follows ('-' => don't care):

1	16	
A AAA AAA AAA ---	000	Start at 'AAAAAAAAA000000
S SSS SSS DDP ---	001	ASR Paper Tape
S SSS SSS DDP ---	010	High Speed Paper Tape
H HHH HHH H-- --0	011	Option B FHD
H HHH HHH H-- 0-0	011	Option B' FHD, DA='21
H HHH HHH H-- 1-0	011	Option B' FHD, DA='23
H HHH HHH H-- 0-0	100	Option B Upper MHD
H HHH HHH H-- 1-0	100	Option B Lower MHD
H HHH HHH H-0	001 100	Option B' Upper MHD, DA='21
H HHH HHH H-0	101 100	Option B' Lower MHD, DA='21
H HHH HHH H-0	011 100	Option B' Upper MHD, DA='23
H HHH HHH H-0	111 100	Option B' Lower MHD, DA='23
H HHH HHH H-1	01 100	Storage Module, DA='26
H HHH HHH H-1	11 100	Storage Module, DA='27
N NNN NNN RRS CT-	101	Magtape
- --- --- --- ---	110	Diskette (Floppy)
- --- --- --- ---	111	Unused

- A..A Addr/'100 to start at
- S..S Sector for boot loader relocation
- DD Displacement for boot loader relocation
- P 1 => suppress auto-start
- C 1 => halt to allow baud rate change
- H..H DOS select:
  - 00000000 Highest that will fit
  - 010----- \*DOS16
  - 011----- \*DOS64
  - 100----- \*DOS32
- N..N File number to load (0=>prompts)
- RR Relocation of boot program to ending address of:
  - 00 - end of physical memory
  - 01 - 16K
  - 10 - 32K
  - 11 - 48K
- T
  - 0 - 9-track
  - 1 - 7-track

Parameter 4 (B Register)

- '110 for 110 BAUD
- '1010 for 300 BAUD
- '2010 for 1200 BAUD
- '3410 for 9600 BAUD

Parameter 5 (X Register)

- '27 for 110 BAUD
- '76 for 300 BAUD
- '373 for 1200 BAUD
- '3735 for 9600 BAUD

Parameter 6 (Keys)

- '740\*\* for 110 BAUD
- '340\*\* for 1200 - 9600 BAUD

\*\* = number of delays after .CR.

TYPICAL SWITCH SETTINGS FOR DISK BOOTS

DVNO	Switches
0	--0004
1	--0044
10	--0003
20	--0006
30	--0014
31	--0054
40	--0014
---050	--0014
---051	--0054
---250	--0034
---251	--0074
---460	--0114

Hit START to initiate load sequence. Select RUN after load has started.

COLD START (PRIMOS IV,V)

- 1) Boot in PRIMOS II (see 'BOOT' above), startup disk containing UFD with PRIMOS IV (typically PR4.64, PR4.16, PR4L16). Attach to UFD containing PRIMOS IV.
- 2) Type 'R PRIMOS'. If there is a C\_PRMO file in the current CMDNC0 the configuration will be taken from that file. Else enter CONFIG command:

CONFIG -- SET SYSTEM CONFIGURATION PARAMETERS

```
CONFIG [<node>] <ntusr> <pagdev> <comdev>
[<memsiz>] [<altdev>] [<namlc>] [<npusr>]
[<nrusr>] [<slmcon>]
```

-or-

```
CONFIG -DATA <config-filename>
```

Commands for latter form documented in PE-T-412.

Cold start command only.

- 3) If PRIMOS IV halts at 1507 (1510 in address lights), it has encountered bad memory during initial memory scan (see HALTS). Hit start to map out the bad page and continue.
- 4) After the introductory messages, enter the date and time:

```
SEtime -<mmddy> -<hhmm>
```

Users may now log into the system.

HALTSON MACHINE HALT:

- 1) Select STOP/STEP mode (rotary switch).
- 2) Place ADDRESS/DATA switch on ADDRESS and note the address displayed in lights. To determine the segment number of the halt, select FETCH, depress DATA CLEAR, set data switches to '14, raise switches 1 and 4, depress START, note displayed segment number.
- 3) Refer to latest load map of PRIMOS IV and/or the following list of load map entries to determine subsequent actions. (NOTE: the address displayed at the halt will always be one location higher than the corresponding halt location address.)

PRIMOS IV HALT LOCATIONS

(Addresses marked with a '+' are those most likely to change when PRIMOS is reloaded. The letters in parentheses refer to subsequent actions that should be taken and are described following the list.)

```
AMLCI_ +6/12714 Bad AMLC Interrupt. (D,W)
BDMEM_ 4/1507 Parity error during cold start. (M,C)
BOOT0_ +6/10634 Halt after SHUTDN ALL command. (C)
IFLTB_ +4/115204 Fault in interrupt handler. (D,C)
INTRT_ +4/115357 Too many PRTNs. (D,C)
IPAGE_ +4/115321 Page flt in interrupt process. (D,C)
MCHK_ 4/305 Machine check. (D,W)
MEMH2_ 4/317 Halt after mapout of bad page. (W*)
MEMPA_ 4/276 Uncorrected mem parity error. (M,W*)
MMOD_ 4/315 Missing memory module. (D,C)
PAGFB_ 6/3577 Illegal page fault. (D,C)
REFL0_ 6/3663 Illegal FLEX, UII, PSU. (D,C)
RMCFO_ 6/3545 Illegal restricted mode fault. (D,C)
SVCF0_ 6/3760 Illegal SVC. (D,C)
WARMH_ 4/1022 Can't warm start (C)
Any other location. (D,C)
```

ACTIONS TO TAKE AFTER HALT CONDITION IS DETERMINED

- D -- Note down register set (if RSAVEPTR.NE.0) and take a tape dump.
- C -- Cold start.
- W -- Warm start.
- W\* -- Warm start is possible only if a user page got the parity error.
- M -- Map out bad page.

MEMORY PARITY ERRORS

On halt (at MEMPA\_): X = user number, A = physical page number, B = word number. Hit start to automatically map out bad page.

c(MMAP+PPN) --> HMAP for page (< '6200 => supervisor page).

c(PTUSEG+(PHMAP.RS.6-'40)=user number

Manual mapout: MMAP+PPN<-- -1, HMAP <-- 0

MEMORY/REGISTER DISPLAY

- 1) Select FETCH Y on rotary switch (this stops the machine).
- 2) Select ADDRESS on ADDRESS/DATA toggle, hit DATA CLEAR, and depress address or register number in switches as shown below.
- 3) After switches depressed/set, select DATA and depress START. The lights now show contents of selected location on register.

For memory references, raised switches are in top row, dialed switches in bottom row. 'H/L' selects high (raised) or low (middle position) side of register.

300 REGS: 

1	12	16
0 000 000 000 0RR RRR		
REG #		

MAPPED MEMORY: 

1	5<--SEG NUM-->	16
0 000 SSS SSS SSS SSS		
W WWW WWW WWW WWW WWW		
<--WORD NUMBER----->		

ABSOLUTE MEMORY: 

1	4	11	16
0 001 000 000 WWW WWW			
W WWW WWW WWW WWW WWW			
<--WORD NUMBER----->			

CURR. REG. SET: 

1	4	12	16
1 00H/L 000 000 0RR RRR			
REG #			

ABSOLUTE REG.: 

1	2	4	11	16
1 10H/L 000 00R RRR RRR				
REG #				

Virtual addresses (but not absolute memory or registers) can be displayed while PRIMOS IV is running. Place ADDRESS/DATA toggle on DATA and enter segment number/word number as follows ('D' => depress switch):

CLEAR SEGNO: 

1	2	16
D D00 000 000 000 000		

DEPRESS SEGNO: 

1	5	16
D 000 DDD DDD DDD DDD		
<---SEG NUM--->		

RAISE WRDNO: 

1	16
W WWW WWW WWW WWW WWW	
<---WORD NUMBER--->	

NOTE: If referenced page is not in memory, zeroes will be displayed (i.e., page faults are ignored).

MEMORY SCAN

- 1) Master clear, load '777 into the PC (location 7), select RUN, place ADDRESS/DATA switch on DATA, data switches in neutral position, hit START. (PRIMOS IV must be in memory.)
- 2) When the data lights change, a bad memory location has been found. The display with all switches neutral is the word number within the page. To display the physical page number, raise switch 15. To display the contents of the location, raise switch 14 (drop switch 15).
- 3) To continue the memory scan, type any character on the system console (ASR).
- 4) The scan will halt when the end of memory is reached. Hitting START will restart the scan.

TAPE DUMP

- 1) Mount non-write-protected tape on first magtape controller, drive 1. Ensure only one unit dialed to 1. Tape should be at load point and online. (PRIMOS IV or V must be in memory.)
- 2) Master clear, set PC (location 7) from '1000 to '776, select RUN, hit START.
- 3) When done, the tape dump program will rewind the tape and halt. Perform WARM or COLD START as appropriate.

WARM START

Master clear, select RUN, hit START twice.

NOTE: Warm start is possible only on CPUs with REV 10 microcode or later, otherwise an immediate halt at WARMH\_ will occur.

7 PERIPHERAL I/OADDRESSES

00	Polling	40	PRIMAD (AIS)
01	Paper Tape Reader	41	Digital Input 1
02	Paper Tape Punch	42	Digital Input 2
03	Unit Record Controller 1	43	Digital Output 1
04	TTY	44	Digital Output 2
05	Unit Record Controller 2	45	Analog Output
06	Interproc. Channel (IPC)	46	Computer Prod. IF
07	--	47	CAMAC Interface
10	--	50	HSSMLC 1
11	--	51	HSSMLC 2
12	Diskette	52	AMLC 3
13	Magtape Controller 2	53	AMLC 2
14	Magtape Controller 1	54	AMLC 1
15	RIOX I/O Bus Switch	55	MACI Autocall
16	RIOX MPS	56	SMLC
17	--	57	--
20	Panel, Real Time Clock	60	Gen. Purp. IF Board
21	Disk (4002 Controller)	61	Ringnet Controller
22	Fixed Head Disk	62	GPIB
23	30 Megabyte Disk	63	GPIB
24	Writeable Control Store	64	GPIB
25	Moveable Head Disk	65	GPIB
26	Storage Module 1	66	GPIB
27	Storage Module 2	67	GPIB
30	IOC 1 (Parallel I/O)	70	GPIB Test
31	IOC 2	71	ADAGE GP/400 IF
32	--	72	--
33	VERSATEC	73	--
34	VERSATEC	74	--
35	AMLC 4	75	--
36	ELFBUS Controller 1	76	--
37	ELFBUS Controller 2	77	I/O Bus Test

AMLCOTA 01 -- Set Line Configuration

1-4	170000	Line Number
5	004000	Unused
6	002000	Data Set Control
7	001000	Loop Line
8-10	000700	Line Speed: xxx0xx - 110 BAUD xxx1xx - 134.5 xxx2xx - 300 xxx3xx - 1200 xxx4xx - Pgmed Clock xxx5xx - Pgmed Clock xxx6xx - Pgmed Clock xxx7xx - Pgmed Clock
11	000040	Unused
12	000020	0 => 1 Stop Bit, 1 => 2
13	000010	1 => Disable Parity
14	000004	0 => Odd Parity, 1 => Even
15-16	000003	Char Len: xxxxx0 - 5 Bits xxxxx1 - 7 Bits xxxxx2 - 6 Bits xxxxx3 - 8 Bits

OTA 02 -- Set Line Control


1-4	170000	Line Number
5-10	007700	Unused
11	000040	1 => Enable Char Time Interrupt
12	000020	Unused
13	000010	1 => Enable Transmit
14	000004	1 => Enable Echo Back
15	000002	1 => Receive Off, Report Break
16	000001	1 => Enable Receive

ASR

BAUD	OPTION-A	SOC CTL 1	SOC CTL 2
110	110	27	740**
300	1010	76	340**
1200	2010	373	340**
9600	3410	3735	340**

\*\* = number of delays used by BOOT, PRIMOS

DISK CONTROLLERS



Disk Channel Program Definitions

Mnem	Op Code	Execution Time (u-s)	Order	Fields
DHLT	0	6	Halt	
SFORM	2		Format	Rec Size 13-16 Track Addr 23-32 # Records 33-40 Head Addr 44-48
SSEEK	3	7.5	Seek	Restore 17 Clear 18 Track Addr 23-32
DSEL	4	7.5	Select	MHD 29-32
SREAD	5		Read	Rec Size 13-16 Offset 17-20 SR 21 Track Addr 23-32 Rec Addr 33-40 Head Addr 44-48
SWRITE	6			Rec Size 13-16 Track Addr 23-32 Rec Addr 33-40 Head Addr 44-48
DSTALL	7	210	Stall	
DSTAT	9	9	Input Status	Mem Addr 17-32
SSTOR	A	9	Store	Diag Addr 16 Mem Addr 17-32
DOAR	B	9	Input OAR	Mem Addr 16
SLOAD	C	9	Load	Diag Addr 16 Mem Addr 17-32
SDMA	D	6	Channel Address	Chain 13-16 Chan Addr 17-32
DINT	E	6+CPU	Interrupt	Vect Addr 17-32
DTRAN	F	6	Transfer	Trans Addr 17-32

bit 5 = 0, do not execute inst if:  
bit 5 = 1, execute inst if:

set bit	Description
6	No function but reserved for "selected diskfile is write protected."
6	Last read or write record inst caused a DMA overrun, check error, controller parity error or header check failure (status word bits 2,4,5, or 6 set).
8	Selected MHD is seeking.
9	Selected diskfile has an error condition (status word bits 14, 15, or 16 are set).
10	For dual port operation only. Selected diskfile is busy servicing the "other" controller.

Disk Device Numbers (DVNO)

1-4	170000	(Offset to First Head)/2
5-8	007400	(Number of Heads)/2
9	000200	0=>Controller 1, 1=>Controller 2
10-13	000170	Type of Controller:
	xxx00x	4000 MHD
	xxx01x	4000 FHD
	xxx02x	Diskette
	xxx03x	4003 8 Sectors/Track
	xxx04x	4003 FHD
	xxx05x	4003 32 Sectors/Track
	xxx06x	4004 Storage Module
	xxx07x-xxx17x	Undefined
14-15	000006	Unit (Inc. bit 16 for Diskette)
16	000001	Diskette: Low Bit of Unit
		4003 Controller: 0 => Top, 1 => Bottom
		Storage Module: LSB of Number Heads

Disk ErrorsOption B (4000 Controller)

```

-- 177777 Bad Record Identifier
-- 177776 Device Not Ready
1  100000 Data Transfer Complete
2  040000 R/W Past End of Record
3  020000 Unused
4  010000 Stack Available
5  004000 Seek Complete OK
6  002000 Write Protect Violation
7  001000 Not Ready
8  000400 Command Error
9  000200 Checksum Error
10 000100 DMX Overrun
11 000040 Stack Overflow
12-15 000036 Unused
16 000001 Not Ready (Software)
-- 000000 Redundant Int. (Warm Start)

```

Option B-Prime (4001 Controller)

```

-- 177777 Bad Record Identifier
-- 177776 Device Not Ready
-- 177775 Memory Parity Error During DMX
1  100000 Bit 1 Always Set
2  040000 DMX Overrun
3  020000 Write Protect Status
4  010000 Checksum Error
5-9 007600 Unused
10 000100 Unit 1 Seeking
11 000040 Unit 2 Seeking
12 000020 Unit 3 Seeking
13 000010 Unit 4 Seeking
14 000004 Illegal Seek
15 000002 Malfunction Detected
16 000001 Not Ready (Software)
-- 000000 Redundant Int. (Warm Start)

```

Diskette Controller

```

-- 177777 Bad Record Identifier
-- 177776 Device Not Ready
1  100000 Normal End of Instruction
2  040000 Sector Not Found
3  020000 Checksum Error on Sector ID
4  010000 Track Error (head misposition)
5  004000 Bad CTA or Not Ready
6  002000 Deleted Data Mark Read
7  001000 DMX Overrun
8  000400 Chksum err, Write Prot. Violation,
Inoperable on Write or Format
9-15 000376 Unused
16 000001 Not Ready
-- 000000 Redundant Int. (Warm Start)

```

Storage Module (4004 Controller)

```

-- 177777 Bad Record Identifier
-- 177776 Device Not Ready
-- 177775 Memory Parity Error During DMX
1  100000 Bit 1 Always On
2  040000 DMA Overrun
3  020000 Write Protect
4  010000 Read Check
5  004000 Data Parity Error
6  002000 Header Check
7-10 001700 Unused
11 000040 Busy (Dual Port Only)
12 000020 Unused
13 000010 Seeking
14 000004 Illegal Seek
15 000002 Select Error
16 000001 Not Ready
-- 000000 Redundant Int. (Warm Start)

```

Disk Sizes

\*\*\* Disk types and sizes \*\*\*  
to be supplied at next update



DMX CONTROL WORDSDMA

	1	12	13
0	-WORD COUNT 0000		
1	STARTING ADDRESS		

OTA '14dd:  $\overline{N}$   $\overline{NNN}$   $\overline{0}$  CHAN ADDRESS

NNNN = Number of channels - 1.

DMC

	1	16
0	START ADDRESS	
1	END ADDRESS	

OTA '14dd:  $\overline{N}$   $\overline{NNN}$   $\overline{1}$  CHAN ADDRESS

NNNN = Number channels - 1.

DMQ

	1	16	
0	T	TTT	(Read Pointer)
1	B	BBB	(Write pointer)
2	0	PPP	(H. O. bits phy addr)
3	M	MMM	(mask)

mask = len-1 of Q  
 len = 2\*\*K, 4 < K < 10  
 (Queue must be on 2\*\*K boundary.)

INPUT: End of Range if no room.  
 OUTPUT: EOR if empty (not w/last entry).

DMT

Device Defined.

MAGTAPECommand Bit Definitions

1	100000	Select Transport (bits 9-12)
2	040000	0=>File Operation, 1=>Record Op
3	020000	0=>Read/Write Op, 1=>Spacing Op
4	010000	1=>9-Track Read and Correct
5	004000	0=>Binary, 1=>BCD (7-track only)
6	002000	0=>7-Track Transport, 1=>9-Track
7	001000	Unused
8	000400	1=>2 Characters per Word
9	000200	1=>Forward Motion (bits 10,11=0)
10	000100	1=>Reverse Motion (bits 9,11,12=0)
11	000040	1=>Rewind (bits 9,10,12=0)
12	000020	1=>Write Order
13	000010	Select Transport 0
14	000004	Select Transport 1
15	000002	Select Transport 2
16	000001	Select Transport 3

Magtape Commands

100000	Select Transport (7 and 9 track)
000040	Rewind to BOT (7 and 9 track)
022100	Backspace File Mark, 9-track
020100	Backspace File Mark, 7-track
062100	Backspace Record, 9-track
060100	Backspace Record, 7-track
022200	Write File Mark, 9-track
020200	Write File Mark, 7-track
062200	Forward Space Record, 9-track
060200	Forward Space Record, 7-track
022200	Forward Space File Mark, 9-track
020200	Forward Space File Mark, 7-track
042200	Write Record One Char/Word, 9-track
042600	Write Record Two Char/Word, 9-track
042200	Read Record One Char/Word, 9-track
042600	Read Record Two Char/Word, 9-track
052200	Read/Correct Record One Char/Word, 9-track
052600	Read/Correct Record Two Char/Word, 9-track
040200	Write Binary Record One Char/Word, 7-track
040600	Write Binary Record Two Char/Word, 7-track
044200	Write BCD Record One Char/Word, 7-track
044600	Write BCD Record Two Char/Word, 7-track
040200	Read Binary Record One Char/Word, 7-track
040600	Read Binary Record Two Char/Word, 7-track
044200	Read BCD Record One Char/Word, 7-track
044600	Read BCD Record Two Char/Word, 7-track

Magtape Status

1	100000	Parity Error
2	040000	Runaway Tape
3	020000	CRC Error
4	010000	LRC Error
5	004000	Low DMX Range
6	002000	Permanent Error
7	001000	Read-After-Write (RAW) Error
8	000400	File Mark Detected
9	000200	Ready
10	000100	Online
11	000040	End of Tape Detected
12	000020	Rewinding
13	000010	Beginning of Tape (at Load Point)
14	000004	Tape is Write-Protected
15	000002	DMX Overrun
16	000001	Rewind Complete

(000300 or 000304 - Normal Completion)

Standard Functions

FF OCP	SKS	INA	OTA
00	Ready	Data Reg	
01	Not Busy		
02			
03			
04	Not Interrupting		
05			
06			
07			
10			
11		Input ID	
12	Normal Mode		
13	Diagnostic Mode		
14	Ack Interrupt		DMX Channel
15	Set Int Mask		
16	Reset Int Mask		Int Vect Addr
17	Initialize		

PROGRAMMED I/O (PIO)OCP -- Output Control Pulse

03FFDD FF=Function, DD=Device Address

SKS -- Skip on Condition

13CCDD CC=Condition, DD=Device Address

INA -- Input to A-Register

07FFDD FF=Function, DD=Device Address

No skip for device '20  
Always skips if status register input.

OTA -- Output from A-Register

17FFDD FF=Function, DD=Device Address

No skip if device '20.

8 PRIMOS IVABORT FLAGS

PCB+4, ABSAVE at 6000/10

100000	MINALM	ONE MINUTE ABORT FLAG
040000	SMLALM	SIMC ALARM
020000	NETALM	NETWORK ALARM
004000	WRMALM	WARM START ALARM
000200	MT1ALM	MTDONE, CONTROLLER 1
000100	MT2ALM	MTDONE, CONTROLLER 2
000020	LOGALM	FORCED LOGOUT ALARM
000010	DISALM	DISCONNECT ALARM
000004	TMOALM	TIMEOUT ALARM
000002	QUTALM	QUIT ALARM
000001	TSEALM	TIME SLICE END (FIRMWARE)

COMMONS

\*\*\* List of COMMONS \*\*\*  
to be supplied at next update

ERRVEC

In PUDCOM at 6000/106

ERRVEC(1)	ALTVAL
ERRVEC(2)	ALTVAL(2)
ERRVEC(3)	NAME (0=>NO NAME)
ERRVEC(4)	"
ERRVEC(5)	"
ERRVEC(6)	"
ERRVEC(7)	WORD NUMBER OF MSG OR 0
ERRVEC(8)	LENGTH (IN CHARS) OF MSG
ERRVEC(9)	SEGMENT NUMBER OF MSG

V-mode error messages saved in ERRVEC:

<u>MESSAGE</u>	<u>ERRVEC(1-2)</u>
ACCESS VIOLATION	PB of instr causing violation
ILLEGAL PAGE REF	32-bit ptr into ill page
ILLEGAL SEGNO	32-bit ptr into ill seg
POINTER FAULT	PB of instr causing fault
NO AVAIL SEGMENTS	32-bit ptr to seg that system attempted to create
UNDEFINED GATE	32-bit ptr into gate seg

FIGCOM

Starts at 4/700

<u>LOC</u>	<u>NAME</u>	<u>DFLT</u>	<u>DEFINITION</u>
------------	-------------	-------------	-------------------

700	LOUTQM	1000	INACTIVE MINUTES TO AUTO LOGOUT
701	RWLOCK	1	SYSTEM READ/WRITE LOCK: 0 - 1 READER OR 1 WRITER 1 - N READERS OR 1 WRITER 3 - N READERS AND 1 WRITER 5 - N READERS AND N WRITERS
702	DONSTP	0	0=>LOGOUT PHANTOMS ON WARM START 1=>CONTINUE PHANTOMS ON WARM START
703	DLOGOT	0	0=>IGNORE DISCONNECT 1=>FORCE LOGOUT ON DISCONNECT
704	DEFERA	242	DEFAULT ERASE CHARACTER = "
705	DEFKIL	277	DEFAULT KILL CHARACTER = ?
706	PRI500		1=>P500
707	VERSIO		PRIMCS REVISION ID (ASCII)
720	NLGPRT		1=>INHIBIT LOGIN MESSAGES
721	LOGOUT		1=>CAN'T LOGIN WHILE LOGGED IN
722	LRQUOT	10000	LOGREC QUOTA

INTERNAL CALLING SEQUENCES

AINIT	VERSIO, MEMSIZ
ALCONF	A, B
ALONF	BNO
AMINIT	--
ASRDIM	--
BADDSK	DISK (LOG FCN)
BFDEQU	BUFCON, NW (FCN)
BFENQU	BUFCON, NW
BFGETR	BUFCON, NW (FCN)
BFRELS	BUFCON
BOOT	--
BRPDIM	--
BRPONF	FLAG
BRPOTA	CHAR (LOG FCN)
BUFCHK	BNO, NUMCHARS (LOG FCN)
BUFCLR	BNO
CE2DIM	--
CENDIM	--
CGETBK	SIZE, ADDR, COND, ALTRTN
CLNLUN	USRBLK, LUNADR, STAT
CLOSE\$	UNIT
CNFLCT	KEY, PDEV (LOG FCN)
COMXIT	--
COPYUP	--
CRDONF	FLAG
DATE\$	XXX (FCN)
DELAY	A, B, C, ALTRTN
DELBKQ	QNM, BKN, ALTRTN
DEMOTE	--
DEQUE	NUM, ADDR, COUNT, ALTRTN

DEVCHK USR (FCN)  
 DEVONF DEVNDX, FLAG  
 DISMSG USRBLK, LUNADR  
 DOSSUB ---  
 DSKEQV DISKA, DISKB (LOG FCN)  
 DUMF FLAG  
 ENQUEB NUM, ADDR, COUNT  
 ENQUET NUM, ADDR, COUNT  
 ERRST\$ LCODE, KEY, TEXT, TXTLEN, MYNAME, MYLEN  
 EXPNAM INNAME, NAMLEN, OUTNAM  
 F\$HT CODE  
 FAMERR ---  
 FAMMSG FUNNO, FAMNO, RA, LOC32 (A1), N1, LOC32 (A2), N2,  
 LOC32 (A3), N3, LOC32 (A4), N4, LOC32 (A5), N5,  
 LOC32 (A6), N6  
 FMLIOB BNO, CHAR (LOG FCN)  
 FNDLUN USRBLK, LSRCID, LUNADR, ALTRTN  
 FREEBL ---  
 GCHAR LOC32 (ARRAY), CHARPTR  
 GET LOC32 (WORD) (FCN)  
 GETBLK SIZE, ADDR, ALTRTN  
 GETCNT SIZE, COUNT  
 GETLUN USRBLK, SW, LUNADR, ALTRTN  
 GETRBK ALTRTN  
 GETREC RA32, DVNO, CODE (INT\*4 FCN)  
 GETREG TVEC  
 GETSBK BLKAD  
 GETSEG USR, SEGNO  
 GETTBK BLKAD, ALTRTN  
 GETUBK USRBLK, ALTRTN  
 GROSS ---  
 GISTAT XXX (FCN)  
 HCRONF FLAG  
 HDFILL TGIN, SRCN, TGTU, MSGBLK, LINTAB, NETHDR, FLGW  
 HPRON0 FLAG  
 HPRON1 FLAG  
 INETMN ---  
 ININET ---  
 INUSRC ---  
 IPCPTM LINEN  
 ISPREM A, B, C (FCN)  
 ITLBNZ ---  
 LGET LOC32 (WORD) (INT\*4 FCN)  
 LINTST LINDFN, ALTRTN  
 LISTF ---  
 LOCATE KEY, RA32, LDEV  
 LOCK KEY, SEMAPHORE (LOG FCN)  
 LOCKFS --- (SHORT CALL)  
 LOCKPG USR, KEY, PTR32, NW  
 LOGEV1 MSG  
 LOGEV2 ---  
 LOGIN KEY, UNAME, NAMLEN, USNAME, LDEV  
 LSTORE LOC32 (WORD), DATA  
 MAPIO LOC32 (USRBFRR), NW, PAGE-MAP-ENTRY (INT\*4 FCN)  
 MAPNDX USR, SEGNO (FCN)  
 MISSIN ARG (LOG FCN)  
 MISZER ARG (FCN)

MODTS DELTA  
 MOV32P LOC32 (FROM), LOC32 (TO), NW  
 MOVNAM INAME, ILEN, ONAME, OLEN, TRULEN  
 MOV52S FRMSEG, LOC16 (FROM), TOSEG, LOC16 (TO), NW  
 MOVUTU FRMUSR, FRMSEG, LOC16 (FROM), TOUSR, TOSEG,  
 LOC16 (TO), NW  
 MPINIT ---  
 MSGOUT KEY, USR, LOC32 (BFR) (FCN)  
 MTDONE CTRLR-INDEX  
 NETALM ---  
 NETMAN ---  
 NETMSG FLGW, LUNADR  
 NETXEC ---  
 NEWDAM DRWP, UNIT, NRAL, CODE  
 NOTIFY OPTION, SEMAPHORE  
 OERRTN ALTVAL, ALTRTN, CODE, TEXT, TXTLEN, NAME, NAMLEN  
 PABORT ABORT-FLAGS  
 PAGTUR LOC32 (VIRTADR)  
 PHINIT ---  
 PNDNAM SYSN, NETABL, ALTRTN  
 PRCFP ABORT-FLAGS  
 PRIPC ---  
 PRSMIC ---  
 PRWERR ALTVAL, CODEV  
 PTRAP INSTRUCTION  
 PTRDIM ---  
 PTRINA CHAR (LOG FCN)  
 PTRONF FLAG  
 QCHECK NUM, ELQUED  
 QTRVRS NUM, BLKN, ADDR, COUNT, ALTRTN  
 QUITON --- (SHORT CALL)  
 RMANLZ INST, FT, OP, ACT, DEV  
 ROUTER RINGBK, HDROFF, MSGBLK, COUNT  
 RINBLK ADDR  
 RINREC RA32, DVNO  
 RINSEG SEGNO  
 RUNUSR FAMBLK, NW, ERVEC  
 SCHAR LOC32 (ARRAY), CPTR, CHAR  
 SCHED RESET-VAL [, QUEUE-SEMAPHORE]  
 SDWIDX USR, SEGNO (FCN)  
 SEEK CYL, DVNO  
 SEMTN SEMAPHORE, INT1, INT2, CODE  
 SEND USR, LUNADR, ALTRTN  
 SETABT KEY, USR, ALARM  
 SETREG TVEC, PARFLG  
 SHUTDN ---  
 SLABRT LPN  
 SLCLDB ---  
 SLCONF FLAG  
 SLERF KEY  
 SMLCEX SVCF, LPN  
 SRWREC KEY, PBAV, MWV, NCH, RA32, DVNO, ALTRTN  
 STAC NEWVAL, OLDVAL, VAR (LOG FCN)  
 STIMER TENIHS  
 STORE LOC32 (WORD), DATA  
 SYSERR ---  
 TIOU USR, CHAR

TEXTOS\$ NAME, NAMLEN, TRULEN, TEXTOK  
 TEXTOK FNAMEBFR  
 TIME USR, TIM  
 TIMES\$ XXX (FCN)  
 TODEC USR, NUM, LEAD-CHAR/FIELDWIDTH  
 TOLIOB BNO, CHAR  
 TPIOS KEY, PBA, PN, RA32, ALTRIN  
 TRNMSG LINTAB, MSGBLK, CNT, MSGVEC  
 TRUNC\$ UNIT, CODE  
 TRWRAT KEY, LDEV  
 UMAPIO LOC32 (USRBFR), NW  
 UNLKFS -- (SHORT CALL)  
 UNLOCK KEY, SEMAPHORE  
 UPDATE KEY, RA32, LDEV  
 UPUSR LOC32 (USRADDR), DATA, NWD  
 VALID TNAME, NETTAB, ALTRIN, NODE  
 VGONF FLAG  
 VGINIT --  
 WAIT SEMAPHORE  
 WREC PBA, NW, NCH, CRA32, DVNO, ALTRIN  
 XEQUSR --  
 \*\*\*\*\*

LOCKS, LCKCOM

Locks are semaphores used to control access to serially reusable resources. Located in LCKCOM (SEG 4), source file NLOCK.

\*\*\* Addition LOCK Information \*\*\*  
 to be supplied at next update

MMAP (MEMORY MAP)

One entry per physical page of memory.

MMAP + n:

- < 0 => Page 'n' unavailable
- = 0 => Page 'n' available
- > 0 => In use, --> HMAP entry for page

MAXPAG = number pages memory in use.

PAGE MAPS

See under Section on CPU.

PTUSEG

PTUSEG(2, KSEG) (SEG 4)

PTUSEG(1, N) Owner of Page Map N  
 PTUSEG(2, N) Segment Number for Page Map N

PUDCOM

006000	SUPSTK	SN FOR SUPERVISOR STACK
002000	STKSIZ	ONE PAGE OF STACK
000000	PUDCOM	SUPFRE (2) ,SUPEXT (2)
000004	CUSR	1 CURRENT USER NUMBER
000005	LUSR	1 USERCOM INDEX
000006	VRTSSW	1 VIRTUAL SENSE SWITCHES
000007	INHPRF	1 INHIBIT-PROCESS-FAULT COUNTER
000010	ABSAVE	1 SAVED ABORT FLAGS
000011	HILOCK	1 ADR HIGHEST OWNED ORDERED LOCK
000011	LCKOWN	
000012	OWNFS	1 NUMBER ORDERED LOCKS OWNED
000013	QUITF	1 QUIT FLAG, INHIBIT COUNT
000014	ASRCWD	1 ASR CONTROLS
000015	ERASCH	1 CHARACTER ERASE CHARACTER
000016	KILLCH	1 LINE DELETE CHARACTER
000017	TKNSAV	1 RDTK\$\$ SAVEAREA
000020	COMPAR	40 COMMAND LINE INPUT BUFFER
000070	COMSWI	1 COMMAND INPUT SWITCH
000071	COMUNI	1 COMMAND INPUT UNIT
000072	COUSWI	1 COMMAND OUTPUT SWITCH
000073	COUPTR	1 COULIN CHARACTER POINTER
000074	COULIN	10 COMMAND OUTPUT BUFFER
000106	ERRVEC	9 ERRVEC
000117	XSAVE	1 TEMP SAVE FOR X IN FAULT RTES
000120	RVSA	1 START ADDRESS IN RVEC
000121	RVEA	1 END ADDRESS IN RVEC
000122	HMAPPP	
000124	BUFNEW	
000125	USRETM	
000126	SUPSF	START OF FIRST RING 0 STACK FRAME
000130	RVPB	2 PBH AND PBL
000136	RVKEYS	1 KEYS
000137	RVPECL	1 LOC(PCL)+2 ON RING 0 PCL ENTRY
000143	RVEC	29 REGISTER SAVEAREA
000143	RVMASK	1 SAVE MASK IN RVEC
000172	PUDEND	END OF PUDCOM

SEGMENT USAGE BY PRIMOS

<u>SEGMENT</u>	<u>CONTENTS</u>
0	LOC '61 (OPTION-A memory increment cell) DMC channels for AMLC, SMLC, MAG TAPE AMLC buffers DISK driver (DVDISK) Disk I/O windows (4 pages) Mag tape I/O windows (6 pages) Mag tape dump window (1 page) IPC I/O window (2 pages) SMLC I/O windows (12 pages)
1	Associative bfrs for file system (64 pages)
2,3	MOVU2U segment windows
4	Interrupt catchers (phantoms) Check catchers Semaphores Ready PCB list (loc '600) Configuration common (FIGCOM) (loc '700) Crash 9 trk magtape dump program (loc '776) Memory parity scanner (loc '777) WARM restart routine (loc '1000) COLD start routine (loc '1400) Memory usage map (MMAP) Page maps (HMAP, LMAP) Segment tables Process control blocks (PCBs) Interrupt fault table Interrupt stack
5	Gate segment for direct-entrance PCLs
6	TMAIN, including: Supervisor and user fault catchers SVC front-ends Supervisor locked data (SUPCOM) Clock process Kernel procedures
7	User terminal buffers
10	Per-user unlocked data (USRCOM)
11	File system procedures
12	Network data and procedures SMLC data and procedures
6000	Ring 0 stack segment (one per user)

SEMAPHORES (SEMCOM)

\*\*\* Refer to SEMAPHORES in Section II \*\*\*

\*\*\* Addition SEMAPHORE Information \*\*\*  
to be supplied in next update

SVC INTERLUDE

```
ENTRY DAC  **
  SVC
  OCT  CODE
  1  100000  1 => interlude call
  2  040000  1 => bounce
  3-4 030000  Unused
  5-16 00****  SVC number
```

USRCOM

SEG 10/(USRNO-1)\*'505 ...

```
+1  UNITAB:   0 <= UNIT <= '21
      +UNIT*17 +0  VSTAT
              +1  VBRA(2)
              +3  VDVNO
              +4  VDCRA(2)
              +6  VDRWP
              +10 VCRA(2)
              +12 VRWP
              +13 VPRIV
              +14 VPOPRA(2)
              +16 VPOPRW
```

```
+417 CUFD:
      +0  CURRENT UFD NAME
      +20 CFDBRA(2)
      +22 CFDDEV
      +23 CFDPOP(2)
      +25 CFDOWN
      +26 CFDLLEN
      +27 CFDPRA(2)
      +31 CF DPRW
```

```
+451 HOMUFD:
      +0  HOME UFD NAME
      +20 HOMBRA(2)
      +22 HOMDEV
      +23 HOMPOP(2)
      +25 HOMOWN
      +26 HOMLEN
      +27 HOMPRA(2)
      +31 HOMPRW
```

```
+503 LOGNAM(3)
```

VQUTM

1	1 MIN.	1 MINUTE (UPDATE, LOGEV2, ETC.)
2	16.5 MSEC	PUNCH DIM
3	--	DIGITAL INPUT
4	112 MSEC	ASR DIM
5	100 MSEC	TENTH SECOND (STIMER QUEUES)
6	--	UNUSED
7	--	UNUSED
8	--	UNUSED
9	--	UNUSED
10	1/2 SEC	SMLCEX ALARM
11	10 SEC	NETWORK GROSS TIMER
12	1 SEC	IPC PROTOCOL TIMER
13	1/2 SEC	REMOTE USER POLL

9 SVC INFORMATIONSVC CALLING SEQUENCES

\* => Also Direct Entrance Call.

ATCH\$\$ -- Attach to UFD

CALL ATCH\$\$ (UFDNAM, NAMLEN, LDISK, PASSWD,  
KEY, CODE) (\*1500)

CALL ATTAC\$ (UFDNAM, NAMLEN, LDISK, PASSWD,  
KEY, LOC(CODE)) (1400)

CALL ATTACH (UFDNAM, LDISK, PASSWD, KEY,  
ALTRIN) (0100)

\*\*\*\*\* KEY \*\*\*\*\*  
K\$IMFD = :0 UFD IS IN MFD  
K\$ICUR = :2 UFD IS IN CURRENT UFD  
\*\*\*\*\* KEYMOD \*\*\*\*\*  
K\$SETC = :0 SET CURRENT UFD (DO NOT SET HOME)  
K\$SETH = :1 SET HOME UFD (AS WELL AS CURRENT)  
\*\*\*\*\* UFDNAM \*\*\*\*\*  
K\$HOME = :0 RETURN TO HOME UFD (KEY=K\$IMFD)  
\*\*\*\*\* LDISK \*\*\*\*\*  
K\$ALLD = :100000 SEARCH ALL DISKS  
K\$CURR = :177777 SEARCH MFD OF CURRENT DISK

\*\*\*\*\* CODES \*\*\*\*\*  
E\$NATT E\$MTUD  
E\$FMIF E\$DISK  
E\$PTRM E\$BPAS  
E\$BKEY E\$BUFD

BREAK\$ -- Disable/Enable Quits

CALL BREAK\$ (KEY) (\*0507)

\*\*\*\*\* KEY \*\*\*\*\*  
= :0 INHIBITS QUILTS  
= :1 ENABLE QUILTS

CLIN -- Read Character from Command Stream

CALL CLIN (CHAR) (\*0601)

CMREAD -- Read Last Command Line

CALL CMREAD (BUFF(18)) (0602)

BUFF(1-3) First name or blanks  
BUFF(4-6) Second name or blanks  
BUFF(7-9) Third name or blanks  
BUFF(10) First octal parameter or 0  
...  
BUFF(18) Ninth octal parameter or 0

CNAM\$\$ -- Change a Filename

CALL CNAM\$\$ (OLDNAM, OLDLEN, NEWNAM, NEWLEN,  
CODE) (\*1515)

CALL CNAME\$ (OLDNAM, OLDLEN, NEWNAM, NEWLEN,  
LOC(CODE)) (1415)

CALL CNAME (OLDNAM, NEWNAM, ALTRIN) (0113)

\*\*\*\*\* CODES \*\*\*\*\*  
E\$BNAM E\$FNIF  
E\$BUFD E\$IREM  
E\$EOF E\$NRIT  
E\$EXST

CNIN\$ -- Raw Data Input from Command Stream

CALL CNIN\$ (BUFF, CHARCNT, STATV(3)) (\*0604)

COMANL -- Read Command Line

CALL COMANL (\*0600)



COMI\$\$ -- Switch Command Input Stream

CALL COMI\$\$ (FILNAM, NAMLEN, UNIT, CODE) (\*1516)  
 CALL COMIN\$ (FILNAM, NAMLEN, UNIT, LOC(CODE)) (1416)  
 CALL COMINP (FILNAM, UNIT, ALTRIN) (0603)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$BDAM E\$NATT  
 E\$BUFD E\$NRIT  
 E\$DIRE E\$PTRM  
 E\$FIUS E\$UIUS  
 E\$FNIF E\$UNOP

COMO\$\$ -- Control Routing of Terminal Output

CALL COMO\$\$ (KEY, FILNAM, NAMLEN, 0, CODE) (\*1523)

\*\*\*\*\* KEY \*\*\*\*\*  
 :1 TURN TTY OUTPUT OFF  
 :2 TURN TTY OUTPUT ON  
 :4 (RESERVED)  
 :10 TURN FILE OUTPUT OFF  
 :20 TURN FILE OUTPUT ON  
 :40 APPEND IF TURNING ON,  
 CLOSE IF TURNING OFF  
 :100 TRUNCATE IF TURNING ON

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$EOF

CONNECT -- Connect Logical Unit Number

CALL CONNECT (TGINAM, TGTUSR, LUN, DATA, STATV,  
 LINTYP) (0401)

CREA\$\$ -- Create New UFD in Current UFD

CALL CREA\$\$ (UFDNAM, NAMLEN, OPASS, NPASS,  
 CODE) (\*1501)  
 CALL CREAT\$ (UFDNAM, NAMLEN, OPASS, NPASS,  
 LOC(CODE)) (1401)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$NATT E\$DKFL  
 E\$BNAM E\$EXST  
 E\$DISK E\$PTRM  
 E\$BUFD  
 E\$UIUS (bounce package only)  
 E\$FIUS (bounce package only)  
 E\$FDL (old partition only)

D\$INIT -- Initialize Disk Devices

CALL D\$INIT (PDEV) (0506)

DISCON -- Disconnect Logical Unit Number

CALL DISCON (LUN, DATA, STATV) (0410)

DUPLX\$ -- Set/Return Terminal Characteristics

Integer = DUPLX\$ (LWORD)

LWORD Contents:

bit	Meaning when on
1 100000	Half duplex
2 040000	No LF after CR
3 020000	XOFF/XON Recognition
4 010000	XOFF Received
5-8 007400	Reserved
9-10 000377	user number

LWORD = -1 => no update of LWORD.  
 Integer set to new LWORD setting.

ERKL\$\$ -- Read/Set Kill and Erase Character

CALL ERKL\$\$ (KEY, ERASEC, KILLC, CODE) (\*1524)

\*\*\*\*\* KEYS \*\*\*\*\*  
see COMO\$\$

\*\*\*\*\* CODES \*\*\*\*\*  
E\$BKEY  
E\$BPAR

ERRPR\$ -- Print Standard System Error Messages

CALL ERRPR\$ (KEY, CODE, TEXT, TXTLEN, NAME, NAMLEN) (\*1402)

\*\*\*\*\* KEY \*\*\*\*\*  
K\$NRIN = :0 NEVER RETURN TO USER  
K\$SRIN = :1 RETURN AFTER START COMMAND  
K\$IRIN = :2 IMMEDIATE RETURN TO USER

\*\*\*\*\* CODES \*\*\*\*\*  
E\$EOF  
E\$LAST

ERRRIN -- Return Error Code

CALL ERRRIN (ALTRIN, NAME, MSG, MSGLEN) (0106)

ERRSET -- Handle Error Messages

CALL ERRSET (ALTVAL, ALTRIN, NAME, MSG, MSGLEN) (0114)

EXIT -- Return to PRIMOS Command Level

CALL EXIT (\*0105)

FAMSVC -- (Called by FAM only)

CALL FAMSVC (A1, A2, A3, A4, A5, A6, ALTRIN) (0400)

FORCEW -- Update Runit to Disk

CALL FORCEW (KEY, UNIT) (\*0115)

GETCON -- Get Pending Connect Information

CALL GETCON (TARGET, USER, DATA, STATV) (0402)

GETERR -- Get Error Messages

CALL GETERR (BUFF, NW) (0110)

GETERR is used after a return from PRWFIL:

<u>On an alternate return:</u>	<u>On a normal return:</u>
ERRVEC(1) Error code	PRWFIL:
	ERRVEC(3) Record number
	ERRVEC(4) Word number

ERRVEC(2) Alternate value	Key of read/write convenient:
	ERRVEC(2) No. of words transferred

SEARCH:  
ERRVEC(2) File type

GINFO -- Return Operating System Information

CALL GINFO (BUFF, NW)

Return information for PRIMOS II:

BUFF(1)	Low bound of PRIMOS II and buffers (77777 octal if 64K PRIMOS II).
2	High bound of PRIMOS II (77777 octal if 64K PRIMOS II).
3	(not valid)
4	(not valid)
5	Low bound of PRIMOS II and buffer (64K PRIMOS II only).
6	High bound of 64K PRIMOS II.

Returned information for PRIMOS III, IV, and V:

<u>xerverc word</u>	<u>content</u>
1	0
2	0
3-6	(not valid)

GPASS\$ -- Obtain UFD Passwords

CALL GPASS\$ (UFDNAM, NAMLEN, OPASS, NPASS,  
CODE) (\*1504)

CALL GPASS\$ (UFDNAM, NAMLEN, OPASS, NPASS,  
CODE) (1404)

\*\*\*\*\* CODES \*\*\*\*\*  
E\$NATT E\$NTUD  
E\$FNIF E\$DISK  
E\$PTRM E\$BUFD  
E\$UIUS (bounce package only)  
E\$FIUS (bounce package only)

NETLNK --

CALL NETLNK (STATV) (0412)

NETWAT -- Put User to Sleep

CALL NETWAT (0406)

NETSTAT -- Get Network Status

CALL NETSTAT (KEY, P1, P2, ARRAY) (0407)

PRERR -- Prints Error Messages

CALL PRERR (0111)

PRWF\$ -- Read-Write-Position SAM/DAM File

CALL PRWF\$ (KEY, FUNIT, LOC (BUFF), BUFLN,  
POS32, RNW, CODE) (\*1506)

CALL PRWFL\$ (KEY, UNIT, LOC (BUFF), NW, POS,  
RNW, LOC (CODE)) (1406)

CALL PRWFIL (KEY, UNIT, LOC (BUFF), NW, POS,  
ALTRIN) (0300)

KEY = RWKEY + POSKEY + MODE

\*\*\*\*\* RWKEY \*\*\*\*\*  
K\$READ = :1 READ  
K\$WRIT = :2 WRITE  
K\$POSN = :3 POSITION ONLY  
K\$TRNC = :4 TRUNCATE  
K\$RPOS = :5 READ CURRENT POSITION  
\*\*\*\*\* POSKEY \*\*\*\*\*  
K\$PRER = :0 PRE-POSITION RELATIVE  
K\$PREA = :10 PRE-POSITION ABSOLUTE  
K\$POSR = :20 POST-POSITION RELATIVE  
K\$POSA = :30 POST-POSITION ABSOLUTE  
\*\*\*\*\* MODE \*\*\*\*\*  
K\$CONV = :400 CONVENIENT NUMBER OF WORDS

\*\*\*\*\* CODES \*\*\*\*\*  
E\$EOF E\$NOF  
E\$UNOP E\$DKFL  
E\$DISK E\$PTRM  
E\$BUNT E\$BOF  
E\$IREM E\$NTUD  
E\$NTSD

RDEN\$\$ -- Read UFD Entry

CALL RDEN\$\$ (KEY, FUNIT, BUFF, BUFLN, RNW, NAM32, NAMLN, CODE) (\*1507)

CALL RDENT\$ (KEY, UNIT, BUFF, BUFLN, RNW, NAME32, NAMELEN, LOC(CODE)) (1407)

Entry Format:

0	ECW	
1	F	
	I	
	L	
	E	
	...	FILENAME (BLANK PADDED)
	N	
	A	
	M	
	E	
17	PROTEC	PROTECTION (OWNER/NONOWNER)
18	RESERVED	RESERVED FOR FUTURE USE
19	FILTYP	FILETYPE <--- END OF ENTRY FOR TYPE=1
20	DATMOD	DATE LAST MODIFIED
21	TIMMOD	TIME LAST MODIFIED
22	RESERVED	RESERVED FOR FUTURE USE
23	RESERVED	RESERVED FOR FUTURE USE

DATMOD = YYYYYYMMMMDDDD where:  
 YYYYYY is the year module 100  
 MMMM is the month  
 DDDDD is the day

DATMOD is held in binary seconds-since-midnight divided by 4.

\*\*\*\*\* KEY \*\*\*\*\*

K\$READ = :1 READ NEXT ENTRY  
 K\$RSUB = :2 READ NEXT SUB-ENTRY  
 K\$GPOS = :3 RETURN CURRENT POSITION IN UFD  
 K\$UPOS = :4 POSITION IN UFD  
 K\$NAME = :5 READ ENTRY SPECIFIED BY NAME

\*\*\*\*\* CODES \*\*\*\*\*

E\$EOF E\$NOF  
 E\$UNOP E\$DISK  
 E\$PTRM E\$BKEY  
 E\$BUNT E\$BUFD  
 E\$BFTS

RDLIN\$ -- Read Line of Characters from ASCII File

CALL RDLIN\$ (UNIT, LINE, NW, CODE) (\*1525) :1506

CALL RDLIN (UNIT, LINE, NW, ALTRIN) (0202) :406

RDTK\$\$ -- Read Token from Command Line

CALL RDTK\$\$ (KEY, INFO(8), BUFF, BUFLN, CODE) (\*1517) :300

CALL RDTKN\$ (KEY, INFO(8), BUFF, BUFLN, LOC(CODE)) (1417)

INFO(1):

- 1 normal token
- 2 register setting parameter
- 5 null token
- 6 end of line

INFO(2): len in chars of token; null = 0 len

INFO(3): further info about token --

- bit 1 (:100000) dec conversion successful, value returned in INFO(4).
- bit 2 (:040000) oct conversion successful, value returned in INFO(5). This bit always set when token type is 2.
- bit 3 (:020000) token begins with unquoted minus sign.
- bit 4 (:010000) explicit position for register setting given, value returned in INFO(4).
- bits 5 - 16: reserved for future use.

INFO(4): depend on flags set in INFO(3)

INFO(5): depend on flags in INFO(3)

INFO(6) - INFO(8): reserved for future use

\*\*\*\*\* CODES \*\*\*\*\*

E\$BKEY  
 E\$BPAR  
 E\$BFTS

RECEIV -- Receive Message from Remote System

CALL RECEIV (LUN, LOC(BUFF), NW, STATV) (0404)

RECYCL -- Cycle to Next User

CALL RECYCL (\*0505)

REST\$\$ -- Restore Memory Image from File

CALL REST\$\$ (RVEC, NAME, NAMLEN, CODE) (\*1520)

CALL RESTO\$ (RVEC, NAME, NAMLEN, LOC(CODE)) (1420)

CALL RESTOR (RVEC, NAME, ALTRIN) (0103)

\*\*\*\*\* CODES \*\*\*\*\*  
see SRCH\$\$

RESU\$\$ -- Resume Memory Image from File

CALL RESU\$\$ (NAME, NAMLEN) (\*1521)

CALL RESUM\$ (NAME, NAMLEN) (1420)

CALL RESUME (NAME) (0104)

\*\*\*\*\* CODES \*\*\*\*\*  
see SRCH\$\$

RJCON -- Reject Pending Connect

CALL RJCON (TARGET, USER, STATV, NUMTYP) (0403)

RREC -- Read Record From Disk to MemoryCALL RREC (LOC(BUFF), BUFLN, N, RA, PDEV,  
ALTRIN) (0500)CALL RRECL (LOC(BUFF), BUFLN, N, RA32, PDEV,  
ALTRIN) (0516)SATR\$\$ -- Set Attributes in UFD Entry

CALL SATR\$\$ (KEY, NAME, NAMLEN, ARRAY, CODE) (\*1510) 506)

CALL SATR\$ (KEY, NAME, NAMLEN, ARRAY,  
LOC(CODE)) (1410) 06)

\*\*\*\*\* KEY \*\*\*\*\*  
K\$PROT = :1 SET PROTECTION 00)  
K\$DTIM = :2 SET DATE/TIME MODIFIED  
K\$DMPB = :3 SET DUMPED BIT  
K\$RWLK = :4 SET PER FILE READ/WRITE LOCK

\*\*\*\*\* CODES \*\*\*\*\*  
E\$NATF E\$FNIF  
E\$DISK E\$PTRM  
E\$BKEY E\$BUFD  
E\$UIUS (bounce package only)  
E\$FIUS (bounce package only)  
E\$OLDP (old partition only)

SAVE\$\$ -- Save P300 Memory Image as a File

CALL SAVE\$\$ (RVEC, NAME, NAMLEN, CODE) (\*1522)

CALL SAVE\$ (RVEC, NAME, NAMLEN, LOC(CODE)) (1422)

CALL SAVE (RVEC, NAME) (0102)

SEM\$DR -- Drain Semaphore

CALL SEM\$DR (SEMNUM, CODE) (\* --)

\*\*\*\*\* CODES \*\*\*\*\*  
E\$BPAR

SEM\$NF -- Notify User Semaphore

CALL SEM\$NF (SEMNUM, CODE) (\* --)

\*\*\*\*\* CODES \*\*\*\*\*  
E\$BPAR  
E\$SEMO

SEM\$TN -- Setup Semaphore for Timed Notices

CALL SEM\$TN (SEMNUM, INT32, INT32, CODE) (\* --)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$BPAR  
 E\$NTIM

SEM\$TS -- Obtain Current Semaphore Value

CALL SEM\$TS (SEMNUM, CODE (INT FCN)) (\* --)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$BPAR

SEM\$WT -- Wait on User Semaphore

CALL SEM\$WT (SEMNUM, CODE) (\* --)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$BPAR

SGDR\$\$ -- Position and Read Segment Directory Entries

CALL SGDR\$\$ (KEY, FUNIT, ENTRYA, ENTRYB, CODE) (\*1512)

CALL SEGDR\$ (KEY, UNIT, ENTRYA, ENTRYB, LOC(CODE)) (1412)

\*\*\*\*\* KEY \*\*\*\*\*  
 K\$SPOS = :1 POSITION TO ENTRY NUM IN SEGDIR  
 K\$GOND = :2 POSITION TO END OF SEGDIR  
 K\$GPOS = :3 RETURN CURRENT ENTRY NUMBER  
 K\$MSIZ = :4 MAKE SEGDIR GIVEN NR OF ENTRIES  
 K\$MVNT = :5 MOVE FILE ENTRY TO DIFFERENT  
 K\$FULL = :6 RETURN NEXT NONEMPTY ENTRY  
 K\$FREE = :7 RETURN NEXT FREE ENTRY  
 POSITION

SLEEP\$ -- Suspend Execution

CALL SLEEP\$ (INT32) (\* --)

INT32 = number of milliseconds to delay

06)

6)

SPASS\$\$ -- Set UFD Passwords

CALL SPASS\$ (OPASS, NPASS, CODE) (\*1513)

CALL SPASS\$ (OPASS, NPASS, LOC(CODE)) (1413)

0)

\*\*\*\*\* CODES \*\*\*\*\*  
 E\$EOF E\$NOF  
 E\$UNOP E\$DKFL  
 E\$NRIT E\$FNIS  
 E\$EXST E\$DISK  
 E\$PTRM E\$BKEY  
 E\$BUNT

SRCH\$\$ -- Open or Close a File

CALL SRCH\$\$ (KEY, NAME, NAMLEN, UNIT, TYPE, CODE) (\*1511)

CALL SEARC\$ (KEY, NAME, NAMLEN, UNIT, TYPE, LOC(CODE)) (1411)

CALL SEARCH (KEY, NAME, UNIT, ALTRIN) (0101)

KEY = ACTION + REF+ NEWFIL

\*\*\*\*\* ACTION \*\*\*\*\*  
 K\$READ = :1 OPEN FOR READ  
 K\$WRIT = :2 OPEN FOR WRITE  
 K\$RDWR = :3 OPEN FOR READING AND WRITING  
 K\$CLOS = :4 CLOSE FILE UNIT  
 K\$DELE = :5 DELETE FILE  
 K\$EXST = :6 CHECK FILE'S EXISTENCE  
 \*\*\*\*\* REF \*\*\*\*\*  
 K\$IUFD = :0 FILE ENTRY IN UFD  
 K\$ISEG = :1000 FILE ENTRY IN SEGMENT DIRECTORY  
 K\$CACC = :1000 CHANGE ACCESS  
 \*\*\*\*\* NEWFIL \*\*\*\*\*  
 K\$NSAM = :0 NEW SAM FILE  
 K\$NDAM = :2000 NEW DAM FILE  
 K\$NSGS = :4000 NEW SAM SEGMENT DIRECTORY  
 K\$NSGD = :6000 NEW DAM SEGMENT DIRECTORY  
 K\$CURR = :177777 CURRENTLY ATTACHED UFD

## \*\*\*\*\* CODES \*\*\*\*\*

E\$NATT	E\$DKFL	E\$NRIT
E\$FDEL	E\$NTUD	E\$NTSD
E\$FNIF	E\$BNAM	E\$DNTE
E\$DISK	E\$BDAM	E\$PTRM
E\$BKEY	E\$BUNT	E\$BSUN
E\$SUNO	E\$BUFD	
E\$UNOP	(for K\$CACC KEY only)	
E\$UIUS	(not for E\$EXST KEY)	
E\$FDFL	(old partition only)	
E\$FIUS	(not for E\$EXST KEY)	

T\$AMLC -- AMLC Receive/Transmit

CALL T\$AMLC (LINE, LOC(BUFF), NW, INST,  
STATV) (\*0513)

T\$CMPC -- Move Card of Info to User's Space

CALL T\$CMPC (UNIT, LOC(BUFF), NW, INST,  
STATV) (\*0512)

T\$LMPC -- Print Data

CALL T\$LMPC (UNIT, LOC(BUFF), NW, INST,  
STATV) (\*0511)

T\$PMPC -- Punch Data

CALL T\$PMPC (UNIT, LOC(BUFF), NW, INST,  
STATV) (\*0515)

T\$MT -- Move Raw Data from Magtape

CALL T\$MT (UNIT, LOC(BUFF), NW, INST, STATV) (\*0510)

T\$VG -- Print Data on Versatec Printer

CALL T\$VG (UNIT, LOC(BUFF), NW, INST, STATV) (\*0514)

T\$SLC -- Performs I/O Over SMLC Lines

CALL T\$SLC (KEY, LINE, LOC(BUFF), NW) (1001) (06)

TIMDAT --

CALL TIMDAT (BUFF, BUFLN) (\*0502) (0)

TIMDAT returns information in BUFF as follows:

- BUFF(1) Two ASCII characters representing month
- (2) Two ASCII characters representing day.
- (3) Two ASCII characters representing year.
- (4) Integer time in minutes since midnight.
- (5) Integer time in seconds.
- (6) Integer time in ticks.
- (7) Integer CPU time used in seconds.
- (8) Integer CPU time used in ticks.
- (9) Integer disk I/O time used in seconds.
- (10) Integer disk I/O time used in ticks.
- (11) Integer number of ticks per second.
- (12) user number.
- (13) 6-character login name, left justified.
- (14)
- (15)

TNOU -- Output CHARCNT Chars with CR and LF

CALL TNOU (MSG, CHARCNT) (\*0702)

TNOUA -- Output CHARCNT Characters

CALL TNOUA (MSG, CHARCNT) (\*0703)

TRNMIT -- Transmit Message to a Remote Machine

CALL TRNMIT (LUN, LOC(BUFF), CNT, STATV) (0405)

UNLINK -- Disconnect All Logical Unit Numbers

CALL UNLINK (0411)

WREC -- Write Record from Memory to Disk

CALL WREC (LOC(BUFF), BUFLLEN, NW, RA, PDEV,  
ALTRTN) (0501)

CALL WRECL (LOC(BUFF), BUFLLEN, NW, RA32, PDEV,  
ALTRTN) (0517)

WTLIN\$ --

CALL WTLIN\$ (UNIT, LINE, NW, CODE) (\*1526)

CALL WTLIN (UNIT, LINE, NW, ALTRTN) (0203)

SVC NUMBERS

\* => PCLable

* -- SEM\$DR	*0600	COMANL	(06)
* -- SEM\$NF	*0601	CLIN	
* -- SEM\$TN	0602	CMREAD	
* -- SEM\$TS	0603	COMINP	6)
* -- SEM\$WT	*0604	CNIN\$	
* -- SLEEP\$			
	*0702	TNOU	0)
0100	*0703	TNOUA	
0101	*0705	DUPLX\$	
0102			
0103	1001	T\$SLC	
0104			
*0105	1400	ATTAC\$	
0106	1401	CREAT\$	
0110	*1402	ERRPR\$	
0111	1404	GPASS\$	
0112	1406	PRWFL\$	
0113	1407	RIDENT\$	
0114	1410	SATTR\$	
*0115	1411	SEARC\$	
	1412	SEGDR\$	
0202	1413	SPASS\$	
0203	1415	CNAME\$	
	1416	COMIN\$	
0300	1417	RDTKN\$	
	1420	RESTO\$	
0400	1421	RESUM\$	
0401	1422	SAVE\$	
0402			
0403	*1500	ATCH\$	
0404	*1501	CREA\$	
0405	*1504	GPAS\$	
0406	*1506	PRWF\$	
0407	*1507	RDEN\$	
0410	*1510	SATR\$	
0411	*1511	SRCH\$	
0412	*1512	SGDR\$	
	*1513	SPAS\$	
0500	*1515	CNAM\$	
0501	*1516	COMI\$	
*0502	*1517	RDTK\$	
*0505	*1520	REST\$	
0506	*1521	RESU\$	
*0507	*1522	SAVE\$	
*0510	*1523	COMO\$	
*0511	*1524	ERKL\$	
*0512	*1525	RDLIN\$	
*0513	*1526	WTLIN\$	
*0514			
*0515			
0516			
0517			



## ERROR MESSAGES AND CODES (SYSCOM&gt;ERRD.F)

E\$EOF=	1	END OF FILE	PE	
E\$BOF=	2	BEGINNING OF FILE	PG	
E\$UNOP=	3	UNIT NOT OPEN	PD,SD	06)
E\$UIUS=	4	UNIT IN USE	SI	
E\$FIUS=	5	FILE IN USE	SI	
E\$BPAR=	6	BAD PARAMETER	SA	6)
E\$NATT=	7	NO UFD ATTACHED	SL,AL	
E\$DFDL=	8	UFD FULL	SK	
E\$DKFL=	9	DISK FULL	DJ	0)
E\$NRIT=	10	NO RIGHT	SX	
E\$FDEL=	11	FILE OPEN ON DELETE	SD	
E\$NTUD=	12	NOT A UFD	AR	
E\$NTSD=	13	NOT A SEGDIR	--	
E\$DIRE=	14	IS A DIRECTORY	--	
E\$FNIF=	15	(FILE) NOT FOUND	SH,AH	
E\$FNIS=	16	(FILE) NOT FOUND IN SEGDIR	SQ	
E\$BNAM=	17	ILLEGAL NAME	CA	
E\$EXST=	18	ALREADY EXISTS	CZ	
E\$DNTE=	19	DIRECTORY NOT EMPTY	--	
E\$SHUT=	20	BAD SHUTDN (FAM ONLY)	BS	
E\$DISK=	21	DISK I/O ERROR	WB	
E\$BDAM=	22	BAD DAM FILE (FAM ONLY)	SS	
E\$PTRM=	23	PTR MISMATCH (FAM ONLY)	PC,DC,AC	
E\$BPAS=	24	BAD PASSWORD (FAM ONLY)	AN	
E\$BCOD=	25	BAD CODE IN ERRVEC	--	
E\$BTRN=	26	BAD TRUNCATE OF SEGDIR	--	
E\$OLDP=	27	OLD PARTITION	--	
E\$BKEY=	28	BAD KEY	--	
E\$BUNT=	29	BAD UNIT NUMBER	--	
E\$BSUN=	30	BAD SEGDIR UNIT	SA	
E\$SUNO=	31	SEGDIR UNIT NOT OPEN	--	
E\$NMLG=	32	NAME TOO LONG	--	
E\$SDER=	33	SEGDIR ERROR	SQ	
E\$BUFD=	34	BAD UFD	--	
E\$BFTS=	35	BUFFER TOO SMALL	--	
E\$FITB=	36	FILE TOO BIG	--	
E\$NULL=	37	(NULL MESSAGE)	--	
E\$IREM=	38	ILL REMOTE REF	--	
E\$DVIU=	39	DEVICE IN USE	--	
E\$RLDN=	40	REMOTE LINE DOWN	--	
E\$FUIU=	41	ALL REMOTE UNITS IN USE	--	
E\$DNS=	42	DEVICE NOT STARTED	--	
E\$TMUL=	43	TOO MANY UFD LEVELS	--	
E\$FBST=	44	FAM - BAD STARTUP	--	
E\$BSGN=	45	BAD SEGMENT NUMBER	--	
E\$FIFC=	46	INVALID FAM FUNCTION CODE	--	
E\$IMRU=	47	MAX REMOTE USERS EXCEEDED	--	
E\$NASS=	48	DEVICE NOT ASSIGNED	--	
E\$BFSV=	49	BAD FAM SVC	--	
E\$SEMO=	50	SEM OVERFLOW	--	
E\$NTIM=	51	NO TIMER	--	
E\$FABT=	52	FAM ABORT	--	
E\$FONC=	53	FAM OP NOT COMPLETE	--	

10 APPENDICESASCII CHARACTER SET

F => Valid file name char  
 R => Rsrved cmd line char  
 ^ => ctrl key depressed

8-Bit Octal Code Char		Code in Left Byte	8-Bit Octal Code Char		Code in Left Byte
200	NUL	1000	240	Sp	1200
201	SOH ^A	1004	241	!	1204 R
202	STX ^B	1010	242	"	1210 R
203	ETX ^C	1014	243	#	1214 F
204	EOT ^D	1020	244	\$	1220 F
205	ENQ ^E	1024	245	%	1224 R
206	ACK ^F	1030	246	&	1230 FR
207	BEL ^G	1034	247	'	1234 R
210	BS ^H	1040	250	(	1240 R
211	HT ^I	1044	251	)	1244 R
212	NL ^J	1050	252	*	1250 F
213	VT ^K	1054	253	+	1254
214	FF ^L	1060	254	,	1260 R
215	CR ^M	1064	255	-	1264 FR
216	RRS ^N	1070	256	.	1270 F
217	BRS ^O	1074	257	/	1274 F
220	RCP ^P	1100	260	0	1300 F
221	RHT ^Q	1104	261	1	1304 F
222	HLF ^R	1110	262	2	1310 F
223	RVT ^S	1114	263	3	1314 F
224	HLR ^T	1120	264	4	1320 F
225	NAK ^U	1124	265	5	1324 F
226	SYN ^V	1130	266	6	1330 F
227	ETB ^W	1134	267	7	1334 F
230	CAN ^X	1140	270	8	1340 F
231	EM ^Y	1144	271	9	1344 F
232	SUB ^Z	1150	272	:	1350 R
233	ESC ^UP-K	1154	273	;	1354 R
234	FS ^UP-L	1160	274	<	1360
235	GS ^UP-M	1164	275	=	1364 R
236	RS ^UP-N	1170	276	>	1370
237	US ^UP-O	1174	277	?	1374

8-Bit Octal Code Char		Code in Left Byte	8-Bit Octal Code Char		Code in Left Byte
300		1400 R	340		1600 R
301	A	1404 F	341	a	1604
302	B	1410 F	342	b	1610
303	C	1414 F	343	c	1614
304	D	1420 F	344	d	1620
305	E	1424 F	345	e	1624
306	F	1430 F	346	f	1630
307	G	1434 F	347	g	1634
310	H	1440 F	350	h	1640
311	I	1444 F	351	i	1644
312	J	1450 F	352	j	1650
313	K	1454 F	353	k	1654
314	L	1460 F	354	l	1660
315	M	1464 F	355	m	1664
316	N	1470 F	356	n	1670
317	O	1474 F	357	o	1674
320	P	1500 F	360	p	1700
321	Q	1504 F	361	q	1704
322	R	1510 F	362	r	1710
323	S	1514 F	363	s	1714
324	T	1520 F	364	t	1720
325	U	1524 F	365	u	1724
326	V	1530 F	366	v	1730
327	W	1534 F	367	w	1734
330	X	1540 F	370	x	1740
331	Y	1544 F	371	y	1744
332	Z	1550 F	372	z	1750
333	[	1554 R	373	{	1754 R
334	\	1560 R	374		1760
335	]	1564 R	375	}	1764 R
336	^	1570 R	376	~	1770 R
337	_	1574 F	377	DEL	1774

## CONVERSION TABLES

OCTAL DECIMAL CONVERSION TABLE

0	0	1	2	3	4	5	6	7
10	8	9	10	11	12	13	14	15
20	16	17	18	19	20	21	22	23
30	24	25	26	27	28	29	30	31
40	32	33	34	35	36	37	38	39
50	40	41	42	43	44	45	46	47
60	48	49	50	51	52	53	54	55
70	56	57	58	59	60	61	62	63
100	64	65	66	67	68	69	70	71
110	72	73	74	75	76	77	78	79
120	80	81	82	83	84	85	86	87
130	88	89	90	91	92	93	94	95
140	96	97	98	99	100	101	102	103
150	104	105	106	107	108	109	110	111
160	112	113	114	115	116	117	118	119
170	120	121	122	123	124	125	126	127
200	128	129	130	131	132	133	134	135
210	136	137	138	139	140	141	142	143
220	144	145	146	147	148	149	150	151
230	152	153	154	155	156	157	158	159
240	160	161	162	163	164	165	166	167
250	168	169	170	171	172	173	174	175
260	176	177	178	179	180	181	182	183
270	184	185	186	187	188	189	190	191
300	192	193	194	195	196	197	198	199
310	200	201	202	203	204	205	206	207
320	208	209	210	211	212	213	214	215
330	216	217	218	219	220	221	222	223
340	224	225	226	227	228	229	230	231
350	232	233	234	235	236	237	238	239
360	240	241	242	243	244	245	246	247
370	248	249	250	251	252	253	254	255
400	256	257	258	259	260	261	262	263
410	264	265	266	267	268	269	270	271
420	272	273	274	275	276	277	278	279
430	280	281	282	283	284	285	286	287
440	288	289	290	291	292	293	294	295
450	296	297	298	299	300	301	302	303
460	304	305	306	307	308	309	310	311
470	312	313	314	315	316	317	318	319
500	320	321	322	323	324	325	326	327
510	328	329	330	331	332	333	334	335
520	336	337	338	339	340	341	342	343
530	344	345	346	347	348	349	350	351
540	352	353	354	355	356	357	358	359

0	0	1	2	3	4	5	6	7
550	360	361	362	363	364	365	366	367
560	368	369	370	371	372	373	374	375
570	376	377	378	379	380	381	382	383
600	384	385	386	387	388	389	390	391
610	392	393	394	395	396	397	398	399
620	400	401	402	403	404	405	406	407
630	408	409	410	411	412	413	414	415
640	416	417	418	419	420	421	422	423
650	424	425	426	427	428	429	430	431
660	432	433	434	435	436	437	438	439
670	440	441	442	443	444	445	446	447
700	448	449	450	451	452	453	454	455
710	456	457	458	459	460	461	462	463
720	464	465	466	467	468	469	470	471
730	472	473	474	475	476	477	478	479
740	480	481	482	483	484	485	486	487
750	488	489	490	491	492	493	494	495
760	496	497	498	499	500	501	502	503
770	504	505	506	507	508	509	510	511
1000	512	513	514	515	516	517	518	519
1010	520	521	522	523	524	525	526	527
1020	528	529	530	531	532	533	534	535
1030	536	537	538	539	540	541	542	543
1040	544	545	546	547	548	549	550	551
1050	552	553	554	555	556	557	558	559
1060	560	561	562	563	564	565	566	567
1070	568	569	570	571	572	573	574	575
1100	576	577	578	579	580	581	582	583
1110	584	585	586	587	588	589	590	591
1120	592	593	594	595	596	597	598	599
1130	600	601	602	603	604	605	606	607
1140	608	609	610	611	612	613	614	615
1150	616	617	618	619	620	621	622	623
1160	624	625	626	627	628	629	630	631
1170	632	633	634	635	636	637	638	639
1200	640	641	642	643	644	645	646	647
1210	648	649	650	651	652	653	654	655
1220	656	657	658	659	660	661	662	663
1230	664	665	666	667	668	669	670	671
1240	672	673	674	675	676	677	678	679
1250	680	681	682	683	684	685	686	687
1260	688	689	690	691	692	693	694	695
1270	696	697	698	699	700	701	702	703
1300	704	705	706	707	708	709	710	711
1310	712	713	714	715	716	717	718	719
1320	720	721	722	723	724	725	726	727
1330	728	729	730	731	732	733	734	735
1340	736	737	738	739	740	741	742	743
1350	744	745	746	747	748	749	750	751
1360	752	753	754	755	756	757	758	759
1370	760	761	762	763	764	765	766	767
1400	768	769	770	771	772	773	774	775
1410	776	777	778	779	780	781	782	783
1420	784	785	786	787	788	789	790	791
1430	792	793	794	795	796	797	798	799
1440	800	801	802	803	804	805	806	807

0	0	1	2	3	4	5	6	7
1450	808	809	810	811	812	813	814	815
1460	816	817	818	819	820	821	822	823
1470	824	825	826	827	828	829	830	831
1500	832	833	834	835	836	837	838	839
1510	840	841	842	843	844	845	846	847
1520	848	849	850	851	852	853	854	855
1530	856	857	858	859	860	861	862	863
1540	864	865	866	867	868	869	870	871
1550	872	873	874	875	876	877	878	879
1560	880	881	882	883	884	885	886	887
1570	888	889	890	891	892	893	894	895
1600	896	897	898	899	900	901	902	903
1610	904	905	906	907	908	909	910	911
1620	912	913	914	915	916	917	918	919
1630	920	921	922	923	924	925	926	927
1640	928	929	930	931	932	933	934	935
1650	936	937	938	939	940	941	942	943
1660	944	945	946	947	948	949	950	951
1670	952	953	954	955	956	957	958	959
1700	960	961	962	963	964	965	966	967
1710	968	969	970	971	972	973	974	975
1720	976	977	978	979	980	981	982	983
1730	984	985	986	987	988	989	990	991
1740	992	993	994	995	996	997	998	999
1750	1000	1001	1002	1003	1004	1005	1006	1007
1760	1008	1009	1010	1011	1012	1013	1014	1015
1770	1016	1017	1018	1019	1020	1021	1022	1023

## POWERS OF TWO

## POSITIVE POWERS OF TWO

n	2
1	2
2	4
3	8
4	16
5	32
6	64
7	128
8	256
9	512
10	1024
11	2048
12	4096
13	8192
14	16384
15	32768
16	65536
17	131072
18	262144
19	524288
20	1048576
21	2097152
22	4194304
23	8388608
24	16777216
25	33554432
26	67108864
27	134217728
28	268435456
29	536870912
30	1073741824
31	2147483648
32	4294967296
33	8589934592
34	17179869184
35	34359738368
36	68719476736
37	137438953472
38	274877906944
39	549755813888
40	1099511627776
41	2199023255552
42	4398046511104
43	8796093022208
44	17592186044416
45	35184372088832
46	70368744177664
47	140737488355328
48	281474976710656

## NEGATIVE POWERS OF TWO

n	2
0	1.0
1	0.5
2	0.25
3	0.125
4	0.0625
5	0.03125
6	0.01562 5
7	0.00781 25
8	0.00390 625
9	0.00195 3125
10	0.00097 65625
11	0.00048 82812 5
12	0.00024 41406 25
13	0.00012 20703 125
14	0.00006 10351 5625
15	0.00003 05175 78125
16	0.00001 52587 89062 5
17	0.00000 76293 94531 25
18	0.00000 38146 97265 625
19	0.00000 19073 48632 8125
20	0.00000 09536 74316 40625
21	0.00000 04768 37158 20312 5
22	0.00000 02384 18579 10156 25
23	0.00000 01192 09289 55078 125
24	0.00000 00596 04644 77539 0625
25	0.00000 00298 02322 38769 53125
26	0.00000 00149 01161 19384 76562 5
27	0.00000 00074 50580 59692 38281 25
28	0.00000 00037 25290 29846 19140 625
29	0.00000 00018 62645 14923 09570 3125
30	0.00000 00009 31322 57461 54785 15625
31	0.00000 00004 65661 28730 77392 57812
32	0.00000 00002 32830 64356 28696 28906
33	0.00000 00001 16415 32182 69348 14453
34	0.00000 00000 58207 66091 34674 07226
35	0.00000 00000 29103 83045 67337 03613
36	0.00000 00000 14551 91522 83668 51806
37	0.00000 00000 07275 95761 41834 25903
38	0.00000 00000 03637 97880 70917 12951
39	0.00000 00000 01818 98940 35458 56475
40	0.00000 00000 00909 49470 17629 28237
41	0.00000 00000 00454 74735 08864 64118
42	0.00000 00000 00227 37367 54432 32059
43	0.00000 00000 00113 68683 77216 16029
44	0.00000 00000 00056 84341 88608 08014

11 GLOSSARY

## ALTRIN

Alternate return.

## BUFF

Buffer (usually INTEGER\*2 array).

## AP

argument pointer.

## code

a value returned by a routine indicating either the success of or the reason for failure to accomplish the requested action.

## command

a program called from command level. (See internal command and external command, below.)

## command level

the process state in which input lines are interpreted by Primos as commands. A process is at command level when a user logs in and when a command either completes, encounters an error, or stops after a quit signal is issued.

## crash

an unplanned interruption of system availability caused by problems in hardware and/or software.

## CRASH ADDR

displacement in hardware register save area (pointed to by R37).

## CRS

Current register set.

## DAM file

a direct access method file.

## directory

a catalog of files and other subordinate directories. See MFD, UFD, and segment directory.

## DSW

diagnostic status word.

## DTAR

descriptor table address register.

## DVNO

physical device number.

## ECB

Entry Control Block.

## external command

a command that executes in user address space.

## FADDRH

fault address, high.

## FADDRL

fault address, low.

## fault

a hardware or software condition that causes system failure.

## FCODE

fault code.

## file

a sam or dam file.

## filename

a name given to an item in a directory.

## FUNIT

A file system unit number 0-'21.

## internal command

a command that executes in the address space occupied by the Primos operating system.

## interrupt

A signal received from a device in the external world (including clocks) indicating that the device either needs to be serviced or has completed an operation.

## LB

linkage base register.

## login name

A 6-character name by which each logged-in user is known to PRIMOS.

## LSB

Least Significant Bit.

## MFD

master file directory. An MFD contains information about each UFD on the disk.

## MSB

Most Significant Bit.

## NODE

the name of a system connected to PRIMENET.

NW  
Number of words.

non-owner, NPASS  
Non-owner password.

owner, OPASS  
Owner password.

page  
a 1024 16-bit word block of data within a segment.

page control  
the routines that manage the transfer of pages between secondary storage and main memory frames.

paged address space  
nonvisible memory; allocation of physical memory.

password  
a character string supplied by the user that controls his access to various files and directories. See owner and non-owner.

PB  
procedure base register.

PBH  
procedure base register, high side.

PBL  
procedure base register, low side.

PCB  
see process control block.

PDEV  
physical device number.

physical volume  
a disk pack.

PMNT  
page map entry.

pointer  
an address value either 16-bits or 32-bits in length.

procedure control block  
64-word block describing current state of a process.

process  
an address space and an execution point. Each logged-in user has his own process.

register file  
128 32-bit registers partitioned into 4 32-register blocks. The first block is reserved for microcode use, the second block is used for DMA channels, the third and fourth blocks are process register sets.

RFIL, RFILE  
Register file address.

ring  
a level of privilege at which programs execute. Supervisor programs run in ring 0; most user programs run in ring 3.

SAM file  
a sequential access method file.

SB  
stack base pointer.

SDW  
Segment Descriptor Word.

segment directory  
a directory that contains nothing but pointers to the first record of each file cataloged in it.

semaphore  
a special purpose integer variable allocated in the universe in which the processes are embedded, to perform explicit mutual synchronization of parallel sequential processes.

segmented address space  
visible memory; allocation of user's data/procedures.

stack  
a pushdown list where active procedures maintain private regions used for temporary variables.

STATV  
A three word vector used by the T\$xxxx routines. STATV(1) set to 0 when operation completes, STATV(2) = device status, STATV(3) = number words transferred.

TRAP  
An asynchronous interruption of sequential microcode execution.

treename, tree  
a character string that specified a file by its position in the file system hierarchy. Valid treenames are of the form:

[<ldev>]ufdname[ password][>ufdname ...]>filename

Use of < and > in a treename are literal and must be typed as shown. If the treename includes embedded blanks and is entered at PRIMOS command level, it should be surrounded by apostrophes.

UFD

User File Directory. An UFD contains information about the location and content of each file cataloged in it.

UNIT

See FUNIT.

wired page

a page that remains in main memory at all times.

word

a unit of information that is 16 bits in length.

XB

temporary base register.



12 INDEX

Abbreviations 149  
 Abort Flags 111  
 ABSAVE 111  
 Access Controls 14  
 Access Violation 111  
 Acronyms 149  
 ADDISK Command 17  
 Addresses (device) 101  
 ALTVAl 111  
 AMLC 102  
 AMLC Command 17  
 AMLC Process 10  
 AMLCI 96  
 AP 3  
 Argument Pointer 3  
 ASCII 141  
 ASR Control Words 102  
 ASR Rate 94  
 ASRCWD Command 17  
 ASSIGN Command 18  
 ATCH\$\$ 121  
 ATTAC\$ 121  
 ATTACH 121  
 ATTACH Command 18  
 AVAIL Command 19  
 B-prime 105  
 BASIC Command 19  
 BASICV Command 19  
 BASINP Command 19  
 BAUD Rate 94  
 BDMEM 96  
 BINARY Command 19  
 BOOT 93  
 Boot Terminal 94  
 BOOT0 96  
 BREAK\$ 121  
 CLIN 122  
 CHAP Command 19  
 Character Set 141  
 Checks 3  
 Clock Process 10  
 CLOSE Command 20  
 CMPF Command 20  
 CMPRES Command 20  
 CMREAD 122  
 CNAM\$\$ 122  
 CNAME 122  
 CNAME Command 20  
 CNAME\$ 122  
 CNIN\$ 122  
 CNVIMA Command 20  
 COBOL Command 21  
 Cold Start 95  
 COMANL 122  
 COMI\$\$ 123  
 COMIN\$ 123  
 COMINP 123  
 COMINP Command 22  
 Command Input 22  
 Command Output 22  
 Commands 17  
 Commons 111  
 COMOS\$ 123  
 COMOUTPUT Command 22  
 CONCAT Command 22  
 Concealed Stack 4  
 Condition Code 7  
 CONECT 123  
 CONFIG Command 95  
 Console Rate 94  
 Conversion Tables 143  
 COPY Command 23  
 CPMP Command 23  
 CPU 3  
 CREAT\$ 124  
 CREATE\$ 124  
 CREATE Command 23  
 CRMP Command 23  
 CRSER Command 23  
 CUFD 119  
 CX Command 24  
 D\$INIT 124  
 DATE Command 24  
 DEFERA 112  
 DEFKIL 112  
 DELAY Command 24  
 DELETE Command 24  
 DELSEG Command 24  
 Device Addresses 101  
 DISALM 111  
 DISCON 124  
 Disk 103  
 Disk Addresses 104  
 Disk Errors 105  
 Diskette 106  
 DISKS Command 25  
 DLOGOT 112  
 DMC 107  
 DMQ 5, 107  
 DMT 107  
 DMX 107  
 DONSTP 112  
 DSKRAT 65  
 DSW 4  
 DTAR 5  
 Dump (of PRIMOS IV) 98  
 DUPLX\$ 124  
 DVNO 104  
 ECB 6  
 ED command 25

EDB Command 28  
 ELIGTS Command 29  
 Entry Control Block 6  
 ERKL\$\$ 125  
 ERRD.F 139  
 Error Codes 111, 139  
 ERRPR\$ 125  
 ERRRTN 125  
 ERRSET 125  
 ERRVEC 111  
 EXIT 125  
 EXPAND Command 29  
 External Commands 17  
 FADDR 6  
 FAMSVC 125  
 Faults 6  
 FCODE 6  
 FIGCOM 112  
 File System 65  
 FILMEM Command 29  
 FILVER Command 29  
 FIXRAT Command 29  
 Floppy 106  
 FORCEW 126  
 FIN Command 30  
 FUTIL Command 32  
 GETCON 126  
 GETERR 126  
 GINFO 126  
 Glossary 149  
 GPAS\$\$ 127  
 GPASS\$ 127  
 Halt Procedures 96  
 Halts 96  
 HMAP 8  
 HOMUFD 119  
 HPSD Command 32  
 I/O 101  
 IFLITB 96  
 Illegal Page Ref 111  
 Illegal Segno 111  
 Indirect Pointer 6  
 INPUT Command 33  
 Instruction Set 71  
 Internal Commands 17  
 INIRT 96  
 IP 6  
 IPAGE 96  
 IPC Process 10  
 Keys 7  
 LCKCOM 116  
 LISTF Command 33  
 LISTING Command 33  
 LMAP 8  
 LOAD Command 33  
 Locks 116  
 LOGALM 111  
 LOGIN Command 34  
 LOGNAM 119  
 LOGOUT 112  
 LOGOUT Command 34  
 LOGPRT Command 35  
 LOOK Command 35  
 LOUTQM 112  
 Low Memory 14  
 LS Command 35  
 LWORD 124  
 Machine Checks 3  
 MACHK Command 36  
 MAGNET Command 37  
 MAGRST Command 38  
 MAGSAV Command 39  
 Magtape 108  
 Magtape Dump 98  
 Magtape Status 108  
 MAIL Command 40  
 MAKE Command 40  
 MAXSCH Command 41  
 MAXUSR Command 41  
 MCHK 96  
 MDL Command 42  
 MEMH2 96  
 Memory Display 97  
 Memory Map 116  
 Memory Parity 97  
 Memory Scan 98  
 MEMPA 96  
 MESSAGE Command 42  
 MINALM 111  
 MMAP 116  
 MMOD 96  
 Modals 7  
 MP2 Process 10  
 MPC Process 10  
 MRGF Command 43  
 MT1ALM 111  
 MT2ALM 111  
 NETALM 111  
 NETLNK 127  
 NETWAT 127  
 NLGPRT 112  
 No Avail Segments 111  
 NTSTAT 127  
 NUMBER Command 43  
 Octal/Decimal 143  
 OPEN Command 43  
 OPRPRI Command 43  
 OPTION-A 94, 102  
 OUTALM 111  
 P400/P500 3  
 Page Maps 8  
 PAGFB 96  
 Panel 8, 97  
 Parity 97

PASSWD Command 43  
 PCB 9  
 PCBs 10  
 PHANTOM Command 44  
 PIO 109  
 PM Command 44  
 PMA Command 44  
 PMA Errors 45  
 Pointer Fault 111  
 Powers of Two 146  
 PPA 10  
 PPB 10  
 PRERR 127  
 PRERR Command 46  
 PRI500 112  
 PRIMOS IV 111  
 PRMPC Command 46  
 Process Control Block 9  
 Programmed I/O 109  
 PROTECT Command 46  
 PRSER Command 46  
 PRVER Command 46  
 PRWF\$\$ 128  
 PRWFIL 128  
 PRWFL\$ 128  
 PSD Command 46  
 PIBOOT Command 49  
 PTCPY Command 49  
 PTUSEG 116  
 PUDCOM 117  
 PUSS Command 49  
 RDN\$\$ 129  
 RDENT\$ 129  
 RDLIN 130  
 RDLIN\$ 130  
 RDTK\$\$ 130  
 RDTKN\$ 130  
 Ready List 10  
 RECEIV 131  
 Record Headers 65  
 RECYCL 131  
 REFL0 96  
 Register Display 97  
 Register File 11  
 Registers 11  
 REST\$\$ 131  
 RESTO\$ 131  
 RESTOR 131  
 RESTORE Command 49  
 RESU\$\$ 131  
 RESUM\$ 131  
 RESUME 131  
 RESUME Command 49  
 RJCON 131  
 RMCFO 96  
 RPG Command 50  
 RREC 131  
 RRECL 131  
 RSAVE Format 13  
 RUNOFF Command 51  
 RWLOCK 112  
 SATR\$\$ 132  
 SATTR\$ 132  
 SAVE 132  
 SAVE Command 54  
 Save Mask 13  
 SAVE\$ 132  
 SAVE\$\$ 132  
 SAVER Command 54  
 SDW 14  
 SEARC\$ 134  
 SEARCH 134  
 Sector 0 14  
 SEG Command 55  
 Seg. Descriptor Word 14  
 SEGDR\$ 133  
 Segment Directory 69  
 Segments 118  
 Segments (PRIMOS IV) 118  
 SEM\$DR 132  
 SEM\$NF 132  
 SEM\$TN 133  
 SEM\$TS 133  
 SEM\$WT 133  
 Semaphore 15  
 Semaphores 119  
 SEMCOM 119  
 SETIME Command 57, 95  
 SFRWLK Command 57  
 SGDR\$\$ 133  
 SHARE Command 58  
 SHUTDN Command 58  
 SIZE Command 58  
 SLEEP\$ 134  
 SLIST Command 58  
 SMLALM 111  
 SMLC Process 10  
 SOC 94, 102  
 SORT Command 58  
 SPASS\$ 134  
 SPASS\$ 134  
 SPOOL Command 59  
 SRCH\$\$ 134  
 Stack (concealed) 4  
 Stack Extension 15  
 Stack Frame 15  
 Stack Root 15  
 START Command 59  
 STARTUP Command 60  
 STATUS Command 60  
 Storage Module 106  
 SVC Calling Sequences 121  
 SVC Information 121  
 SVC Interlude 119

SVC Numbers 138  
 SVCF0 96  
 SVCSW Command 60  
 T\$AMLC 135  
 T\$CMPC 135  
 T\$LMPC 135  
 T\$MT 135  
 T\$PMPC 135  
 T\$SLC 136  
 T\$VG 135  
 TA comand 60  
 Tape Dump 98  
 TAPXAM Command 61  
 TERM Command 62  
 Terminal Rate 94  
 TIMDAT 136  
 TIME Command 62  
 TMOALM 111  
 TNOU 136  
 TNOUA 136  
 TRAMLC Command 62  
 TRNMIT 136  
 TSEALM 111  
 UFD Entry 67  
 UFD Header 67  
 UII Requirements 33  
 UNASSIGN Command 62  
 Undefined Gate 111  
 UNITAB 119  
 UNLINK 136  
 UPCASE Command 62  
 USERS Command 62  
 USRASR Command 63  
 VERSATEC Process 10  
 VERSIO 112  
 VPSD Command 63  
 VQUTM 120  
 VRTSSW Command 63  
 Wait List 15  
 Warm Start 99  
 WARMH 96, 99  
 WREC 137  
 WRECL 137  
 WRMALM 111  
 WTLIN 137  
 WTLIN\$ 137  
 X.CONCAT 22  
 X.MAIL Command 40