

S800

20 MHz 386 AT® Compatible



An outstanding combination of 386 power, performance and value, the S800 is ideal as a stand-alone system, powerful workstation, or a fast, low cost network fileserver.

Fast, 20MHz operating speed (page mode operation, zero wait state) and 1MB of RAM.

Full-featured standard equipment includes a 1.2MB 5 1/4" floppy disk drive, a 1.44MB 3 1/2" floppy drive, eight expansion slots, a 101-key enhanced keyboard, two built-in serial ports, a parallel port and a 240 watt power supply.

Additional data storage is available with three 5 1/4" half-height drive bays, two internally accessible.

Supports all standard graphic display interfaces by installing an optional CGA, EGA or VGA adapter.

Specifications

S800

| | |
|-------------------------------|---|
| Microprocessor | 80386 |
| Operating Speed | 10MHz or 20MHz, zero wait state, keyboard selectable |
| On-Board RAM | 1MB; expandable to 8MB using SIMM's |
| Read Only Memory (ROM) | 64KB; EPROM |
| Expansion Slots | Eight; one 32-bit, six 16-bit, one 8-bit; all available |
| Built-In Ports | Two serial communication ports, one parallel printer port |
| Clock/Calendar | Long-life lithium battery backup |
| Numeric Coprocessor | 80387; socket only |
| Data Storage | One 1.2MB 5 1/4" floppy disk drive and one 1.44MB 3 1/2" floppy disk drive; three additional drive bays available |
| Floppy Disk Controller | Built-in on motherboard |
| Video Display Adapter | Optional; compatible with VGA, EGA, CGA, HGC, MDA |
| Hardware Security | Keylock disables keyboard |
| Hardware Reset | Push button on front panel |
| Power Supply | 240 Watts |
| Power Requirements | 115VAC, 60Hz or 230VAC, 50Hz |
| Operating Temperature | 50°F to 113°F (10°C to 45°C) |
| Keyboard | 101-key, enhanced AT compatible |
| Cabinet Dimensions | 20.9" x 6.6" x 16.8" (W x H x D) |
| Weight | 34 lbs. |
| Operating System | MS-DOS; GW-BASIC |
| 12-Month Warranty | |



Samsung Information Systems America, Inc.
3655 North First Street
San Jose, CA 95134
Telephone: (800) 446-0262
Fax: (408) 434-5653

AUTHORIZED RESELLER

©1989 Samsung Information Systems America, Inc.
In order to assure our customers of the best possible product, Samsung reserves the right to change, improve or enhance these specifications without prior notice.
MS-DOS and GW-BASIC are registered trademarks of Microsoft Inc. CAD graphic courtesy of DesignCAD 3-D.
This device complies with FCC Class B.
Printed in USA. ACR1089