

FEATURES

Compaq ProLiant 5000

Compaq ProLiant 5000 6/166

Compaq ProLiant 5000 6/200

System Unit

Microprocessor	Two 166-MHz Intel Pentium® Pro processors	200-MHz Intel Pentium Pro processor
Upgradability	Processor upgradable to future Pentium Pro processors	Processor upgradable to future Pentium Pro processors
Cache	512-KB high-speed 4-way set associative per processor	256-KB high-speed 4-way set associative (Model 1) 512-KB high-speed 4-way set associative (Model 1X, 2) 1-MB high-speed 4-way set (associative option kit)
Architecture	ProLiant 5000 System Architecture	ProLiant 5000 System Architecture
Standard Processor Sockets	2 (1 available) Model 1 4 (2 available) Model 2	2 (1 available in Model 1) 4 (3 available in Models 1X) 4 (2 available in Model 2)
Optional Processor Sockets	2 (1 available) Model 1	2 via the ProLiant 5000 Dual Pentium Pro processor board (Model 1)
Expansion Slots		4 (2 available) in Models 1X and 2
I/O (Total)	8 (7 available, 6 in array models)	8
PCI	7 (6 available, 5 in array models)	7 (6 available)
EISA	3	3
Shared PCI/EISA	2	2
RAM		
Standard	64 MB	64 MB (Model 1, 1S) 128 MB (Models 1X, 2 and 2S)
Maximum	4 GB	4 GB

Network Interface Controllers

Serial/Parallel Interface Board	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-SC Controller	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC Controller	Optional	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC Controller	Optional	Optional
Netelligent 100 FDDI PCI SAS UTP Controller	Optional	Optional
NetFlex-3/P Controller		
100Base-TX UTP Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100VG-AnyLAN UTP Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100Base-FX Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
Netelligent 10 T/2 PCI UTP/Coax Controller	Optional	Optional
Netelligent 10 T PCI UTP Controller	Optional	Optional
Netelligent 10/100 TX PCI UTP Controller	Standard	Standard
Netelligent 16/4 TR PCI IBM UTP/STP Controller	Optional	Optional
Netelligent 4/16 TR PCI UTP/STP Controller	Optional	Optional
Netelligent Dual 10/100 TX PCI UTP Controller	Optional	Optional
AUI to BNC Transceiver	Optional	Optional

	Compaq ProLiant 5000 6/166	Compaq ProLiant 5000 6/200
Network Interface Controllers <i>(cont'd)</i>		
Compaq 336 ISA Fax Modem	Optional	Optional
Compaq Netelligent 56K ISA Fax Modem	Optional	Optional
Server Management		
Compaq Insight Manager	Standard	Standard
Compaq Remote Insight Board	Optional	Optional
Automatic Server Recovery	Standard	Standard
Server Health Logs	Standard	Standard
Recovery Server Option	Optional	Optional
Storage		
Diskette Drives	1.44-MB	1.44-MB
CD-ROM Drives		
Standard	8X CD-ROM Internal	8X CD-ROM Internal
Optional	8X CD-ROM Internal	8X CD-ROM Internal
Hard Drives		
Standard	—	—
Optional	2.1-GB, 4.3-GB, 9.1-GB and 18.2-GB Pluggable Wide-Ultra SCSI-3; 4.3-GB and 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm	2.1-GB, 4.3-GB, 9.1-GB and 18.2-GB Pluggable Wide-Ultra SCSI-3; 4.3-GB and 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm
External Storage		
ProLiant Storage System	Optional	Optional
ProLiant Storage System/U1 and /U2	Optional	Optional
SCSI Storage Expander	Optional	Optional
Maximum Storage Capacity		
Internal	72.8 GB	72.8 GB
External	1.5 TB (with 18.2-GB drives)	1.5 TB (with 18.2-GB drives)
CD-Storage System		
Tower	Optional	Optional
Tape Drives		
Optional	4/8-GB SLR, 2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, Internal TurboDAT AutoLoader, Internal 15/30-GB DLT, 35/70-GB DLT, DLT Tape Array II, DLT Cartridge Library Model 1530-1 ¹ , DLT 15 Cartridge Library Models 3570-1 and 3570-2	4/8-GB SLR, 2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, Internal TurboDAT AutoLoader, Internal 15/30-GB DLT, 35/70-GB DLT, DLT Tape Array II, DLT Cartridge Library Model 1530-1 ¹ , DLT 15 Cartridge Library Models 3570-1 and 3570-2
Controllers		
Standard	Integrated 32-Bit Fast-Wide SCSI-2	Integrated 32-Bit Fast-Wide SCSI-2
Optional	SMART-2/E Array, SMART-2DH Array, Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3	SMART-2/E Array, SMART-2DH Array, Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3

	Compaq ProLiant 5000 6/166	Compaq ProLiant 5000 6/200
Interfaces		
Parallel	1	1
Serial	2	2
Pointing Device (mouse)	1	1
Graphics	1	1
Keyboard	1	1
External Fast-Wide SCSI-2	1	1
Network		
RJ-45	1	1
BNC	Optional	Optional
Graphics		
Integrated 1024 x 768 Video System	Standard	Standard
Monitors		
V55 Color	Optional	
V75 Color	Optional	
V90 Color	Optional	
P50 Color	Optional	
P75 Color	Optional	
P110 Color	Optional	
P1610 Color	Optional	
TFT450 Flat Panel Color Monitor	Optional	
TFT500 Flat Panel Color Monitor	Optional	
Keyboard		
Keyboard and Mouse	Standard	Standard
Supported System Software from Compaq		
Compaq Insight Manager	Standard	Standard
Compaq SmartStart	Standard	Standard
Microsoft Windows NT Server 3.51, 4.0	Optional	Optional
Novell NetWare 3.20	Optional	Optional
Novell intraNetWare	Optional	Optional
SCO UnixWare 2.1	Optional	Optional
SCO Open Server Release 3.0	Optional	Optional
SCO OpenServer Release 5	Optional	Optional
IBM OS/2 v2.1x	Optional	Optional
IBM OS/2 Warp 3.0	Optional	Optional
IBM LAN Server 3.0x, 4.0	Optional	Optional
Other Supported System Software		
Microsoft Windows NT Server 4.0	Optional	Optional
Microsoft Windows NT Workstation 3.51	Optional	Optional

Compaq ProLiant 5000 6/166	Compaq ProLiant 5000 6/200
----------------------------	----------------------------

Other Supported System
Software *(cont'd)*

Microsoft BackOffice	Optional	Optional
Novell intraNetWare SFT III	Optional	Optional
SCO Open Desktop v3.0	Optional	Optional
Banyan VINES v5.5x, 6.0	Optional	Optional

¹ Mounts in a standard Compaq rack; for use on a tabletop, requires the Tabletop Conversion Kit (Part #295162-B21). Refer to the Compaq DLT 15 Cartridge Library Model 1530-1 Quickspec for details.