

NAME

`cref` - make cross reference listing

SYNOPSIS

`cref [-acilnostux123] name ...`

DESCRIPTION

Cref makes a cross reference listing of program files in assembler or C format. The files named as arguments in the command line are searched for symbols in the appropriate syntax.

The output report is in four columns:

(1)	(2)	(3)	(4)
symbol	file	see	text as it appears in file
			below

Cref uses either an *ignore* file or an *only* file. If the `-i` option is given, the next argument is taken to be an *ignore* file; if the `-o` option is given, the next argument is taken to be an *only* file. *Ignore* and *only* files are lists of symbols separated by new lines. All symbols in an *ignore* file are ignored in columns (1) and (3) of the output. If an *only* file is given, only symbols in that file appear in column (1). At most one of `-i` and `-o` may be used. The default setting is `-i`. Assembler predefined symbols or C keywords are ignored.

The `-s` option causes current symbols to be put in column 3. In the assembler, the current symbol is the most recent name symbol; in C, the current function name. The `-l` option causes the line number within the file to be put in column 3.

The `-t` option causes the next available argument to be used as the name of the intermediate temporary file (instead of `/tmp/crt??`). The file is created and is not removed at the end of the process.

Options:

a	assembler format (default)
c	C format input
i	use <i>ignore</i> file (see above)
l	put line number in col. 3 (instead of current symbol)
n	omit column 4 (no context)
o	use <i>only</i> file (see above)
s	current symbol in col. 3 (default)
t	user supplied temporary file
u	print only symbols that occur exactly once
x	print only C external symbols
1	sort output on column 1 (default)
2	sort output on column 2
3	sort output on column 3

FILES

<code>/tmp/crt??</code>	temporaries
<code>/usr/lib/aign</code>	default assembler <i>ignore</i> file
<code>/usr/lib/atab</code>	grammar table for assembler files
<code>/usr/lib/cign</code>	default C <i>ignore</i> file
<code>/usr/lib/ctab</code>	grammar table for C files
<code>/usr/lib/crpost</code>	post processor
<code>/usr/lib/upost</code>	post processor for <code>-u</code> option
<code>/bin/sort</code>	used to sort temporaries

SEE ALSO

`as(1)`, `cc(1)`, `xref(1)`

BUGS

Cref inserts "delete" characters into the intermediate temporary file after the eighth character of names which were eight or more characters in the source file.